

# REQUEST FOR PROPOSAL

*ISSUING AGENCY*

*Fannin County Board of Commissioners  
400 West Main St., Suite 100  
Blue Ridge, Georgia 30513  
PHONE: 706-632-2203  
FAX: 706-632-2507*

*ISSUE DATE*

*May 26, 2023*

*PROPOSAL CLOSING DATE*

*Tuesday June 13, 2023*

*PROPOSAL CLOSING TIME*

*3:00 P.M.*

*Commodity*

*Fannin County Fire  
Department Rescue/Pumper  
Project# FC-2023-02*

## **REQUEST FOR PROPOSAL**

THE FANNIN COUNTY BOARD OF COMMISSIONERS IS REQUESTING PROPOSALS FROM QUALIFIED APPARATUS MANUFACTURERS.

PROPOSALS WILL BE RECEIVED BY THE FANNIN COUNTY COMMISSIONER'S OFFICE, 400 W. MAIN ST., STE 100, BLUE RIDGE, GA 30513 UNTIL 3:00 PM LOCAL TIME ON JUNE 13, 2023. LATE PROPOSALS WILL NOT BE CONSIDERED NOR RETURNED. PROPOSALS WILL BE FORMALLY ACCEPTED AND ACKNOWLEDGED AT THE FANNIN COUNTY COMMISSIONER'S OFFICE BY STAFF PERSONNEL.

THE PROPOSAL DOCUMENTS AND SPECIFICATIONS ARE AVAILABLE FOR INSPECTION ON THE FANNIN COUNTY WEBSITE AT [WWW.FANNINCOUNTYGA.COM](http://WWW.FANNINCOUNTYGA.COM) AND AT THE FANNIN COUNTY COMMISSIONER'S OFFICE 400 W. MAIN ST., STE 100, BLUE RIDGE, GA 30513; PHONE 706-632- 2203 OR FAX 706-632-2507

### **RFP DOCUMENTS ARE AVAILABLE AT THE FANNIN COUNTY, GEORGIA WEBSITE:**

[www.fannincountyga.com/fire-department/](http://www.fannincountyga.com/fire-department/)

(LEGAL AD) TO RUN 5/31/23 and 6/7/2023

ALSO TO BE ADVERTISED ON THE COUNTY WEBSITE, THE GEORGIA PROCUREMENT REGISTRY, AND GEORGIA LOCAL ACCESS MARKETPLACE.

**Fannin County Fire Department**

**Specifications**

**For**

**One (1) Custom Rescue Pumper**

# Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes      No**

## INTENT OF SPECIFICATIONS

It shall be the intent of these specifications to provide a complete apparatus equipped as hereinafter and as specified. With a view to obtaining the best results and the most acceptable apparatus for service in the Department, these specifications cover only the general requirements as to the type of construction and tests to which the apparatus must conform, together with certain details as to finish, equipment and appliances with which the successful bidder shall conform. Minor details of construction and materials where not otherwise specified are left to the discretion of the contractor, who shall be solely responsible for the design and construction for all features. The manufacturer shall provide loose equipment only when specified by the customer. The (NFPA) 1901, Standard for Automotive Fire Apparatus, unless otherwise specified as requested by the customer in these specifications, shall prevail.

The apparatus must meet all NFPA, DOT, ICC, AE, SAE, UL, TRA, FMVSS and local state Motor Vehicle Requirements.

It is required that the apparatus be manufactured to current NFPA edition standards, all NFPA equipment (LOOSE EQUIPMENT) not specified in the specifications will not be provided by the contractor.

Bids shall only be considered from companies that have an established reputation in the field of fire apparatus construction that have been in business and construction for a minimum of twenty-five (25) years.

The bidder of the apparatus herein specified; shall be wholly owned (100%) and managed by a Company, Corporation, and/or Parent Company that is wholly based, and permanently resides in the United States of America.

The Company, Corporation, and/or Parent Company and all assets belonging to such; shall be wholly owned and managed (100%) by the entities specified above.

The bidder shall state the location of the manufacturing facility where the apparatus is to be built and the location of the parent company if a subsidiary of a manufacturer.

The bidder shall provide satisfactory evidence of their ability to construct the apparatus specified in the bidders manufacturing facilities.

The bidder's representation shall state the length of time representing the manufacturer of specified apparatus.

Due to the severe service requirements the department will impose on the apparatus as specified, each bidder shall provide a list of at least six (6) departments in which similar apparatus utilizing the brand of chassis proposed have been in service for over one year. This list shall include contact names and phone numbers.

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes      No**

Due to the importance of keeping this vital piece of firefighting apparatus in service with a minimum of downtime, the manufacturer shall maintain a network of service centers with factory-training personnel.

The bid shall be accompanied by a set of "Contractor's Specifications" consisting of a detailed description of the apparatus being furnished under this contract which conform. Computer runoff sheets are not acceptable as "Contractor's Specifications". Item compliance shall be indicated in the "Yes/No" column of each item by all Bidders. Note: Each bidder shall submit their bid in the same sequence as these specifications to allow the department to easily compare. NO EXCEPTIONS

These specifications shall indicate size, type, model and make of all component parts and equipment. NO EXCEPTIONS

### **QUALITY AND WORKMANSHIP**

The design of the Apparatus shall embody the latest approved automotive engineering practices.

The workmanship must be of the highest quality in its respective field. Special consideration will be given to the following points: Accessibility of the various units, which require periodic maintenance, ease of operation (including both pumping and driving) and symmetrical proportions.

Construction shall be rugged and ample safety factors shall be provided to carry loads as specified and to meet both on and off road requirements and to speed conditions as set forth under "Performance tests and requirements".

Welding shall be employed in the assembly of the apparatus in a manner that will not prevent the ready removal of any component part for service or repair, with apparatus bodies of bolt together design not being acceptable.

All steel welding shall follow American Welding Society requirements for AWS D1.1:2012 Structural Welding Code for welding steel structural assemblies. All aluminum welding shall follow American Welding Society requirements for AWS D1.2/D1.2M:2003 Structural Welding Code for any type of structure made from aluminum structural alloys. All sheet metal welding shall follow American Welding Society AWS D9.1M/D9.1:2006 Structural Welding code for Arc/Braze requirements of non-structural materials. All pressure pipe welding shall follow American Society of Mechanical Engineers ASME IX/ ASME B31:2010 requirements to the qualification of procedures in welding and brazing, in accordance with the ASME Boiler and Pressure Vessel Code and the ASME B31 Code for Pressure Piping. Flux core arc welding to use alloy rods, type 7000, American Welding Society AWS standards A5.20-E70T1.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes      No**

**DELIVERY**

The bidder shall provide the number of calendar days from the date the bid is awarded to the delivery of the completed unit. **Not exceed 460 days No Exception**

A qualified delivery engineer representing the contractor shall deliver the apparatus and instruct the Fire Department personnel in the proper operation, care and maintenance of the equipment delivered.

To ensure proper break-in of all components while still under warranty, the apparatus shall be delivered under its own power. The unit will remain insured by the apparatus manufacturer until the department accepts the unit.

**PERFORMANCE TESTS AND REQUIREMENTS**

A road test shall be conducted with the apparatus fully loaded to its estimated in-service weight and shall be capable of the following performance while on dry paved roads that are in good condition and for a continuous run of ten (10) miles or more, during which time the apparatus shall show no loss of power or overheating. The transmission drive shaft or shafts and rear axles shall run quietly and be free from abnormal vibration or noise throughout the operating range of the apparatus. The successful bidder shall furnish a Weight Certificate showing weights on front axle, rear axles and total weight for the completed apparatus at time of delivery.

- A. The apparatus shall be capable of accelerating to 35 MPH (55 km/hr) from a standing start within 25 seconds on a level concrete highway without exceeding the maximum governed RPM of the engine.
- B. The apparatus, fully loaded, shall be capable of obtaining a minimum top speed of 50 MPH (80 km/hr) on a level dry concrete highway with the engine not exceeding its governed RPM (fully loaded).
- C. The service brakes shall be capable of stopping a fully loaded vehicle in 35ft (10.7 m) at 20 mph (32.2 km/hr) on a level concrete highway. The air brake system shall conform to Federal Motor Vehicle Safety Standards (FMVSS) 121.
- D. The apparatus, when fully loaded, shall have not less than 25 percent or more than 50 percent of the weight on the front axle, and not less than 50 percent nor more than 75 percent on the rear axle.
- E. From a steady pace of 15 mph, the vehicle will accelerate to a true speed of 35 mph within 15 seconds. This will be accomplished without moving gear selector.
- F. The apparatus will be able to maintain a speed of at least 20 mph on any grade up to and including 6 percent.

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes      No**

- G. The contractor shall have the Underwriter's Laboratories, LLC conduct the tests of the apparatus as in accordance with standard practices required by the Underwriter Laboratories, LLC (Guide for the Certification of Fire Department Pumper latest edition). A copy of all tests shall accompany the Apparatus. (For apparatus sold within Canadian ULC S515 latest revision shall prevail).
- H. The contractor shall furnish copies of the Pump Manufacturer's Certification of hydrostatic test, the Engine Manufacturer current certified brake horsepower curve, and the Manufacturer's record of pumper construction details when delivered.
- I. All fluid levels and applicable pressures will be brought to proper levels and noted prior to final delivery.

### **INFORMATION REQUIRED**

The manufacturer shall supply at time of delivery, a complete operation and maintenance manual covering the completed apparatus as delivered.

A Fire Apparatus Safety Guide published by Fire Apparatus Manufacturer's Association shall be provided with the apparatus upon delivery. This manual includes essential safety information for fire fighters, fire chiefs, apparatus mechanics, and fire department safety officers. The guide is applicable to municipal, wildland, and airport firefighting apparatus manufactured on either custom or commercial chassis.

A permanent plate shall be mounted in the driver's compartment to specify the quantity and type of the following fluids used in the vehicle: Engine oil, engine coolant, and chassis transmission fluid, pump transmission lubrication fluid, pump primer fluid (if used) and drive axle lubrication fluid.

The manufacture shall supply the final certification of GVWR and GAWR on a nameplate affixed to the vehicle.

A permanent plate in the driver's compartment shall be installed, specifying the seating capacity of the enclosed cab.

Signs that state "OCCUPANTS MUST BE SEATED AND BELTED WHEN APPARATUS IS IN MOTION" shall be provided and will be visible from each seated position. An accident prevention sign shall be located at the rear step area of the apparatus. It shall warn all personnel that standing on the step while apparatus is in motion shall be prohibited.

A nameplate indicating the chassis transmission shift selector position to be used when pumping shall be provided in the driving compartment and located so that it can be easily read from the driver's position.

### **LIABILITY**

The bidder, if their bid is accepted, shall defend any and all suits and assume all liability for

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes      No**

the use of any patented device or article forming part of the apparatus or any appliance provided under the contract.

### **GENERAL CONSTRUCTION**

The apparatus shall be designed with due consideration to distribution of load between the front and rear axles, so that all specified equipment, including filled water tank, a full complement of personnel and fire hose will be carried without injury to the apparatus. Weight balance and distribution shall be in accordance with the recommendations of the (NFPA) 1901, Standard for Automotive Fire Apparatus, documentation.

The apparatus shall be designed so that all recommended daily maintenance checks can be performed easily by the operator without the need for hand tools. Apparatus components that interfere with repair or removal of other major components must be attached with fasteners (cap, screws, nuts, etc.) so that the components can be removed and installed with normal hand tools. These components must not be welded or otherwise permanently secured into place.

The GAWR and GVWR of the chassis shall be adequate to carry the fully equipped apparatus including all tanks filled, the specified hose load, unequipped personnel weight, ground ladders and a miscellaneous equipment allowance per NFPA criteria. It shall be the responsibility of the purchaser to provide the contractor with the weight of equipment to be carried if it is in excess of the allowance as set forth by NFPA.

The unequipped personnel weight shall be calculated at 250 lbs. per person times the maximum number of persons to ride on the apparatus.

The height of the fully loaded vehicle's center of gravity shall not exceed the chassis manufacturer's maximum limit.

The front to rear weight distribution of the fully loaded vehicle shall be within the limits set by the chassis manufacturer. The front axle loads shall not be less than the minimum axle loads specified by the chassis manufacturer, under full loads and all other loading conditions.

The difference in weight on the end of each axle, from side to side, when the vehicle is fully loaded and equipped shall not exceed 7 percent.

The apparatus shall be so designed that the various parts are readily accessible for lubrication, inspection, adjustment and repair.

Where special tools manufactured or designed by the contractor and are required to provide routine service on any component of the apparatus built or supplied by the contractor, such tools shall be provided with the apparatus.



**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**EXCEPTIONS TO SPECIFICATIONS**

The following specifications shall be strictly adhered to. Exceptions shall be allowed if they are equal to or superior to that as specified and providing, they are listed and entirely explained on a separate page entitled "Exceptions to Specifications". The exceptions list to refer to specification page number and paragraph.

Proposals taking total exception to specifications or total exception to certain parts of the specifications such as Electrical Systems, Chassis, Body or Pump, will not be accepted.

Prototype units will not be acceptable. Apparatus shall be inspected upon completion for compliance with specifications.

Deviations will not be tolerated and will be cause for rejection of Apparatus unless they were originally listed in bidder's proposal and accepted in writing by the department.

If the bidder takes an exception, on the exception page, the bidder must state an option price to bring their specifications into full compliance with the Department specifications.

Failure to provide this information shall be cause to reject the proposal as being non-responsive.-**NO EXCEPTIONS**

Copied or run off sheets of these specifications shall be unacceptable, and the bid will be rejected no exceptions.

**WARRANTY**

Warranties applicable to the chassis and body (excluding vendor supplied components {engine, transmission, axles, etc.} which carry their own specific warranties) will be addressed by a single point warranty service provider approved by the manufacturer to perform service as necessary.

**PURCHASER'S RIGHTS**

The Purchaser reserves the right to accept or reject any or all bids as it deemed in their best interests.

**BID/PROPOSAL DRAWINGS**

For purposes of evaluation, the bidder shall provide a drawing illustrating, but not limited to, the overall dimensions, wheelbase, and overall length of the proposed apparatus and other specified equipment, shall be required to be included with the bidder's proposal package.

The drawings shall be large "D" size (minimum 24.00 inches x 36.00 inches).

Smaller size drawings, "similar to" drawings or general sales drawings, shall not be acceptable.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

Failure to provide a bid evaluation drawing in accordance with these specifications shall be cause for rejection of the bid proposal.

**PRE-CONSTRUCTION DRAWINGS**

After the award of the bid, the contractor shall provide detailed colored engineering drawings including, but not limited to, the overall dimensions, wheelbase, and overall length of the proposed apparatus for use during the pre-construction conference.

The drawings shall include, but shall not be limited to the right, left, top, front and rear views of the apparatus.

**In addition, a detailed engineering drawing of the pump operator's panel shall be provided prior to manufacturing for fire department approval.**

**SINGLE SOURCE MANUFACTURER**

Bids shall only be accepted from a single source apparatus manufacturer. **No Exception**

The definition of single source manufacturer is a company that designs and manufactures their products utilizing an approach that includes complete product integration, including the apparatus chassis, cab, and body modules being constructed, assembled, and tested on company premises only.

Warranties qualified to the chassis and body design construction (excluding vender component warranties such as engine, axles, transmission, and pumps, etc.) will be from a single source manufacturer and not separated between manufacturers (i.e., body and chassis). The bidder shall provide evidence of maintaining compliance to this requirement.

**TAG-ON ORDERS-COOPERATIVE PURCHASING**

Other fire departments, metropolitan regions, or municipalities may purchase apparatus and equipment from same manufacture similar to the Apparatus and Equipment that is the subject of this Contract held by the same manufacture. The following terms shall apply to any such tag-on orders:

(a) Changes - Tag-on orders utilizing the same specification as the Apparatus and Equipment that is the subject of this Contract in order to provide favorable pricing and lead-times to other buyers due to having such specification fully engineered. Limited changes will be permitted. Such changes will be captured in the pre-construction meeting and the price of any tag-on unit adjusted accordingly.

(b) Term – Tag-on orders may be placed for a term of one year after the Effective Date of this Contract.

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

(c) Escalation - Manufacture reserves the right to adjust the price of any tag-on order if material costs escalate during the term of this Contract, changes in regulations become effective (for example EPA, NFPA or other), or the tag-on order would cross a model year.

(d) Acceptance – Manufacture holding the contract reserves the right to accept or reject any tag-on orders under this Contract.

### **FINITE ELEMENT ANALYSIS AND TESTING**

Finite Element Analysis (FEA) shall be provided by the manufacturer.

Prototype bodies have been subjected to rigorous testing over varied terrains simulating different environmental conditions.

The purpose of such complex engineering methods of analysis shall be to ensure the longevity of the design by analyzing stress levels throughout the body and incorporating the structural supports wherever necessary.

There shall have been a minimum of three (3) different load cases (per DOT, FHWA, and TTMA recommended practice) applied and analyzed to properly display the different areas and levels of stresses that will be present under the various operating conditions of the apparatus.

In addition to the FEA analysis, the core product design shall be strain gauged instrumental to ensure validation of FEA results and “Real World” drive/apparatus driving conditions.

Analysis shall also have been conducted on the mounting system for the apparatus body and pump house. **EXCEPTIONS TO THIS STATEMENT MAY BE CAUSE FOR IMMEDIATE REJECTION AND/OR BE CONSIDERED NON-COMPLIANT.**

### **SUPPLIED INFORMATION & EXTRAS**

The apparatus manufacturer shall supply two (2) hard copies of apparatus manuals with all manufactured apparatus.

The manuals shall include, but not be limited to: all component warranties, users' manuals and information for supplied products, apparatus engineering information including drawings and build prints, and whatever other pertinent information the manufacturer can supply to its customer regarding the said apparatus.

Included in the delivery of the unit, the manufacturer shall also include spare hardware and extra fasteners, paint for touch-up, information regarding washing and care procedures, as well as other recommendations for care and maintenance of the general apparatus.

The manufacturer shall also supply a manufacturer's record of apparatus construction details, including the following information:

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes      No**

- Owner name and address
- Apparatus manufacturer, model, and serial number
- Chassis make, model, and serial number
- GAWR of front and rear axles
- Front tire size and total rated capacity in kilograms
- Rear tire size and total rated capacity in kilograms
- Chassis weight distribution in kilograms with water (if applicable) and manufacturer mounted equipment (front and rear)
- Engine make, model, serial number, rated horsepower, related speed and no load governed speed
- Type of fuel and fuel tank capacity
- Electrical system voltage and alternator output in amps
- Battery make and model, capacity in CCA
- Paint numbers
- Weight documents from a certified scale showing actual loading on the front axle, rear axle(s), and overall vehicle (with the water tank full (if applicable) but without personnel, equipment, and hose)
- Written load analysis and results of the electrical system performance tests
- Transmission make, model, and type
- Pump to drive through the transmission (yes or no)
- Engine to pump gear ratio and transmission gear ratio used
- Pump make and model, rated capacity in gallons per minute, serial number, and number of stages
- Pump manufacturer's certification of suction capability
- Pump manufacturer's certification of hydrostatic test
- Pump manufacturer's certification of inspection and test for the fire pump
- Copy of the apparatus manufacturer's approval for stationary pumping applications
- Pump transmission make, model and serial number
- Priming device type
- Type of pump pressure control system
- The engine manufacturer's certified brake horsepower curve for the engine furnished, showing the maximum no load governed speed
- Certification of the water tank capacity

**ELECTRICAL SCHEMATICS**

The apparatus manufacturer shall supply one (1) set(s) as-built wiring schematics, to include all line voltage schematics with each apparatus.

**WARNING AND INFORMATION LABELS**

All warning and informational labels (non-vendor specific) shall be provided in compliance with (NFPA) 1901, Standard for Automotive Fire Apparatus, and installed in the appropriate locations to alert the operator of potential hazards and operating instructions.

<b>Fannin County Fire-Rescue</b>	<b>Bidder Complies</b>	
	<b>Yes</b>	<b>No</b>
<p><b><u>ON-LINE CUSTOMER INTERACTION</u></b></p> <p>The manufacture shall provide the capability for online access through the manufacture’s website. The customer shall be able to view digital photos of their apparatus in the specified phases of construction. The following phases will be captured and displayed on the manufacture’s website:</p> <ol style="list-style-type: none"> <li>1. Chassis when available at manufacturing facility</li> <li>2. Body – Prior to Paint</li> <li>3. Body – Painted</li> <li>4. Pump and Plumbing</li> <li>5. Assembly – 80% Complete</li> </ol> <p>Due to the complex nature of fire apparatus and the importance of communication between the manufacture and customer, this line item is considered a critical requirement. <b>NO EXCEPTIONS</b></p> <p><b><u>LIABILITY INSURANCE COVERAGE</u></b></p> <p>In order to protect the department and its personnel, the bidder shall show proof that it has no less than \$10 million in liability insurance in force. A certificate of coverage shall be included in the bid package. Failure to carry liability insurance of at least this amount or failure to include proof of coverage shall be cause to reject the bidder's proposal.</p> <p><b><u>GENERAL WARRANTY</u></b></p> <p>The manufacturer shall provide a two (2) year warranty from the date of delivery. <b>No Exception</b></p> <p>In the case of a commercial chassis being used, the warranty on the chassis, engine, transmission, tires, storage batteries, generators, electrical lamps and other devices subject to deterioration is limited to the warranty of the manufacturer thereof and adjustments for the same are to be made directly with the manufacturer by the customer.</p> <p><b><u>PLUMBING WARRANTY</u></b></p> <p>A Stainless Steel Plumbing/Piping warranty shall be provided by the apparatus manufacturer for products of its manufacture to be free from defects in material and workmanship, under normal use and service, for a period of ten (10) years from the date of delivery.</p> <p><b><u>THIRD PARTY PUMP CERTIFICATION AND TESTING</u></b></p> <p>The apparatus upon completion will be tested and certified by an independent third party testing company. The certification tests will follow the guide lines outlined in (NFPA) 1901, Standard for Automotive Fire Apparatus.</p>		

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes      No**

There shall be multiple tests performed by the contractor and the third party testing company when the apparatus has been completed. The manufacturer shall provide the completed Test Certificate(s) to the purchaser at time of delivery.

The fire pump shall be mounted on the apparatus and shall have a minimum rated capacity of 250 gpm (1000 L/min) at 150 psi (1000 kPa) net pump pressure.

Where the apparatus is designed for pump in-motion operations, the vehicle drive engine and drive train shall be arranged so that the pump can deliver at least 20 gpm (76 L/min) at a gauge pressure of 80 psi (550 kPa), while the fire apparatus is moving.

If the pumping system provided is rated at 3000 gpm (12,000 L/min) or less, the pump shall be capable of delivering the following:

- (1) One hundred percent of rated capacity at 150 psi (1000 kPa) net pump pressure
- (2) Seventy percent of rated capacity at 200 psi (1400 kPa) net pump pressure
- (3) Fifty percent of rated capacity at 250 psi (1700 kPa) net pump pressure

If the pumping system provided is rated at greater than 3000 gpm (12,000 L/min), the pump shall be capable of delivering the following:

- (1) One hundred percent of rated capacity at 100 psi (700 kPa) net pump pressure
- (2) Seventy percent of rated capacity at 150 psi (1000 kPa) net pump pressure
- (3) Fifty percent of rated capacity at 200 psi (1400 kPa) net pump pressure

If the fire pump has a rated capacity of 750 gpm (3000 L/min) or greater, the pump shall be tested after the pump and all its associated piping and equipment have been installed on the apparatus.

The tests shall include at least the pumping test, the pumping engine overload test, the pressure control system test, the priming device tests, and the vacuum test.

A test plate shall be provided at the pump operator's panel that gives the rated discharges and pressures together with the speed of the engine as determined by the certification test for each unit, the position of the parallel/series pump as used, and the governed speed of the engine as stated by the engine manufacturer on a certified brake horsepower curve. The plate shall be completely stamped with all information at the factory and attached to the vehicle prior to shipping.

### **Pumping Test:**

The test site shall be adjacent to a supply of clear water at least 4 feet (1.2 m) deep, with the water level not more than 10 feet (3 m) below the center of the pump intake, and close enough

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes    No**

to allow the suction strainer to be submerged at least 2 feet (0.6 m) below the surface of the water when connected to the pump by 20 feet (6 m) of suction hose.

Tests shall be performed when conditions are as follows:

- (1) Air temperature: 0 degrees Fahrenheit to 110 degrees Fahrenheit (-18 degrees Celsius to 43 degrees Celsius)
- (2) Water temperature: 35 degrees Fahrenheit to 90 degrees Fahrenheit (2 degrees Celsius to 32 degrees Celsius)
- (3) Barometric pressure: 29 inches Hg (98.2 kPa), minimum (corrected to sea level)

Engine-driven accessories shall not be functionally disconnected or rendered inoperative during the tests.

The following devices shall be permitted to be turned off or not operating during the pump test:

- (1) Aerial hydraulic pump
- (2) Foam pump
- (3) Hydraulically driven equipment (other than hydraulically driven line voltage generator)
- (4) Winch
- (5) Windshield wipers
- (6) Four-way hazard flashers
- (7) Compressed air foam system (CAFS) compressor

All structural enclosures, such as floorboards, gratings, grilles, and heat shields, not provided with a means for opening them in service shall be kept in place during the tests.

All test gauges shall meet the requirements for Grade A gauges as defined in ASME B40.100, *Pressure Gauges and Gauge Attachments*, and shall be at least size 3 1/2 per ASME B40.100. The pump intake gauge shall have a range of 30 in. Hg (100 kPa) vacuum to zero for a vacuum gauge, or 30 in. Hg (100 kPa) vacuum to a gauge pressure of 150 psi (1000 kPa) for a compound gauge. The discharge pressure gauge shall have a gauge pressure range of 0 psi to 400 psi (0 kPa to 2800 kPa). All pilot gauges shall have a gauge pressure range of at least 0 psi to 160 psi (0 kPa to 1100 kPa). All gauges shall be calibrated in the month preceding the tests using a dead-weight gauge tester or a master gauge meeting the requirements for Grade 3A or 4A gauges, as defined in ASME B40.100, *Pressure Gauges and Gauge Attachments*, that has been calibrated within the preceding year.

The engine speed-measuring equipment shall consist of a nonadjustable tachometer supplied from the engine or transmission electronics, a revolution counter on a checking shaft outlet and a stopwatch, or other engine speed-measuring means that is accurate to within  $\pm 50$  rpm of actual speed.

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

If the apparatus is equipped with a fire pump rated at 750 gpm (3000 L/min) or greater but not greater than 3000 gpm (12,000 L/min), the pump shall be subjected to a 3 hour pumping test from draft consisting of 2 hours of continuous pumping at rated capacity at a minimum of 150 psi (1000 kPa) net pump pressure, followed by 1/2 hour of continuous pumping at 70 percent of rated capacity at a minimum of 200 psi (1400 kPa) net pump pressure and 1/2 hour of continuous pumping at 50 percent of rated capacity at a minimum of 250 psi (1700 kPa) net pump pressure and shall not be stopped until after the 2 hour test at rated capacity, unless it becomes necessary to clean the suction strainer.

If the apparatus is equipped with a fire pump rated at greater than 3000 gpm (12,000 L/min), the pump shall be subjected to a 3 hour pumping test from draft consisting of 2 hours of continuous pumping at rated capacity at 100 psi (700 kPa) net pump pressure, followed by 1/2 hour of continuous pumping at 70 percent of rated capacity at 150 psi (1000 kPa) net pump pressure and 1/2 hour of continuous pumping at 50 percent of rated capacity at 200 psi (1400 kPa) net pump pressure and shall not be stopped until after the 2 hour test at rated capacity, unless it becomes necessary to clean the suction strainer.

If the apparatus is equipped with a fire pump rated at less than 750 gpm (3000 L/min), the pump shall be subjected to a 50-minute pumping test from draft consisting of 30 minutes of continuous pumping at rated capacity at a minimum of 150 psi (1000 kPa) net pump pressure, followed by 10 minutes of continuous pumping at 70 percent of rated capacity at a minimum of 200 psi (1400 kPa) net pump pressure and 10 minutes of continuous pumping at 50 percent of rated capacity at a minimum of 250 psi (1700 kPa) net pump pressure and shall not be stopped until after the 30-minute test at rated capacity, unless it becomes necessary to clean the suction strainer.

### **Pumping Engine Overload Test:**

If the pump has a rated capacity of 750 gpm (3000 L/min) or greater but not greater than 3000 gpm (12,000 L/min), the apparatus shall be subjected to an overload test consisting of pumping rated capacity at 165 psi (1100 kPa) net pump pressure for at least 10 minutes.

This test shall be performed immediately following the pumping test of rated capacity at 150 psi (1000 kPa).

The capacity, discharge pressure, intake pressure, and engine speed shall be recorded at least three times during the overload test.

### **Pressure Control System Test:**

If the pump is rated at 3000 gpm (12,000 L/min) or less, the pressure control system on the pump shall be tested as follows:

(1) The pump shall be operated at draft, delivering rated capacity at a discharge gauge pressure of 150 psi (1000 kPa).



## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes      No**

- (2) The pressure control system shall be set in accordance with the manufacturer's instructions to maintain the discharge gauge pressure at 150 psi (1000 kPa)  $\pm 5$  percent.
- (3) All discharge valves shall be closed not more rapidly than in 3 seconds and not more slowly than in 10 seconds.
- (4) The rise in discharge pressure shall not exceed 30 psi (200 kPa) and shall be recorded.
- (5) The original conditions of pumping rated capacity at a discharge gauge pressure of 150 psi (1000 kPa) shall be reestablished.
- (6) The discharge pressure gauge shall be reduced to 90 psi (620 kPa) by throttling the engine fuel supply, with no change to the discharge valve settings, hose, or nozzles.
- (7) The pressure control system shall be set according to the manufacturer's instructions to maintain the discharge gauge pressure at 90 psi (620 kPa)  $\pm 5$  percent.
- (8) All discharge valves shall be closed not more rapidly than in 3 seconds and not more slowly than in 10 seconds.
- (9) The rise in discharge pressure shall not exceed 30 psi (200 kPa) and shall be recorded.
- (10) The pump shall be operated at draft, pumping 50 percent of rated capacity at a discharge gauge pressure of 250 psi (1700 kPa).
- (11) The pressure control system shall be set in accordance with the manufacturer's instructions to maintain the discharge gauge pressure at 250 psi (1700 kPa)  $\pm 5$  percent.
- (12) All discharge valves shall be closed not more rapidly than in 3 seconds and not more slowly than in 10 seconds.
- (13) The rise in discharge pressure shall not exceed 30 psi (200 kPa) and shall be recorded.
- If the pump is rated at greater than 3000 gpm (12,000 L/min), the pressure control system on the pump shall be tested as follows:
- (1) The pump shall be operated at draft, delivering rated capacity at a discharge gauge pressure of 100 psi (700 kPa).
- (2) The pressure control system shall be set in accordance with the manufacturer's instructions to maintain the discharge gauge pressure at 100 psi (700 kPa)  $\pm 5$  percent.
- (3) All discharge valves shall be closed not more rapidly than in 3 seconds and not more slowly than in 10 seconds.
- (4) The rise in discharge pressure shall not exceed 30 psi (200 kPa) and shall be recorded.

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

(5) The original conditions of pumping rated capacity at a discharge gauge pressure of 150 psi (1000 kPa) shall be reestablished.

(6) The pump shall be operated at draft, pumping 50 percent of rated capacity at a discharge gauge pressure of 200 psi (1400 kPa).

(7) The pressure control system shall be set according to the manufacturer's instructions to maintain the discharge gauge pressure at 200 psi (1400 kPa)  $\pm$ 5 percent.

(8) All discharge valves shall be closed not more rapidly than in 3 seconds and not more slowly than in 10 seconds.

(9) The rise in discharge pressure shall not exceed 30 psi (200 kPa) and shall be recorded.

### **Priming System Tests:**

With the apparatus set up for the pumping test, the primer shall be operated in accordance with the manufacturer's instructions until the pump has been primed and is discharging water. This test shall be permitted to be performed in connection with priming the pump for the pumping test.

The interval from the time the primer is started until the time the pump is discharging water shall be noted. The time required to prime the pump shall not exceed 30 seconds if the rated capacity is 1250 gpm (5000 L/min) or less. The time required to prime the pump shall not exceed 45 seconds if the rated capacity is 1500 gpm (6000 L/min) or more.

An additional 15 seconds shall be permitted in order to meet the requirements of 16.13.5.3 and 16.13.5.4 when the pump system includes an auxiliary 4 inches (100 mm) or larger intake pipe having a volume of 1 foot<sup>3</sup> (0.30 m<sup>3</sup>) or more.

### **Vacuum Test:**

The vacuum test shall consist of subjecting the interior of the pump, with all intake valves open, capped or plugged, and all discharge caps removed, to a vacuum of 22 inches/Hg (75 kPa) by means of the pump priming system.

At altitudes above 2000 feet (600 m), the vacuum attained shall be permitted to be less than 22 inches/Hg (75 kPa) by 1 inch/Hg (3.4 kPa) for each 1000 feet (305 m) of altitude above 2000 feet (610 m).

The vacuum shall not drop more than 10 inches/Hg (34 kPa) in 5 minutes.

The primer shall not be used after the 5 minute test period has begun and the engine shall not be operated at any speed greater than the governed speed during this test.

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes      No**

### **Water Tank-to-Pump Flow Test:**

A water tank-to-pump flow test shall be conducted as follows:

- (1) The water tank shall be filled until it overflows.
- (2) All intakes to the pump shall be closed.
- (3) The tank fill line and bypass cooling line shall be closed.
- (4) Hose lines and nozzles for discharging water at the rated tank-to-pump flow rate shall be connected to one or more discharge outlets.
- (5) The tank-to-pump valve(s) and the discharge valves leading to the hose lines and nozzles shall be fully opened.
- (6) The engine throttle shall be adjusted until the required flow rate  $-0/+5$  percent is established.
- (7) The discharge pressure shall be recorded.
- (8) The discharge valves shall be closed, and the water tank refilled.
- (9) The bypass line shall be permitted to be opened temporarily, if needed, to keep the water temperature in the pump within acceptable limits.
- (10) The discharge valves shall be reopened fully, and the time noted.
- (11) If necessary, the engine throttle shall be adjusted to maintain the discharge pressure recorded as noted in 16.13.7.1(7).
- (12) When the discharge pressure drops by 10 psi (70 kPa) or more, the time shall be noted and the elapsed time from the opening of the discharge valves shall be calculated and recorded.

### **Volume Discharge Calculation:**

The volume discharged shall be calculated by multiplying the rate of discharge in gallons per minute (liters per minute) by the time in minutes elapsed from the opening of the discharge valves until the discharge pressure drops by at least 10 psi (70 kPa).

Other means shall be permitted to be used to determine the volume of water pumped from the tank such as a totalizing flowmeter, weighing the truck before and after, or refilling the tank using a totalizing flowmeter.

The rated tank-to-pump flow rate shall be maintained until 80 percent of the rated capacity of the tank has been discharge.

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes      No**

### **Engine Speed Advancement Interlock Test**

The engine speed advancement interlock system shall be tested to verify that engine speed cannot be increased at the pump operator's panel unless there is throttle-ready indication.

If the apparatus is equipped with a stationary pump driven through split-shaft PTO, the test shall verify that the engine speed control at pump operator's panel cannot be advanced when either of the following conditions exists:

- (6) The chassis transmission is in neutral, the parking brake is off, and the pump shift in the driving compartment is in the road position.
- (7) The chassis transmission has been placed in the position for pumping as indicated on the label provided in the driving compartment, the parking brake is on, and the pump shift in the driving compartment is in the road position.

If the apparatus is equipped with a stationary pump driven through a transmission mounted PTO, front-of-engine crankshaft PTO, or engine flywheel PTO, the test shall verify that the engine speed control on the pump operator's panel cannot be advanced when either of the following conditions exists:

- (1) The chassis transmission is in neutral, the parking brake is off, and the pump shift status in the driving compartment is disengaged.
- (2) The chassis transmission is in any other gear other than neutral, the parking brake is on, and the pump shift in the driving compartment is in the "Pump Engaged" position.

If the apparatus is equipped with a pump driven by the chassis engine designed for both stationary pumping and pump-in-motion, the test shall verify that the engine speed control at pump operator's panel cannot be advanced when either of the following conditions exists:

- (1) The chassis transmission is in neutral, the parking brake is on, and the pump shift status in the driving compartment is disengaged.
- (2) The chassis transmission is in any other gear other than neutral, the parking brake is on, and the pump shift in the driving compartment is in the "Pump Engaged" or the "OK to Pump In-Motion" position.

If the apparatus is equipped with a stationary pump driven through transfer case PTO, the test shall verify that the engine speed control on the pump operator's panel cannot be advanced when either of the following conditions exists:

- (1) The chassis transmission is in neutral, the transfer case is in neutral, the parking brake is off, and the pump shift in the driving compartment is in the road position.
- (2) The chassis transmission is in neutral, the transfer case is engaged, the parking brake is off, and the pump shift in the driving compartment is in the road position.
- (3) The chassis transmission has been placed in the position for pumping as indicated on the label provided in the driving compartment, the parking brake is on, and the pump shift in the driving compartment is in the road position.

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

### **LOW-VOLTAGE ELECTRICAL SYSTEM PERFORMANCE TESTING**

The apparatus low-voltage electrical system will be tested and certified. Tests shall be performed when the air temperature is between 0 degrees Fahrenheit and 110 degrees Fahrenheit (-18 degrees Celsius and 43 degrees Celsius). The three tests defined in NFPA shall be performed in the order in which they appear. Before each test, the batteries shall be fully charged until the voltage stabilizes at the voltage regulator set point and the lowest charge current is maintained for 10 minutes. Failure of any of these tests shall require a repeat of the sequence.

#### **Reserve Capacity Test:**

The engine shall be started and kept running until the engine and engine compartment temperatures are stabilized at normal operating temperatures and the battery system is fully charged.

The engine shall be shut off and the minimum continuous electrical load shall be activated for 10 minutes.

All electrical loads shall be turned off prior to attempting to restart the engine. The battery system shall then be capable of restarting the engine. Failure to restart the engine shall be considered a test failure of the battery system.

#### **Alternator Performance Test at Idle:**

The minimum continuous electrical load shall be activated with the engine running at idle speed.

The engine temperature shall be stabilized at normal operating temperature.

The battery system shall be tested to detect the presence of battery discharge current. The detection of battery discharge current shall be considered a test failure.

#### **Alternator Performance Test at Full Load:**

The total continuous electrical load shall be activated with the engine running up to the engine manufacturer's governed speed.

The test duration shall be a minimum of 2 hours.

Activation of the load management system shall be permitted during this test.

An alarm sounded by excessive battery discharge, as detected by the system required in NFPA 13.3.4, or a system voltage of less than 11.8 V dc for a 12 V nominal system or 23.6 V dc for a 24 V nominal system, for more than 120 seconds, shall be considered a test failure.

<b>Fannin County Fire-Rescue</b>	<b>Bidder Complies</b>	
	Yes	No
<p><b>Low Voltage Alarm Test:</b></p> <p>Following the above test, a Low Voltage Alarm Test will be performed in the manner prescribed.</p> <p>With the engine shut off, the total continuous electrical load shall be activated and shall continue to be applied until the excessive battery discharge alarm activates.</p> <p>The battery voltage shall be measured at the battery terminals.</p> <p>The test shall be considered a failure if the alarm has not yet sounded 140 seconds after the voltage drops to 11.70V for a 12 V nominal system or 23.4 V for a 24 V nominal system.</p> <p>The battery system shall then be able to restart the engine. Failure to restart the engine shall be considered a test failure.</p> <p><b><u>FACTORY PRE-CONSTRUCTION CONFERENCE</u></b></p> <p>The factory authorized Distributor shall be required, prior to manufacturing, to have a pre-construction conference at the manufacturing facility <u>with</u> a factory representative present and with Three (3) individual(s) from the to finalize all construction details.</p> <p>The factories authorized distributor shall, at his expense, provide transportation, lodging, and meals. Any distance greater than 200 miles shall be by commercial air travel.</p> <p><b><u>FINAL INSPECTION CONFERENCE</u></b></p> <p>The factory authorized Distributor shall be required, during manufacturing, to have a final completion inspection conference at the site of the manufacturing facility with Three (3) individuals from the to inspect the apparatus after construction.</p> <p>The factories authorized distributor shall, at his expense, provide transportation, lodging, and meals. Any distance greater than 200 miles shall be by commercial air travel.</p> <p><b><u>MAXIMUM OVERALL LENGTH REQUIREMENT</u></b></p> <p>The apparatus specified shall be constructed as detailed and shall NOT exceed a maximum overall length of 388-392 inches. <b>No Exception</b></p> <p><b><u>MAXIMUM OVERALL HEIGHT REQUIREMENT</u></b></p> <p>The apparatus specified shall be constructed as detailed and shall NOT exceed a maximum overall height of 134-136 inches. <b>No Exception</b></p> <p><b><u>MAXIMUM OVERALL WIDTH OF NINETY-NINE (99) INCHES</u></b></p> <p>The apparatus specified shall be constructed as detailed and shall NOT exceed a Maximum</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

Overall Width of Ninety-nine (99.00) inches.

This dimension shall include the primary construction of the apparatus body and chassis cab. Any peripheral items shall not be incorporated into this measurement.

The items included, but not limited to, are: Rub Rails, Fenderettes, Mirrors, Lights, Handrails, Front Bumpers, Cab Steps, Overlays, Etc.

**MAXIMUM WHEELBASE REQUIREMENT**

The apparatus specified shall be constructed as detailed and shall NOT exceed a maximum wheelbase of 188-190 inches. **No Exception**

**ALTITUDE PERFORMANCE REQUIREMENT**

The apparatus specified shall be constructed with no altitude performance restrictions.

**CHASSIS MODEL**

The chassis shall be an MFD model. The cab and chassis shall include design considerations for multiple emergency vehicle applications, rapid transit and maneuverability. The chassis shall be manufactured for heavy duty service with the strength and capacity to support a fully laden apparatus, one hundred (100) percent of the time.

**MODEL YEAR**

The chassis shall have a vehicle identification number that reflects a 2024 model year.

**COUNTRY OF SERVICE**

The chassis shall be put in service in the country of United States of America (USA).

The chassis will meet applicable U.S.A. federal motor vehicle safety standards per CFR Title 49 Chapter V Part 571 as clarified in the incomplete vehicle book per CFR Title 49 Chapter V Part 568 Section 4 which accompanies each chassis. The chassis manufacturer is not responsible for compliance to state, regional, or local regulations. Dealers should identify those regulations and order any necessary optional equipment from the chassis manufacturer or their OEM needed to be in compliance with those regulations.

**CAB AND CHASSIS LABELING LANGUAGE**

The cab and chassis shall include the applicable caution, warning, and safety notice labels with text to be written in English.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**APPARATUS TYPE**

The apparatus shall be a pumper vehicle designed for emergency service use which shall be equipped with a permanently mounted fire pump which has a minimum rated capacity of 750 gallons per minute (3000 L/min). The apparatus shall include a water tank and hose body whose primary purpose is to combat structural and associated fires.

**VEHICLE TYPE**

The chassis shall be manufactured for use as a straight truck type vehicle and designed for the installation of a permanently mounted apparatus behind the cab. The apparatus of the vehicle shall be supplied and installed by the apparatus manufacturer.

**VEHICLE ANGLE OF APPROACH PACKAGE**

The angle of approach of the apparatus shall be a minimum of 8.00 degrees.

NFPA1901 Angle of Approach definition:

“To determine the angle of approach, place a thin steel strip against the front of the tires where they touch the ground or stretch a tight string from one front tire to the other at the front where they touch the ground. Determine the lowest point (component or equipment) on the vehicle forward of the front tire that would make the smallest angle of approach. Hang a plumb bob from the lowest point and mark the point on the ground where the point of the plumb bob touches. Measure the vertical distance from the ground to the point where the plumb bob was hung (distance *V*). Measure the horizontal distance from the plumb bob point to the steel strip or string running from front tire to front tire (distance *H*). Divide the vertical distance by the horizontal distance. The ratio of *V/H* is the tangent of the angle of approach. If the ratio is known, the angle of approach can be determined from a table of trigonometric functions of angles or from a math calculator. The standard requires a minimum angle of approach of 8.00 degrees: since the tangent of 8.00 degrees is 0.1405, if *V* divided by *H* is 0.1405 or larger, the angle of approach is 8.00 degrees or greater.”

**AXLE CONFIGURATION**

The chassis shall feature a 4 x 2 axle configuration consisting of a single rear drive axle with a single front steer axle.

**GROSS AXLE WEIGHT RATINGS FRONT**

The front gross axle weight rating (GAWR) of the chassis shall be 20,000 pounds.

**No Exception**

This front gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

**GROSS AXLE WEIGHT RATINGS REAR**

The rear gross axle weight rating (GAWR) of the chassis shall be 27,000 pounds. **No Exception**



**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes      No**

This rear gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

**PUMP PROVISION**

The chassis shall include provisions to mount a drive line pump in the middle of the chassis, behind the cab, more commonly known as the midship location. Chassis driveline pump provisions shall include an interlock feature for automatic setting of the park brake when the vehicle is shifted into pump mode while the transmission is in neutral and the transmission output speed translates to less than 1 mph. When the conditions are met the driver side parking brake valve shall activate. Once shifted to road mode the condition for electric automatic brake engagement is no longer present and the driver’s parking brake control valve shall function normally.

**WATER & FOAM TANK CAPACITY**

The chassis shall include a carrying capacity of 750 gallons (2839 liters) to 1250 gallons (4732 liters). The water and/or foam tank(s) shall be supplied and installed by the apparatus manufacturer.

**CAB STYLE**

The cab shall be a custom, fully enclosed, MFD model with a 10.00 inch raised roof over the driver, officer, and crew area, **No Exception** designed and built specifically for use as an emergency response vehicle by a company specializing in cab and chassis design for all emergency response applications. The cab shall be designed for heavy-duty service utilizing superior strength and capacity for the application of protecting the occupants of the vehicle. This style of cab shall offer up to eight (8) seating positions.

The cab shall incorporate a fully enclosed design with side wall roof supports, allowing for a spacious cab area with no partition between the front and rear sections of the cab. To provide a superior finish by reducing welds that fatigue cab metal; the roof, the rear wall and side wall panels shall be assembled using a combination of welds and proven industrial adhesives designed specifically for aluminum fabrication for construction.

The cab shall be constructed using multiple aluminum extrusions in conjunction with aluminum plate, which shall provide proven strength and the truest, flattest body surfaces ensuring less expensive paint repairs if needed. All aluminum welding shall be completed to the American Welding Society and ANSI D1.2-96 requirements for structural welding of aluminum.

All interior and exterior seams shall be sealed for optimum noise reduction and to provide the most favorable efficiency for heating and cooling retention.

The cab shall be constructed of 5052-H32 corrosion resistant aluminum plate. The cab shall incorporate tongue and groove fitted 6061-T6 0.13 & 0.19 inch thick aluminum extrusions for extreme duty situations. A single formed, one (1) piece extrusion shall be used for the “A”

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

pillar, adding strength and rigidity to the cab as well as additional roll-over protection. The cab side walls and lower roof skin shall be 0.13 inch thick; the rear wall and raised roof skins shall be 0.09 inch thick; the front cab structure shall be 0.19 inch thick.

The exterior width of the cab shall be 94.00 inches wide with a minimum interior width of 88.00 inches. The overall cab length shall be 131.10 inches with 54.00 inches from the centerline of the front of the axle to the back of the cab.

The cab interior shall be designed to afford the maximum usable interior space and attention to ergonomics with hip and legroom while seated which exceeds industry standards. The crew cab floor shall be flat across the entire walking area for ease of movement inside the cab.

The cab shall offer an interior height of 57.50 inches from the front floor to the headliner in the non-raised roof area and a rear floor to headliner height of 65.00 inches in the raised roof area, at a minimum. The cab shall offer an interior measurement at the floor level from the rear of the engine tunnel to the rear wall of the cab of 51.88 inches. All interior measurements shall include the area within the interior trimmed surfaces and not to any unfinished surface.

The cab shall include a driver and officer area with two (2) cab doors large enough for personnel in full firefighting gear. The front doors shall offer a clear opening of 40.25 inches wide X 53.50 inches high, from the cab floor to the top of the door opening. The cab shall also include a crew area with up to two (2) cab doors, also large enough for personnel in full firefighting gear. The rear doors shall offer a clear opening of 32.25 inches wide X 61.00 inches high, from the cab floor to the top of the door opening.

The cab shall incorporate a progressive two (2) step configuration from the ground to the cab floor at each door opening. The progressive steps are vertically staggered and extend the full width of each step well allowing personnel in full firefighting gear to enter and exit the cab easily and safely.

The first step for the driver and officer area shall measure approximately 11.50 inches deep X 31.13 inches wide. The intermediate step shall measure approximately 8.50 inches deep X 32.50 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 11.00 inches.

The first step for the crew area shall measure approximately 11.50 inches deep X 20.44 inches wide. The intermediate step shall measure approximately 10.25 inches deep X 22.75 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 12.80 inches.

### **CAB FRONT FASCIA**

The front cab fascia shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick plate which shall be an integral part of the cab.

The cab fascia will encompass the entire front of the aluminum cab structure from the bottom of the windshield to the bottom of the cab and shall be the "Classic" design.

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

The front cab fascia shall include two (2) modules on each side accommodating a total of up to four (4) Hi/Low beam headlights and two (2) turn signal lights or up to four (4) warning lights. Two (2) chrome plated bezels shall be provided on each side around each set of two lamps.

### **FRONT GRILLE**

The front fascia shall include a 304 stainless steel front grille.

### **CAB UNDERCOAT**

There shall be a rubberized undercoating applied to the underside of the cab that provides abrasion protection, sound deadening and corrosion protection.

### **CAB SIDE DRIP RAIL**

There shall be a drip rail along the top radius of each cab side. The drip rails shall help prevent water from the cab roof running down the cab side.

### **CAB PAINT EXTERIOR**

The cab exterior shall be painted two tone per customers specified paint colors.

### **CAB PAINT PROCESS/MANUFACTURER**

The cab shall be painted with Sikkens paint prior to the installation of glass accessories and all other cab trim to ensure complete paint coverage and the maximum in corrosion protection of all metal surfaces.

All metal surfaces on the cab shall be mechanically etched by sanding disc to remove any surface oxidation or surface debris which may hinder the paint adhesion. Once all imperfections on the exterior surfaces are removed and sanded smooth, body fillers shall be applied to the cab on all surfaces that require a critically aesthetic finish and sanded smooth.

The entire cab shall then be coated with a high quality base primer that is designed to fill any minor surface defects, provide an adhesive bond between the primer and the paint and improve the color and gloss retention of the color. The finish to this procedure shall be sanding the cab to a smooth finish followed by sealing the seams with an automotive seam sealer. The minimum thickness of the primer coat after sanding shall be 2.50 mils with a maximum thickness of 5.00 mils.

The cab shall then be painted the specific color(s) designated by the customer with an acrylic urethane type system designed to retain color and resist acid rain and most atmospheric chemicals found on an emergency scene. The paint shall have a minimum thickness of 1.00 mils with a maximum of 4 mils, followed by a clear top coat with a minimum of 2.5 mils and a maximum of 3.5 mils. The entire cab shall then be baked to speed the curing process of the coatings.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**CAB PAINT PRIMARY/LOWER COLOR**

The primary/lower paint color shall be Sikkens FLNA 3001 Red.

**CAB PAINT SECONDARY/UPPER COLOR**

The secondary/upper paint color shall be Sikkens FLNA 7114 Gray.

**CAB PAINT EXTERIOR BREAKLINE**

The upper and lower paint shall meet at a breakline on the cab which shall be located approximately 1.00 inch below the door windows on each side of the cab. The breakline shall curve down at the front cab corners to approximately 5.00 inches below the windshields on the front of the cab.

**CAB PAINT PINSTRIPE**

Where the upper and lower paint colors meet a temporary 0.50 inch wide black pinstripe shall be applied over this break line to offer a more finished look prior to the final pinstripe being installed by the OEM.

**CAB PAINT WARRANTY**

Purchaser shall receive a Paint and Finish (Exterior Clear coated) Two (2) Year limited warranty in accordance with, and subject to, warranty certificate RFW0702. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request.

**CAB PAINT INTERIOR**

The visible interior cab structure surfaces shall be painted with a multi-tone silver gray texture finish.

**CAB ENTRY DOORS**

The cab shall include four (4) entry doors, two (2) front doors and two (2) crew doors designed for ease of entering and egress when outfitted with an SCBA. The doors shall be constructed of extruded aluminum with a nominal thickness of 0.13 inch. The exterior skins shall be constructed of 0.13 inch aluminum plate.

The doors shall include a double rolled style automotive rubber seal around the perimeter of each door frame and door edge which ensures a weather tight fit.

All door hinges shall be hidden within flush mounted cab doors for a pleasing smooth appearance and perfect fit along each side of the cab. Each door hinge shall be piano style with a 0.38 inch pin and shall be constructed of stainless steel.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**CAB ENTRY DOOR TYPE**

All cab entry doors shall be barrier clear design resulting in exposed lower cab steps. The doors shall provide approximately 32.00 inches of clearance from the ground to the bottom of the door so cab doors may be opened un-hindered by most obstacles encountered, such as guard rails along interstate highways.

Entry doors shall include Pollak mechanical plunger style switches for electrical component activation.

**CAB INSULATION**

The cab ceiling and walls shall include a nonwoven polyester fiber insulation. The insulation shall act as a barrier absorbing noise as well as assisting in sustaining the desired climate within the cab interior.

**CAB STRUCTURAL WARRANTY**

Purchaser shall receive a Cab Structure (Aluminum) Five (5) Years limited warranty in accordance with, and subject to, warranty certificate RFW0601. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request. **No Exception**

**CAB TEST INFORMATION**

The cab shall have successfully completed the preload side impact, static roof load application and frontal impact without encroachment to the occupant survival space when tested in accordance with Section 4 of SAE J2420 COE Frontal Strength Evaluation Dynamic Loading Heavy Trucks, Section 5 of SAE J2422 Cab Roof Strength Evaluation Quasi –Static Loading Heavy Trucks and ECE R29 Uniform Provisions Concerning the Approval of Vehicles with regard to the Protection of the Occupants of the Cab of a Commercial Vehicles Annex 3 Paragraph 5.

The above tests have been witnessed by and attested to by an independent third party. The test results were recorded using cameras, high speed imagers, accelerometers and strain gauges. Documentation of the testing shall be provided upon request.

**ELECTRICAL SYSTEM**

The chassis shall include a single starting electrical system which shall include a 12 volt direct current multiplexing system, suppressed per SAE J551. The wiring shall be appropriate gauge cross link with 311 degree Fahrenheit insulation. All SAE wires in the chassis shall be color coded and shall include the circuit number and function where possible. The wiring shall be protected by 275 degree Fahrenheit minimum high temperature flame retardant loom. All nodes and sealed Deutsch connectors shall be waterproof.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**DATA RECORDING SYSTEM**

The chassis shall have a Weldon Vehicle Data Recorder (VDR) system installed. The system shall be designed to meet NFPA 1901 and shall be integrated with the Weldon Multiplex electrical system. The following information shall be recorded:

- Vehicle Speed
- Acceleration
- Deceleration
- Engine Speed
- Engine Throttle Position
- ABS Event
- Seat Occupied Status
- Seat Belt Status
- Master Optical Warning Device Switch Position
- Time
- Date

Each portion of the data shall be recorded at the specified intervals and stored for the specified length of time to meet NFPA 1901 guidelines and shall be retrievable by connecting a laptop computer to the VDR system. The laptop connection shall be a panel mounted female type B USB connection point, remotely mounted in the left side foot well.

**LOAD MANAGEMENT SYSTEM**

The apparatus load management shall be performed by the included multiplex system. The multiplex system shall also feature the priority of sequences and shall shed electrical loads based on the priority list specifically programmed.

**ACCESSORY POWER**

The electrical distribution panel shall include two (2) power studs. The studs shall be size #10 and each of the power studs shall be circuit protected with a fuse of the specified amperage. One (1) power stud shall be capable of carrying up to a 40 amp battery direct load. One (1) power stud shall be capable of carrying up to a 15 amp ignition switched load. The two (2) power studs shall share one (1) #10 ground stud. A 225 amp battery direct power and ground stud shall be provided and installed on the chassis near the left hand battery box for OEM body connections.

**EXTERIOR ELECTRICAL TERMINAL COATING**

All terminals exposed to the elements will be sprayed with a high visibility protective rubberized coating to prevent corrosion.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes      No**

**ELECTRICAL SYSTEM WARRANTY**

Purchaser shall receive an Electrical System One (1) Year or 18,000 Miles limited warranty in accordance with, and subject to, warranty certificate RFW0201. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request.

**ENGINE**

The chassis engine shall be a Cummins L9 engine. The L9 engine shall be an in-line six (6) cylinder, four cycle diesel powered engine. The engine shall offer a rating of 450 horse power at 2100 RPM and shall be governed at 2200 RPM. The torque rating shall feature 1250 foot pounds of torque at 1200 RPM with 543 cubic inches (8.9 liters) of displacement.

The L9 engine shall feature a VGT™ Turbocharger, a high pressure common rail fuel system, fully integrated electronic controls with an electronic governor, and shall be EPA certified to meet the 2021 emissions standards using cooled exhaust gas recirculation and selective catalytic reduction technology.

The engine shall include an engine mounted combination full flow/by-pass oil filter with replaceable spin on cartridge for use with the engine lubrication system. The engine shall include Citgo brand Citgard 500, or equivalent SAE 15W40 CK-4 low ash engine oil which shall be utilized for proper engine lubrication.

A wiring harness shall be supplied ending at the back of the cab. The harness shall include a connector which shall allow an optional harness for the pump panel. The included circuits shall be provided for a tachometer, oil pressure, engine temperature, hand throttle, high idle and a PSG system. A circuit for J1939 data link shall also be provided at the back of the cab.

**CAB ENGINE TUNNEL**

The cab interior shall include an integrated engine tunnel constructed of 5052-H32 Marine Grade, 0.19 of an inch thick aluminum. The tunnel shall be a maximum of 41.50 inches wide X 25.50 inches high.

**DIESEL PARTICULATE FILTER CONTROLS**

There shall be two (2) controls for the diesel particulate filter. One (1) control shall be for regeneration and one (1) control shall be for regeneration inhibit.

**ENGINE PROGRAMMING HIGH IDLE SPEED**

The engine high idle control shall maintain the engine idle at approximately 1250 RPM when engaged.

<b>Fannin County Fire-Rescue</b>	<b>Bidder Complies</b>	
	Yes	No
<p><b><u>ENGINE HIGH IDLE CONTROL</u></b></p> <p>The vehicle shall be equipped with a high-idle speed rocker switch and an automatic high-idle speed control. It shall be pre-set so when activated, it will operate the engine at the appropriate RPM to increase alternator output. This device shall operate only when the engine is running and the transmission is in neutral with the parking brake set. When automatically engaged the high idle shall disengage when the operator depresses the brake pedal, or the transmission is placed in gear, and shall be available to manually or automatically re-engage when the brake is released, or when the transmission is placed in neutral.</p> <p><b><u>ENGINE PROGRAMMING ROAD SPEED GOVERNOR</u></b></p> <p>The engine shall include programming which will govern the top speed of the vehicle.</p> <p><b><u>AUXILIARY ENGINE BRAKE</u></b></p> <p>A compression brake, for the six (6) cylinder engine shall be provided. A cutout relay shall be installed to disable the compression brake when in pump mode or when an ABS event occurs. The engine compression brake shall activate upon 0% accelerator when in operation mode and actuate the vehicle's brake lights.</p> <p>The engine shall utilize a variable geometry turbo (VGT) as an integrated auxiliary engine brake to offer a variable rate of exhaust flow, which when activated in conjunction with the compression brake shall enhance the engine's compression braking capabilities.</p> <p><b><u>AUXILIARY ENGINE BRAKE CONTROL</u></b></p> <p>An engine compression brake control device shall be included. The electronic control device shall monitor various conditions and shall activate the engine brake only if all of the following conditions are simultaneously detected:</p> <ul style="list-style-type: none"> <li>• A valid gear ratio is detected.</li> <li>• The driver has requested or enabled engine compression brake operation.</li> <li>• The throttle is at a minimum engine speed position.</li> <li>• The electronic controller is not presently attempting to execute an electronically controlled final drive gear shift.</li> </ul> <p>The compression brake shall be controlled through an on/off switch and a low/medium/high selector switch.</p> <p><b><u>ELECTRONIC ENGINE OIL LEVEL INDICATOR</u></b></p> <p>The engine oil shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal. The warning shall activate in a low oil situation upon turning on the master battery and ignition switches without the engine running.</p>		



<b>Fannin County Fire-Rescue</b>	<b>Bidder Complies</b>	
	Yes	No
<p><b><u>FLUID FILLS</u></b></p> <p>The engine oil, coolant, transmission, and power steering fluid fills shall be located under the cab. The windshield washer fill shall be accessible through the front left side mid step.</p> <p><b><u>ENGINE DRAIN PLUG</u></b></p> <p>The engine shall include an original equipment manufacturer installed oil drain plug.</p> <p><b><u>ENGINE WARRANTY</u></b></p> <p>The Cummins engine shall be warranted for a period of five (5) years or 100,000 miles, whichever occurs first.</p> <p><b><u>REMOTE THROTTLE HARNESS</u></b></p> <p>An apparatus interface wiring harness for the engine and transmission pump interlocks shall be supplied with the chassis. The harness shall include a connector for connection to a chassis pump panel harness supplied by the body builder and shall terminate in the left frame rail behind the cab for connection by the body builder. The harness shall include circuits deemed for a pump panel and shall contain circuits for a hand throttle, and a multiplexed gauge. Separate circuits shall also be included for a pump control switch, “Pump Engaged” and “OK to Pump” indicator lights, open compartment ground, start signal, park brake ground, ignition signal, master power, clean power, customer ignition, air horn solenoid switch, high idle switch and high idle indicator light. The harness shall contain interlocks that will prevent shifting to road or pump mode unless the transmission output speed translates to less than 1 mph and the transmission is in neutral. The shift to pump mode shall also require the park brake be set.</p> <p><b><u>ENGINE PROGRAMMING REMOTE THROTTLE</u></b></p> <p>The engine ECM discreet wire remote throttle circuit will be turned on for use with a discreet wire based pump controller.</p> <p><b><u>ENGINE PROGRAMMING IDLE SPEED</u></b></p> <p>The engine low idle speed will be programmed at 700 rpm.</p> <p><b><u>ENGINE AIR INTAKE</u></b></p> <p>The engine air intake system shall include an ember separator. This ember separator shall be designed to protect the downstream air filter from embers using a combination of unique flat and crimped metal screens packaged in a heavy duty galvanized steel frame. This multilayered screen shall trap embers and allow them to burn out before passing through the pack.</p>		

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

The engine air intake system shall also include an air cleaner mounted above the radiator. This air cleaner shall utilize a replaceable dry type filter element designed to prevent dust and debris from being ingested into the engine. A service cover shall be provided on the housing, reducing the chance of contaminating the air intake system during air filter service.

**No Exception**

The air intake system shall include a restriction indicator light in the warning light cluster on the instrument panel, which shall activate when the air cleaner element requires replacement.

**ENGINE FAN DRIVE**

The engine cooling system fan shall incorporate a thermostatically controlled, Horton fully variable type fan drive with SmartClutch J-1939 CAN controller.

The variable speed fan clutch only engages at the amount needed for proper cooling to facilitate improved vehicle performance, cab heating in cold climates, and fuel economy. The fan clutch design shall be fail-safe so that if the clutch drive fails the fan shall engage to prevent engine overheating due to the fan clutch failure. The fan speed shall include a J-1939 CAN clutch controller to receive signal from the engine control module to activate at variable rates of speed. Variable speeds shall be set through thermostatic and engine speed signals to run as efficiently and quietly as required to maintain temperature.

**ENGINE COOLING SYSTEM**

There shall be a heavy-duty aluminum cooling system designed to meet the demands of the emergency response industry. The cooling system shall have the capacity to keep the engine properly cooled under all conditions of road and pumping operations. The cooling system shall be designed and tested to meet or exceed the requirements specified by the engine and transmission manufacturer and all EPA requirements. The complete cooling system shall be mounted to isolate the entire system from vibration or stress. The individual cores of the cooling system shall be mounted in a manner to allow expansion and contraction at various rates without inducing stress into the adjoining cores.

The cooling system shall be comprised of a charge air cooler to radiator serial flow package that provides the maximum cooling capacity for the specified engine as well as serviceability. The main components shall include a surge tank, a charge air cooler bolted to the front of the radiator, recirculation shields, a shroud, a fan, and required tubing.

The radiator shall be a down-flow design constructed with aluminum cores, plastic end tanks, and a steel frame. The radiator shall be equipped with a drain cock to drain the coolant for serviceability.

The cooling system shall include a one piece injected molded polymer fan with a three (3) piece fiberglass fan shroud.

The cooling system shall be equipped with a surge tank that is capable of removing entrained air from the system. The surge tank shall be equipped with a low coolant probe and rearward

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

oriented sight glass to observe coolant in the system. A cold fill and observation line shall be included within the frame mounted translucent recovery bottle to monitor the level of the coolant. The surge tank shall have a dual seal cap that meets the engine manufacturer's pressure requirements and allows for expansion and recovery of coolant into a separate integral expansion chamber.

All radiator tubes shall be formed from aluminized steel tubing. Recirculation shields shall be installed where required to prevent heated air from reentering the cooling package and affecting performance.

The charge air cooler shall be a cross-flow design constructed completely of aluminum with cast tanks. All charge air cooler tubes shall be formed from aluminized steel tubing and installed with silicone hump hoses and stainless steel "constant torque" style clamps meeting the engine manufacturer's requirements.

The radiator and charge air cooler shall be removable through the bottom of the chassis.

### **ENGINE COOLING SYSTEM PROTECTION**

The engine cooling system shall include a recirculation shield designed to act as a light duty skid plate below the radiator to provide additional protection for the engine cooling system from light impacts, stones, and road debris.

### **ENGINE COOLANT**

The cooling package shall include Extended Life Coolant (ELC). The use of ELC provides longer intervals between coolant changes over standard coolants providing improved performance. The coolant shall contain a 50/50 mix of ethylene glycol and de-ionized water to keep the coolant from freezing to a temperature of -34 degrees Fahrenheit.

Proposals offering supplemental coolant additives (SCA) shall not be considered, as this is part of the extended life coolant makeup.

### **ELECTRONIC COOLANT LEVEL INDICATOR**

The instrument panel shall feature a low engine coolant indicator light which shall be located in the center of the instrument panel. An audible tone alarm shall also be provided to warn of a low coolant incident.

### **ENGINE PUMP HEAT EXCHANGER**

A single bundle type coolant to water heat exchanger shall be installed between the engine and the radiator. The heat exchanger shall be designed to prohibit water from the pump from coming in contact with the engine coolant. This shall allow the use of water from the discharge side of the pump to assist in cooling the engine.

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>COOLANT HOSES</u></b></p> <p>The cooling systems hose shall be formed silicone hose and formed aluminized steel tubing and include stainless steel constant torque band clamps.</p> <p><b><u>ENGINE COOLANT OVERFLOW BOTTLE</u></b></p> <p>A remote engine coolant overflow expansion bottle shall be provided in the case of over filling the coolant system. The overflow bottle shall capture the expansion fluid or overflow rather than allow the fluid to drain on the ground.</p> <p><b><u>ENGINE EXHAUST SYSTEM</u></b></p> <p>The exhaust system shall include an end-in end-out horizontally mounted single module after treatment device, and downpipe from the charge air cooled turbo. The single module shall include four temperature sensors, diesel particulate filter (DPF), urea dosing module (UL2), and a selective catalytic reduction (SCR) catalyst to meet current EPA standards. The selective catalytic reduction catalyst utilizes a diesel exhaust fluid solution consisting of urea and purified water to convert NOx into nitrogen, water, and trace amounts of carbon dioxide. The solution shall be mixed and injected into the system through the DPF and SCR.</p> <p>The system shall utilize 0.07 inch thick stainless steel exhaust tubing between the engine turbo and the DPF. Zero leak clamps seal all system joints between the turbo and DPF.</p> <p>The single module after treatment through the end of the tailpipe shall be connected with zero leak clamps. The discharge shall terminate horizontally on the right side of the vehicle ahead of the rear tires.</p> <p>The exhaust system after treatment module shall be mounted below the frame in the outboard position.</p> <p><b><u>DIESEL EXHAUST FLUID TANK</u></b></p> <p>The exhaust system shall include a molded cross linked polyethylene tank for Diesel Exhaust Fluid (DEF). The tank shall have a capacity of six (6) usable gallons and shall be mounted on the left hand side of the chassis frame behind the batteries below the frame.</p> <p>The DEF tank shall be designed with capacity for expansion in case of fluid freezing. Engine coolant, which shall be thermostatically controlled, shall be run through lines in the tank to help prevent the DEF from freezing and to provide a means of thawing the fluid if it should become frozen.</p> <p>The tank fill tube shall be routed under the rear of the cab with the fill neck and splash guard accessible in the top rear step.</p>		

# Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes    No**

## **ENGINE EXHAUST ACCESSORIES**

An exhaust temperature mitigation device shall be shipped loose for installation by the body manufacturer on the vehicle. The temperature mitigation device shall lower the temperature of the exhaust by combining ambient air with the exhaust gasses at the exhaust outlet.

## **ENGINE EXHAUST WRAP**

The exhaust tubing between the engine turbo and the diesel particulate filter (DPF) shall be wrapped with a thermal cover in order to retain the necessary heat for DPF regeneration. The exhaust wrap shall also help protect surrounding components from radiant heat which can be transferred from the exhaust.

The exhaust flex joint shall not include the thermal exhaust wrap.

## **EMISSIONS SYSTEMS WARRANTY**

Purchaser shall receive a Regulated Emissions Systems Five (5) Years or 100,000 Miles limited warranty in accordance with, and subject to, warranty certificate RFW0140. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request.

## **TRANSMISSION**

The drive train shall include an Allison model EVS 3000 torque converting, automatic transmission which shall include electronic controls. The transmission shall feature two (2) 10-bolt PTO pads located on the converter housing.

The transmission shall include two (2) internal oil filters which shall offer Allison formulated Castrol TranSynd™ synthetic transmission fluid which shall be utilized in the lubrication of the EVS transmission. An electronic oil level sensor shall be included with the readout located in the shift selector.

The transmission gear ratios shall be:

- 1st    3.49:1
- 2nd    1.86:1
- 3rd    1.41:1
- 4th    1.00:1
- 5th    0.75:1
- 6th    0.65:1 (if applicable)
- Rev    5.03:1

## **TRANSMISSION MODE PROGRAMMING**

The transmission, upon start-up, will automatically select a four (4) speed operation. The fifth and sixth speeds shall be programmed as over drive speeds and shall be available with the activation of the mode button on the shifting pad.

# Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes    No**

## **TRANSMISSION FEATURE PROGRAMMING**

The Allison Gen V/VI-E transmission EVS group package number 127 shall contain the 198 vocational package in consideration of the duty of this apparatus as a pumper. This package shall incorporate an automatic neutral with selector override. This feature commands the transmission to neutral when the park brake is applied, regardless of drive range requested on the shift selector. This requires re-selecting drive range to shift out of neutral for the override.

This package shall be coupled with the use of a split shaft PTO and incorporate pumping circuits. These circuits shall be used allowing the vehicle to operate in the fourth range lockup while operating the pump mode due to the 1 to 1 ratio through the transmission, therefore the output speed of the engine is the input speed to the pump. The pump output can be easily calculated by using this input speed and the drive ratio of the pump itself to rate the gallons of water the pump can provide.

A transmission interface connector shall be provided in the cab. This package shall contain the following input/output circuits to the transmission control module. The Gen V/VI-E transmission shall include prognostic diagnostic capabilities. These capabilities shall include the monitoring of the fluid life, filter change indication, and transmission clutch maintenance.

<u>Function ID</u>	<u>Description</u>	<u>Wire assignment</u>
Inputs		
C	PTO Request	142
J	Fire Truck Pump Mode (4th Lockup)	122 / 123
Outputs		
C	Range Indicator	145 (4th)
G	PTO Enable Output	130
	Signal Return	103

## **ELECTRONIC TRANSMISSION OIL LEVEL INDICATOR**

The transmission fluid shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal.

## **TRANSMISSION SHIFT SELECTOR**

An Allison pressure sensitive range selector touch pad shall be provided and located to the right of the driver within clear view and easy reach. The shift selector shall have a graphical Vacuum Florescent Display (VFD) capable of displaying two lines of text. The shift selector shall provide mode indication and a prognostic indicator (wrench symbol) on the digital display. The prognostics monitor various operating parameters and shall alert you when a specific maintenance function is required.

## **TRANSMISSION PRE-SELECT WITH AUXILIARY BRAKE**

When the auxiliary brake is engaged, the transmission shall automatically shift to second gear to decrease the rate of speed assisting the secondary braking system and slowing the vehicle.

<b>Fannin County Fire-Rescue</b>	<b>Bidder Complies</b>	
	Yes	No
<p><b><u>TRANSMISSION COOLING SYSTEM</u></b></p> <p>The transmission shall include a water to oil cooler system located in the cooling loop between the radiator and the engine. The transmission cooling system shall meet all transmission manufacturer requirements. The transmission cooling system shall feature continuous flow of engine bypass water to maintain uninterrupted transmission cooling.</p> <p><b><u>TRANSMISSION DRAIN PLUG</u></b></p> <p>The transmission shall include an original equipment manufacturer installed magnetic transmission fluid drain plug.</p> <p><b><u>TRANSMISSION WARRANTY</u></b></p> <p>The Allison EVS series transmission shall be warranted for a period of five (5) years with unlimited mileage. Parts and labor shall be included in the warranty.</p> <p><b><u>PTO LOCATION</u></b></p> <p>The transmission shall have two (2) power take off (PTO) mounting locations, one (1) in the 8:00 o'clock position and one (1) in the 4:00 o'clock position.</p> <p><b><u>DRIVELINE</u></b></p> <p>All drivelines shall be heavy duty metal tube and equipped with MSI 1710 series universal joints. The shafts shall be dynamically balanced prior to installation to alleviate future vibration. In areas of the driveline where a slip shaft is required, the splined slip joint shall be coated with Glide Coat<sup>®</sup>. The drivelines shall include Meritor brand u-joints with thrust washers.</p> <p><b><u>MIDSHIP PUMP / GEARBOX</u></b></p> <p>A temporary jackshaft driveline shall be installed by the chassis manufacturer to accommodate the mid-ship split shaft pump as specified by the apparatus manufacturer.</p> <p><b><u>MIDSHIP PUMP / GEARBOX MODEL</u></b></p> <p>The midship pump/gearbox provisions shall be for a Hale DSD forward pump.</p> <p><b><u>MIDSHIP PUMP GEARBOX DROP</u></b></p> <p>The Hale pump gearbox shall have an "L" (long) drop length.</p> <p><b><u>MIDSHIP PUMP RATIO</u></b></p> <p>The ratio for the midship pump shall be 2.28:1 (23).</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**MIDSHIP PUMP LOCATION C/L SUCTION TO C/L REAR AXLE**

The midship pump shall be located so the dimension from the centerline of the suction to the centerline of the rear axle is 107.00 inches.

**PUMP SHIFT CONTROLS**

One (1) air pump shift control panel shall be located on the left hand side of the engine tunnel, integrated with the shifter pod. The following shall be provided on the panel: a three (3) position control lever; an engraved PUMP ENGAGED identification light; and an engraved OK TO PUMP identification light. The pump shift control panel shall be black with a yellow border outline and shall include pump instructions. An instruction plate describing the transmission shift selector position used for pumping shall be provided and located so it can be read from the driver's position per NFPA **16.10.1.3**. The road mode shall be selected when the control lever is in the forward position and pump mode shall be selected when the control lever is in the rearward position.

The control lever center position shall exhaust air from both pump and road sides of the pump gear box shift cylinder.

**PUMP SHIFT CONTROL PLUMBING**

Air connections shall be provided from the air supply tank to the pump shift control valve and from the pump shift control valve to the frame mounted bracket. The frame mounted bracket shall include labeling identifying the pump and road connection points with threaded 0.25 inch NPT fittings on the solenoid for attaching the customer installed pump. The air supply shall be pressure protected from service brake system.

**FUEL FILTER/WATER SEPARATOR**

The fuel system shall have a Fleetguard FS20121 fuel filter/water separator as a primary filter. The fuel filter shall have a drain valve.

A water in fuel sensor shall be provided and wired to an instrument panel lamp and audible alarm to indicate when water is present in the fuel/water separator.

A secondary fuel filter shall be included as approved by the engine manufacturer.

**FUEL LINES**

The fuel system supply and return lines installed from the fuel tank to the engine shall be reinforced nylon tubing rated for diesel fuel. The fuel lines shall be brown in color and connected with brass fittings.



**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**ELECTRIC FUEL PRIMER**

Integral to the engine assembly is an electric lift pump that serves the purpose of pre-filter fuel priming.

**FUEL TANK**

The fuel tank shall have a capacity of fifty (50) gallons and shall measure 35.00 inches in width X 15.00 inches in height X 24.00 inches in length.

The baffled tank shall have a vent port to facilitate venting to the top of the fill neck for rapid filling without "blow-back" and a roll over ball check vent for temperature related fuel expansion and draw.

The tank is designed with dual draw tubes and sender flanges. The tank shall have 2.00 inch NPT fill ports for right or left hand fill. A 0.50 inch NPT drain plug shall be centered in the bottom of the tank.

The fuel tank shall be mounted below the frame, behind the rear axle. Two (2) three-piece strap hanger assemblies with "U" straps bolted midway on the fuel tank front and rear shall be utilized to allow the tank to be easily lowered and removed for service purposes. Rubber isolating pads shall be provided between the tank and the upper tank mounting brackets. Strap mounting studs through the rail, hidden behind the body shall not be acceptable.

**FUEL TANK MATERIAL AND FINISH**

The fuel tank shall be constructed of 12 gauge aluminized steel. The exterior of the tank shall be powder coated black and then painted to match the frame components.

All powder coatings, primers and paint shall be compatible with all metals, pretreatments and primers used. The cross hatch adhesion test per ASTM D3359 Method B, results to be 5B minimum. The pencil hardness test per ASTM D3363 shall have a final post-curved pencil hardness of H-2H. The direct impact resistance test per ASTM D2794, results to be 5B minimum.

Any proposals offering painted fuel tanks with variations from the above process shall not be accepted. The film thickness of vendor supplied parts shall also be sufficient to meet the performance standards as stated above.

**FUEL TANK STRAP MATERIAL**

The fuel tank straps shall be constructed of ASTM A-36 steel. The fuel tank straps shall be powder coated black and then painted to match the frame components if possible.

<b>Fannin County Fire-Rescue</b>	<b>Bidder Complies</b>	
	Yes	No
<p><b><u>FUEL TANK FILL PORT</u></b></p> <p>The fuel tank fill ports shall be offset with the left fill port located in the rearward position and the right fill port located in the middle position on the fuel tank.</p> <p><b><u>FUEL TANK DRAIN PLUG</u></b></p> <p>A 0.5 inch NPT magnetic drain plug shall be centered in the bottom of the fuel tank.</p> <p><b><u>FRONT AXLE</u></b></p> <p>The front axle shall be a Meritor Easy Steer Non drive front axle, model number MFS-20. The axle shall include a 3.74 inch drop and a 71.00 inch king pin intersection (KPI). The axle shall include a conventional style hub with a standard knuckle. <b>No Exception</b></p> <p><b><u>FRONT AXLE WARRANTY</u></b></p> <p>The front axle shall be warranted by Meritor for five (5) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.</p> <p><b><u>FRONT WHEEL BEARING LUBRICATION</u></b></p> <p>The front axle wheel bearings shall be lubricated with oil. The oil level can be visually checked via clear inspection windows in the front axle hubs.</p> <p><b><u>FRONT SHOCK ABSORBERS</u></b></p> <p>Two (2) Bilstein inert, nitrogen gas filled shock absorbers shall be provided and installed as part of the front suspension system. The shocks shall be a monotubular design and fabricated using a special extrusion method, utilizing a single blank of steel without a welded seam, achieving an extremely tight peak-to-valley tolerance and maintains consistent wall thickness. The monotubular design shall provide superior strength while maximizing heat dissipation and shock life.</p> <p>The ride afforded through the use of a gas shock is more consistent and shall not deteriorate with heat, the same way a conventional oil filled hydraulic shock would.</p> <p>The Bilstein front shocks shall include a digressive working piston assembly allowing independent tuning of the compression and rebound damping forces to provide optimum ride and comfort without compromise. The working piston design shall feature fewer parts than most conventional twin tube and “road sensing” shock designs and shall contribute to the durability and long life of the Bilstein shock absorbers.</p> <p>Proposals offering the use of conventional twin tube or “road sensing” designed shocks shall not be considered.</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**FRONT SUSPENSION**

The front suspension shall include a ten (10) leaf spring pack in which the longest leaf measures 54.00 inch long and 4.00 inches wide and shall include a military double wrapped front eye. Both spring eyes shall have a case hardened threaded bushing installed with lubrication counter bore and lubrication land off cross bore with grease fitting. The spring capacity shall be rated at 21,500 pounds.

**STEERING COLUMN/ WHEEL**

The cab shall include a Douglas Autotech steering column which shall include a seven (7) position tilt, a 2.25 inch telescopic adjustment, and an 18.00 inch, two (2) spoke steering wheel located at the driver’s position. The steering wheel shall be covered with black polyurethane foam padding.

The steering column shall contain a horn button, self-canceling turn signal switch, four-way hazard switch and headlamp dimmer switch.

**ELECTRONIC POWER STEERING FLUID LEVEL INDICATOR**

The power steering fluid shall be monitored electronically and shall send a signal to activate an audible alarm and visual warning in the instrument panel when fluid level falls below normal.

**POWER STEERING PUMP**

The hydraulic power steering pump shall be a TRW PS and shall be gear driven from the engine. The pump shall be a balanced, positive displacement, sliding vane type. The power steering system shall include an oil to air passive cooler.

**FRONT AXLE CRAMP ANGLE**

The chassis shall have a front axle cramp angle of 48-degrees to the left and 44-degrees to the right.

**POWER STEERING GEAR**

The power steering gear shall be a TRW model TAS 65 with an assist cylinder.

**CHASSIS ALIGNMENT**

The chassis frame rails shall be measured to insure the length is correct and cross checked to make sure they run parallel and are square to each other. The front and rear axles shall be laser aligned. The front tires and wheels shall be aligned and toe-in set on the front tires by the chassis manufacturer.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**REAR AXLE**

The rear axle shall be a Meritor model RS-25-160 single drive axle. The axle shall include precision forged, single reduction differential gearing, and shall have a fire service rated capacity of 27,000 pounds. **No Exception**

The axle shall be built of superior construction and quality components to provide the rugged dependability needed to stand up to the fire industry’s demands. The axle shall include rectangular shaped, hot-formed housing with a standard wall thickness of 0.63 of an inch for extra strength and rigidity and a rigid differential case for high axle strength and reduced maintenance.

The axle shall have heavy-duty Hypoid gearing for longer life, greater strength and quieter operation. Industry-standard wheel ends for compatibility with both disc and drum brakes, and unitized oil seal technology to keep lubricant in and help prevent contaminant damage will be used.

**REAR AXLE DIFFERENTIAL LUBRICATION**

The rear axle differential shall be lubricated with oil.

**REAR AXLE WARRANTY**

The rear axle shall be warranted by Meritor for five (5) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.

**REAR WHEEL BEARING LUBRICATION**

The rear axle wheel bearings shall be lubricated with oil.

**VEHICLE TOP SPEED**

The top speed of the vehicle shall be approximately 68 MPH +/-2 MPH at governed engine RPM.

**REAR SUSPENSION**

The single rear axle shall feature a Reyco 79KB vari-rate, self-leveling captive slipper type conventional multi-leaf spring suspension, with 57.50 inch X 3.00 inch springs. One (1) adjustable and one (1) fixed torque rod shall be provided.

The rear suspension capacity shall be rated from 21,000 to 31,500 pounds.

<b>Fannin County Fire-Rescue</b>	<b>Bidder Complies</b>	
	Yes	No
<p><b><u>TIRE INTERMITTENT SERVICE RATING</u></b></p> <p>The chassis shall be rated using Intermittent Service ratings provided to the emergency vehicle market by the tire manufacturers as the basis for determining the maximum vehicle load and speed.</p> <p><b><u>FRONT TIRE</u></b></p> <p>The front tires shall be Michelin 315/80R-22.5 20PR "L" tubeless radial XZUS 2 regional tread.</p> <p>The front tire stamped load capacity shall be 20,000 pounds per axle with a nominal speed rating of 65 miles per hour when properly inflated to 130 pounds per square inch.</p> <p>The Michelin Intermittent Service Rating maximum load capacity shall be 21,400 pounds per axle with a maximum speed of 65 miles per hour when properly inflated to 130 pounds per square inch.</p> <p>The Michelin Intermittent Service Rating maximum speed capacity shall be 20,000 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 130 pounds per square inch.</p> <p>The Michelin Intermittent Service Rating limits the operation of the emergency vehicle to no more than fifty (50) miles of continuous operation under maximum recommended payload, or without stopping for at least twenty (20) minutes. The emergency vehicle must reduce its speed to no more than 50 MPH after the first fifty (50) miles of travel.</p> <p><b><u>REAR TIRE</u></b></p> <p>The rear tires shall be Michelin 12R-22.5 16PR "H" tubeless radial XDN2 all-weather tread.</p> <p>The rear tire stamped load capacity shall be 27,120 pounds per axle with a nominal speed rating of 75 miles per hour when properly inflated to 120 pounds per square inch.</p> <p>The Michelin Intermittent Service Rating maximum load capacity shall be 29,020 pounds per axle with a maximum speed of 75 miles per hour when properly inflated to 120 pounds per square inch.</p> <p>The Michelin Intermittent Service Rating maximum speed capacity shall match the nominal speed rating.</p> <p>The Michelin Intermittent Service Rating limits the operation of the emergency vehicle to no more than fifty (50) miles of continuous operation under maximum recommended payload, or without stopping for at least twenty (20) minutes. The emergency vehicle must reduce its speed to no more than 50 MPH after the first fifty (50) miles of travel.</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**REAR AXLE RATIO**

The rear axle ratio shall be 5.38:1.

**TIRE PRESSURE INDICATOR**

There shall be electronic chrome LED valve caps shipped loose for installation by the OEM which shall illuminate with a red LED when tire pressure drops 8psi provided. The valve caps are self-calibrating and set to the pressure of the tire upon installation.

**FRONT WHEEL**

The front wheels shall be Accuride hub piloted, 22.50 inch X 9.00 inch steel wheels. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts.

**WHEEL PAINT**

The front steel wheels shall be pretreated in a zinc phosphate bath, coated with a cathode electro deposited white primer base coat (E-Coat). The E-Coat shall exceed 336 hours under industry standard ASTM salt spray testing.

The wheels shall then be finish painted gloss black by the chassis manufacturer.

**REAR WHEEL**

The rear wheels shall be Accuride hub piloted, heavy duty, 22.50 inch X 8.25 inch steel wheels. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts.

**WHEEL PAINT**

The rear steel wheels shall be pretreated in a zinc phosphate bath, coated with a cathode electro deposited white primer base coat (E-Coat). The E-Coat shall exceed 336 hours under industry standard ASTM salt spray testing.

The wheels shall then be finish painted gloss black by the chassis manufacturer.

**BRAKE SYSTEM**

A rapid build-up air brake system shall be provided. The air brakes shall include, at a minimum, a two (2) air tank, three (3) reservoir system with a total of 4152 cubic inch of air capacity. A floor mounted treadle valve shall be mounted inside the cab for graduated control of applying and releasing the brakes. An inversion valve shall be installed to provide a service brake application in the unlikely event of primary air supply loss. All air reservoirs provided on the chassis shall be labeled for identification.

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

The rear axle spring brakes shall automatically apply in any situation when the air pressure falls below 25 PSI and shall include a mechanical means for releasing the spring brakes when necessary. An audible alarm shall designate when the system air pressure is below 60 PSI.

A four (4) sensor, four (4) modulator anti-lock braking system (ABS) shall be installed on the front and rear axles in order to prevent the brakes from locking or skidding while braking during hard stops or on icy or wet surfaces. This in turn shall allow the driver to maintain steering control under heavy braking and in most instances, shorten the braking distance. The electronic monitoring system shall incorporate diagonal circuitry which shall monitor wheel speed during braking through a sensor and tone ring on each wheel. A dash mounted ABS lamp shall be provided to notify the driver of a system malfunction. The ABS system shall automatically disengage the auxiliary braking system device when required. The speedometer screen shall be capable of reporting all active defaults using PID/SID and FMI standards.

Additional safety shall be accommodated through Automatic Traction Control (ATC) which shall be installed on the single rear axle. The ATC system shall apply the ABS when the drive wheels lose traction. The system shall scale the electronic engine throttle back to prevent wheel spin while accelerating on ice or wet surfaces.

A momentary rocker style switch shall be provided and properly labeled "mud/snow". When the switch is pressed once, the system shall allow a momentary wheel slip to obtain traction under extreme mud and snow conditions. During this condition the ATC light and the light on the rocker switch shall blink continuously notifying the driver of activation. Pressing the switch again shall deactivate the mud/snow feature.

The Electronic Stability Control (ESC) unit is a functional extension of the electronic braking system. It is able to detect any skidding of the vehicle about its vertical axis as well as any rollover tendency. The control unit comprises an angular-speed sensor that measures the vehicle's motion about the vertical axis, caused, for instance, by cornering or by skidding on a slippery road surface. An acceleration sensor measures the vehicle's lateral acceleration. The Controller Area Network (CAN) bus provides information on the steering angle. On the basis of lateral acceleration and steering angle, an integrated microcontroller calculates a theoretical angular speed for the stable vehicle condition.

### **FRONT BRAKES**

The front brakes shall be Meritor EX225 Disc Plus disc brakes with 17.00 inch vented rotors.

### **REAR BRAKES**

The rear brakes shall be Meritor 16.50 inch X 8.63 inch S-cam drum type. The brakes shall feature a cast iron shoe.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**PARK BRAKE**

Upon application of the push-pull valve in the cab, the rear brakes will engage via mechanical spring force. This is accomplished by dual chamber rear brakes, satisfying the FMVSS parking brake requirements.

**PARK BRAKE CONTROL**

A Meritor-Wabco manual hand control push-pull style valve shall operate the parking brake.

The parking brake actuation valve shall be mounted to the left side of the engine tunnel integrated into the transmission shift pod console within easy access of the driver.

**REAR BRAKE SLACK ADJUSTERS**

The rear brakes shall include Meritor automatic slack adjusters installed on the axle which features a simple, durable design offering reduced weight. The automatic slack adjusters shall feature a manual adjusting nut which cannot inadvertently be backed off and threaded grease fittings for easy serviceability.

**AIR DRYER**

The brake system shall include a Wabco System Saver 1200 air dryer with an integral 100 watt heater with a Metri-Pack sealed connector. The air dryer incorporates an internal turbo cutoff valve that closes the path between the air compressor and air dryer purge valve during the compressor "unload" cycle. The turbo cutoff valve allows purging of moisture and contaminants without the loss of turbo boost pressure. The air dryer shall be located on the right hand frame rail forward of the front wheel behind the right hand cab step.

**FRONT BRAKE CHAMBERS**

The front brakes shall be provided with MGM type 24 long stroke brake chambers.

**REAR BRAKE CHAMBERS**

The rear axle shall include TSE 30/36 brake chambers which shall convert the energy of compressed air into mechanical force and motion. This shall actuate the brake camshaft, which in turn shall operate the foundational brake mechanism forcing the brake shoes against the brake drum. The TSE Type 36 brake chamber has a 36.00 square inch effective area.

**AIR COMPRESSOR**

The air compressor provided for the engine shall be a Wabco® SS318 single cylinder pass-through drive type compressor which shall be capable of producing 18.7 CFM at 1200 engine RPMs. The air compressor shall feature a higher delivery efficiency translating to more air delivery per horsepower absorbed. The compressor shall include an aluminum cylinder head which shall improve cooling, reduce weight and decrease carbon formation. Superior piston



## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

and bore finishing technology shall reduce oil consumption and significantly increasing the system component life.

### **AIR GOVERNOR**

An air governor shall be provided to control the cut-in and cut-out pressures of the engine mounted air compressor. The governor shall be calibrated to meet FMVSS requirements. The air governor shall be located on the air dryer bracket.

### **MOISTURE EJECTORS**

Manual pet-cock type drain valves shall be installed on all reservoirs of the air supply system.

### **AIR SUPPLY LINES**

The air system on the chassis shall be plumbed with color coded reinforced nylon tubing air lines. The primary (rear) brake line shall be green, the secondary (front) brake line red, the parking brake line orange and the auxiliary (outlet) will be blue.

Push to connect type fittings shall be used on the nylon tubing. All drop hoses shall include fiber reinforced neoprene covered hoses.

### **WHEELBASE**

The chassis wheelbase shall be 188.50 inches.

### **REAR OVERHANG**

The chassis rear overhang shall be 47.00 inches.

### **FRAME**

The frame shall consist of double rails running parallel to each other with cross members forming a ladder style frame. The frame rails shall be formed in the shape of a "C" channel, with the outer rail measuring 10.25 inches high X 3.50 inches deep upper and lower flanges X 0.38 inches thick with an inner channel of 9.44 inches high X 3.13 inches deep and 0.38 inches thick. Each rail shall be constructed of 110,000 psi minimum yield high strength low alloy steel. Each double rail section shall be rated by a Resistance Bending Moment (RBM) minimum of 3,213,100 inch pounds and have a minimum section modulus of 29.21 cubic inches. The frame shall measure 35.00 inches in width.

Proposals calculating the frame strength using the "box method" shall not be considered.

Proposals including heat treated rails shall not be considered. Heat treating frame rails produces rails that are not uniform in their mechanical properties throughout the length of the rail. Rails made of high strength, low alloy steel are already at the required yield strength prior to forming the rail.

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

A minimum of seven (7) fully gusseted 0.25 inch thick cross members shall be installed. The inclusion of the body mounting, or bumper mounting shall not be considered as a cross member. The cross members shall be attached using zinc coated grade 8 fasteners. The bolt heads shall be flanged type, held in place by distorted thread flanged lock nuts. Each cross member shall be mounted to the frame rails utilizing a minimum of 0.25 inch thick gusset reinforcement plates at all corners balancing the area of force throughout the entire frame.

Any proposals not including additional reinforcement for each cross member shall not be considered.

All relief areas shall be cut in with a minimum 2.00 inch radius at intersection points with the edges ground to a smooth finish to prevent a stress concentration point.

### **FRAME PAINT**

The frame shall be powder coated black prior to any attachment of components.

All powder coatings, primers and paint shall be compatible with all metals, pretreatments and primers used. The cross hatch adhesion test per ASTM D3359 shall not have a fail of more than ten (10) squares. The pencil hardness test per ASTM D3363 shall have a final post-curved pencil hardness of H-2H. The direct impact resistance test per ASTM D2794 shall have an impact resistance of 120.00 inches per pound at 2 mils.

Any proposals offering painted frame with variations from the above process shall not be accepted. The film thickness of vendor supplied parts shall also be sufficient to meet the performance standards as stated above.

### **FRAME ASSEMBLY STRUCTURAL**

Purchaser shall receive a Frame Assembly Structural Five (5) Years limited warranty in accordance with, and subject to, warranty certificate RFW0301. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request.

### **FRAME RAIL CORROSION**

Purchaser shall receive a Frame Rail Corrosion (Powder Coat) Three (3) Years or 48,000 Miles limited warranty in accordance with, and subject to, warranty certificate RFW0311. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request.

### **FRAME COMPONENTS CORROSION**

Purchaser shall receive a Frame Components Corrosion (Powder Coat) One (1) Year or 18,000 Miles limited warranty in accordance with, and subject to, warranty certificate RFW0313. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request.

<b>Fannin County Fire-Rescue</b>	<b>Bidder Complies</b>	
	Yes	No
<p><b><u>FRONT BUMPER</u></b></p> <p>A one piece, two (2) rib wrap-around style, polished stainless steel front bumper shall be provided. The material shall be 10 gauge 304 stainless steel, 12.00 inches high and 99.00 inches wide.</p> <p><b><u>FRONT BUMPER EXTENSION LENGTH</u></b></p> <p>The front bumper shall be extended approximately 24.00 inches ahead of the cab.</p> <p><b><u>FRONT BUMPER APRON</u></b></p> <p>The 24.00 inch extended front bumper shall include an apron constructed of 0.19 inch thick embossed aluminum tread plate.</p> <p>The apron shall be installed between the bumper and the front face of the cab affixed using stainless steel bolts attaching the apron to the top bumper flange.</p> <p><b><u>FRONT BUMPER COMPARTMENT CENTER</u></b></p> <p>The front bumper shall include a compartment in the bumper apron located in the center between the frame rails which may be used as a hose well. The compartment shall be constructed of 0.13 inch 5052-H32 grade aluminum and shall include drain holes in the bottom corners to allow excess moisture to escape. The compartment shall include a cover constructed of 0.19 inch thick bright embossed aluminum tread plate.</p> <p><b><u>FRONT BUMPER COMPARTMENT COVER HARDWARE</u></b></p> <p>The front bumper compartment cover(s) shall include gas cylinder stays which shall hold the cover open. Each cover shall be held in the closed position via a D-ring style latch.</p> <p><b><u>MECHANICAL SIREN</u></b></p> <p>The front bumper shall include an electro mechanical Federal Q2B™ siren, which shall be streamlined, chrome-plated and shall produce 123 decibels of sound at 10.00 feet. The Q2B™ siren produces a distinctive warning sound that is recognizable at long distances. A unique clutch design provides a longer coast down sound while reducing the amp draw to 100 amps. The siren shall measure 10.50 inches wide X 10.00 inches high X 14.00 inches deep. The siren shall include a pedestal mount to surface mount on a horizontal surface.</p> <p><b><u>MECHANICAL SIREN LOCATION</u></b></p> <p>The siren shall be pedestal mounted on the bumper apron on the furthest outboard section of the bumper on the driver side.</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**AIR HORN**

The front bumper shall include two (2) Hadley brand E-Tone air horns which shall measure 21.00 inches long with a 6.00 inch round flare. The air horns shall be trumpet style with a chrome finish on the exterior and a painted finish deep inside the trumpet.

**AIR HORN LOCATION**

The air horns shall be recess mounted in the front bumper face, one (1) on the right side of the bumper in the inboard position relative to the right hand frame rail and one (1) on the left side of the bumper in the inboard position relative to the left hand frame rail.

**AIR HORN RESERVOIR**

One (1) air reservoir, with a 1200 cubic inch capacity, shall be installed on the chassis to act as a supply tank for operating air horns. The reservoir shall be isolated with a 90 PSI pressure protection valve on the reservoir supply side to prevent depletion of the air to the air brake system.

**ELECTRONIC SIREN SPEAKER**

There shall be one (1) Cast Products Inc. model SA4301, 100 watt speaker provided. The speaker shall measure 6.20 inches tall X 7.36 inches wide X 3.06 inches deep. The speaker shall include a flat mounting flange which shall be polished aluminum.

**ELECTRONIC SIREN SPEAKER LOCATION**

The electronic siren speaker shall be located on the front bumper face on the right side outboard of the frame rail in the far outboard position.

**FRONT BUMPER TOW HOOKS**

Two (2) heavy duty tow hooks, painted to match the frame components, shall be installed in the rearward position out of the approach angle area, bolted directly to the side of each chassis frame rail with grade 8 bolts.

**CAB TILT SYSTEM**

The entire cab shall be capable of tilting approximately 45-degrees to allow for easy maintenance of the engine and transmission. The cab tilt pump assembly shall be located on the right side of the chassis above the battery box.

The electric-over-hydraulic lift system shall include an ignition interlock and red cab lock down indicator lamp on the tilt control which shall illuminate when holding the “Down” button to indicate safe road operation.

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes      No**

It shall be necessary to activate the master battery switch and set the parking brake in order to tilt the cab. As a third precaution the ignition switch must be turned off to complete the cab tilt interlock safety circuit.

Two (2) spring-loaded hydraulic hold down hooks located outboard of the frame shall be installed to hold the cab securely to the frame. Once the hold-down hooks are set in place, it shall take the application of pressure from the hydraulic cab tilt lift pump to release the hooks.

Two (2) cab tilt cylinders shall be provided with velocity fuses in each cylinder port. The cab tilt pivots shall be 1.90 inch ball and be anchored to frame brackets with 1.25 inch diameter studs.

A steel safety channel assembly, painted safety yellow shall be installed on the right side cab lift cylinder to prevent accidental cab lowering. The safety channel assembly shall fall over the lift cylinder when the cab is in the fully tilted position. A cable release system shall also be provided to retract the safety channel assembly from the lift cylinder to allow the lowering of the cab.

### **CAB TILT CONTROL RECEPTACLE**

The cab tilt control cable shall include a receptacle which shall be temporarily located on the right hand chassis rail rear of the cab to provide a place to plug in the cab tilt remote control pendant. The tilt pump shall include 8.00 feet of cable with a six (6) pin Deutsch receptacle with a cap.

The remote control pendant shall include 20.00 feet of cable with a mating Deutsch connector. The remote control pendant shall be shipped loose with the chassis.

### **CAB TILT LOCK DOWN INDICATOR**

The cab dash shall include a message located within the dual air pressure gauge which shall alert the driver when the cab is unlocked and ajar. The alert message shall cease to be displayed when the cab is in the fully lowered position and the hold down hooks are secured and locked to the cab mounts.

In addition to the alert message an audible alarm shall sound when the cab is unlocked and ajar with the parking brake released.

### **CAB WINDSHIELD**

The cab windshield shall have a surface area of 2825.00 square inches and be of a two (2) piece wraparound design for maximum visibility.

The glass utilized for the windshield shall include standard automotive tint. The left and right windshield shall be fully interchangeable thereby minimizing stocking and replacement costs.

Each windshield shall be installed using black self-locking window rubber.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**GLASS FRONT DOOR**

The front cab doors shall include a window which is 27.00 inches in width X 26.00 inches in height. These windows shall have the capability to roll down completely into the door housing. This shall be accomplished manually utilizing a crank style handle on the inside of the door. A reinforced window regulator assembly shall be provided for severe duty use.

There shall be an irregular shaped fixed window which shall measure 2.50 inches wide at the top, 8.00 inches wide at the bottom X 26.00 inches in height, more commonly known as “cozy glass” ahead of the front door roll down windows.

The windows shall be mounted within the frame of the front doors trimmed with a black anodized ring on the exterior.

**GLASS TINT FRONT DOOR**

The windows located in the left and right front doors shall have a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

**GLASS REAR DOOR RH**

The rear right hand side door shall include a window which is 27.00 inches in width X 26.00 inches in height. This window shall roll up and down manually utilizing a crank style handle on the inside of the door. A reinforced window regulator assembly shall be provided for severe duty use.

**GLASS TINT REAR DOOR RIGHT HAND**

The window located in the right hand side rear door shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

**GLASS REAR DOOR LH**

The rear left hand side door shall include a window which is 27.00 inches in width X 26.00 inches in height. This window shall roll up and down manually utilizing a crank style handle on the inside of the door. A reinforced window regulator assembly shall be provided for severe duty use.

**GLASS TINT REAR DOOR LEFT HAND**

The window located in the left hand side rear door shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

**GLASS SIDE MID RH**

The cab shall include a window on the right side behind the front and ahead of the crew door which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

within this space and shall be rectangular in shape. The window shall be mounted using self-locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

**GLASS TINT SIDE MID RIGHT HAND**

The window located on the right hand side of the cab between the front and rear doors shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

**GLASS SIDE MID LH**

The cab shall include a window on the left side behind the front door and ahead of the crew door and above the wheel well which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

**GLASS TINT SIDE MID LEFT HAND**

The window located on the left hand side of the cab between the front and rear doors shall include a standard green automotive tint which shall allow seventy-five percent (75%) light transmittance.

**CLIMATE CONTROL**

The cab shall include a 57,500 BTU @ 425 CFM front overhead heater/defroster which shall be provided and installed above the windshield between the sun visors.

The cab shall also include a combination heater air-conditioning unit mounted on the engine tunnel. This unit shall offer eight (8) adjustable louvers, four (4) forward facing and four (4) rearward facing, a temperature control valve and two (2) blowers offering three (3) speeds which shall be capable of circulating 550 cubic feet of air per minute. The unit shall be rated for 42,500 BTU/Hr of cooling and 36,000 BTU/Hr of heating.

All defrost/heating systems shall be plumbed with one (1) seasonal shut-off valve at the front corner on the right side of the cab.

The air conditioner lines shall be a mixture of custom bend zinc coated steel fittings and Aeroquip flexible hose with Aeroquip EZ clip fittings.

**CLIMATE CONTROL DRAIN**

The climate control system shall include a gravity drain for water management. The gravity drain shall remove condensation from the air conditioning system without additional mechanical assistance.

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>CLIMATE CONTROL ACTIVATION</u></b></p> <p>The heating and defrosting controls shall be located on the front overhead climate control unit. There shall be additional heating and air conditioning controls located on the engine tunnel mounted climate control unit.</p> <p><b><u>A/C CONDENSER LOCATION</u></b></p> <p>A roof mounted A/C condenser shall be installed centered on the cab forward of the raised roof against the slope rise.</p> <p><b><u>A/C COMPRESSOR</u></b></p> <p>The air-conditioning compressor shall be a belt driven, engine mounted, open type compressor that shall be capable of producing a minimum of 32,000 BTU at 1500 engine RPMs. The compressor shall utilize R-134A refrigerant and PAG oil.</p> <p><b><u>UNDER CAB INSULATION</u></b></p> <p>The underside of the cab tunnel surrounding the engine shall be lined with multi-layer insulation, engineered for application inside diesel engine compartments.</p> <p>The insulation shall act as a noise barrier, absorbing noise thus keeping the decibel level in the cab well within NFPA recommendations. As an additional benefit, the insulation shall assist in sustaining the desired temperature within the cab interior.</p> <p>The engine tunnel insulation shall measure approximately 0.30 inch thick including a multi-layer foil faced glass cloth and polyester fiber layer. The foil surface acts as protection against heat, moisture and other contaminants. The insulation shall meet or exceed FMVSS 302 flammability test.</p> <p>The insulation shall be cut precisely to fit each section and sealed for additional heat and sound deflection. The insulation shall be held in place by acrylic pressure sensitive adhesive.</p> <p><b><u>INTERIOR TRIM FLOOR</u></b></p> <p>The floor of the cab shall be covered with a multi-layer mat consisting of 0.25 inch thick sound absorbing closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The covering shall be held in place by a pressure sensitive adhesive and aluminum trim molding. All exposed seams shall be sealed with silicone caulk matching the color of the floor mat to reduce the chance of moisture and debris retention.</p> <p><b><u>INTERIOR TRIM</u></b></p> <p>The cab interior shall include trim on the front ceiling, rear crew ceiling, and the cab walls. It shall be easily removable to assist in maintenance. The trim shall be constructed of insulated vinyl over a hard board backing.</p>		



## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

### **REAR WALL INTERIOR TRIM**

The rear wall of the cab shall be trimmed with vinyl.

### **HEADER TRIM**

The cab interior shall feature header trim over the driver and officer dash constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum.

### **TRIM CENTER DASH**

The main center dash area shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate. There shall be four (4) holes located on the top of the dash near each outer edge of the electrical access cover for ventilation.

### **TRIM LH DASH**

The left hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate for a perfect fit around the instrument panel. For increased occupant protection the extreme duty left hand dash utilizes patent pending break away technology to reduce rigidity in the event of a frontal crash. The left hand dash shall offer lower vertical surface area to the left and right of the steering column to accommodate control panels.

### **TRIM RH DASH**

The right hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate and shall include a glove compartment with a hinged door and a Mobile Data Terminal (MDT) provision. The glove compartment size will measure 14.00 inches wide X 6.38 inches high X 5.88 inches deep. The MDT provision shall be provided above the glove compartment.

### **ENGINE TUNNEL TRIM**

The cab engine tunnel shall be covered with a multi-layer mat consisting of 0.25 inch closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The mat shall be held in place by pressure sensitive adhesive. The engine tunnel mat shall be trimmed with anodized aluminum stair nosing trim for an aesthetically pleasing appearance.

### **POWER POINT DASH MOUNT**

The cab shall include a 12 volt cigarette lighter type receptacle in the cab dash to provide a power source for 12 volt electrical equipment. The cab shall also include one (1) Blue Sea dual universal serial bus (USB) charging receptacle in the cab dash switch panel to provide a power source for USB chargeable electrical equipment. The USB port shall be capable of a 5 Volt-4.8 amp total output. The receptacles shall be wired battery direct.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**STEP TRIM**

Each cab entry door shall include a three-step entry. The first step closest to the ground shall be constructed of polished 5032 H32 aluminum Grip Strut® grating with angled outer corners. The step shall feature a splash guard to reduce water and debris from splashing in to the step. The splash guard shall have an opening on the outer edge to allow debris and water to flow through rather than becoming trapped within the stepping surface. The lower step shall be mounted to a frame which is integral with the construction of the cab for rigidity and strength. The middle step shall be integral with the cab construction and shall be trimmed with a Flex-Tred® adhesive grit surface material.

**UNDER CAB ACCESS DOOR**

The cab shall include an access door in the left crew step riser constructed of DA finish aluminum with a push and turn latch. The under-cab access door shall provide access to the diesel exhaust fluid fill.

**INTERIOR DOOR TRIM**

The interior trim on the doors of the cab shall consist of an aluminum panel constructed of Marine Grade 5052-H32 0.13 of an inch thick aluminum plate. The door panels shall include a painted finish.

**CAB DOOR TRIM REFLECTIVE**

The interior of each door shall include high visibility reflective tape. A white reflective tape shall be provided vertically along the rear outer edge of the door. The lowest portion of each door skin shall include a reflective tape chevron with red and white stripes and a manufacture logo. The chevron tape shall measure 6.00 inches in height.

**INTERIOR GRAB HANDLE "A" PILLAR**

There shall be two (2) rubber covered 11.00 inch grab handles installed inside the cab, one on each "A" post at the left and right door openings. The left handle shall be located 7.88 inches above the bottom of the door window opening and the right handle shall be located 2.88 inches above the bottom of the door window opening. The handles shall assist personnel in entering and exiting the cab.

**INTERIOR GRAB HANDLE FRONT DOOR**

Each front door shall include one (1) ergonomically contoured 9.00 inch cast aluminum handle mounted horizontally on the interior door panels. The handles shall feature a textured black powder coat finish to assist personnel entering and exiting the cab.

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>INTERIOR GRAB HANDLE REAR DOOR</u></b></p> <p>A black powder coated cast aluminum assist handle shall be provided on the inside of each rear crew door. A 30.00 inch long handle shall extend horizontally the width of the window just above the window sill. The handle shall assist personnel in exiting and entering the cab.</p> <p><b><u>INTERIOR SOFT TRIM COLOR</u></b></p> <p>The cab interior soft trim surfaces shall be gray in color.</p> <p><b><u>INTERIOR TRIM SUNVISOR</u></b></p> <p>The header shall include two (2) sun visors, one each side forward of the driver and officer seating positions above the windshield. Each sun visor shall be constructed of Masonite and covered with padded vinyl trim.</p> <p><b><u>INTERIOR FLOOR MAT COLOR</u></b></p> <p>The cab interior floor mat shall be gray in color.</p> <p><b><u>CAB PAINT INTERIOR DOOR TRIM</u></b></p> <p>The inner door panel surfaces shall be painted with multi-tone silver gray texture finish.</p> <p><b><u>HEADER TRIM INTERIOR PAINT</u></b></p> <p>The metal surfaces in the header area shall be coated with multi-tone silver gray texture finish.</p> <p><b><u>TRIM CENTER DASH INTERIOR PAINT</u></b></p> <p>The entire center dash shall be coated with multi-tone silver gray texture finish. Any accessory pods attached to the dash shall also be painted this color.</p> <p><b><u>TRIM LH DASH INTERIOR PAINT</u></b></p> <p>The left hand dash shall be painted with a multi-tone silver gray texture finish.</p> <p><b><u>TRIM RIGHT HAND DASH INTERIOR PAINT</u></b></p> <p>The right hand dash shall be painted with multi-tone silver gray texture finish.</p> <p><b><u>DASH PANEL GROUP</u></b></p> <p>The main center dash area shall include three (3) removable panels located one (1) to the right of the driver position, one (1) in the center of the dash and one (1) to the left of the officer position. The center panel shall be within comfortable reach of both the driver and officer.</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**SWITCHES CENTER PANEL**

The center dash panel shall include twelve (12) rocker switch positons in a single row across the top of the panel.

A rocker switch with a blank legend installed directly above shall be provided for any position without a switch and legend designated by a specific option. The non-specified switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

**SWITCHES LEFT PANEL**

The left dash panel shall include eight (8) switches. There shall be six (6) switches across the top of the panel and two (2) staggered on the left hand portion of the panel. Five (5) of the top row of switches shall be rocker type and the left one (1) shall be the headlight switch. The remaining switches shall consist of one (1) windshield wiper/washer control switch and one (1) instrument lamp dimmer switch.

A rocker switch with a blank legend installed directly above shall be provided for any position not designated by a specific option. The non-designated switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

**SWITCHES RIGHT PANEL**

The right dash panel shall include no rocker switches or legends.

**SEAT BELT WARNING**

A Weldon seat belt warning system, integrated with the Vehicle Data Recorder system, shall be installed for each seat within the cab. The system shall activate a digital seat position indicator with a seat position legend and integrated audible alarm in the switch panel.

The warning system shall activate when any seat is occupied with a minimum of 60 pounds and the corresponding seat belt remains unfastened. The warning system shall also activate when any seat is occupied and the corresponding seat belt was fastened in an incorrect sequence. Once activated, the visual indicators and applicable audible alarm shall remain active until all occupied seats have the seat belts fastened.

**SEAT MATERIAL**

The Bostrom Firefighter seats shall include a covering of extra high strength, wear resistant fabric made of durable low seam Durawear Plus™ ballistic polyester. A PVC coating shall be bonded to the back side of the material to help protect the seats from UV rays and from being saturated or contaminated by fluids. Durawear Plus™ meets or exceeds specification of

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

the common trade name Imperial 1800. The material meets FMVSS 302 flammability requirements.

*If applicable, Theatre style seats located in the cab shall be high strength, wear resistant fabric made of durable ballistic polyester. A PVC coating shall be bonded to the back side of the material to help protect the seats from UV rays and from being saturated or contaminated by fluids. Common trade names for this material are Imperial 1200 and Durawear.*

### **SEAT COLOR**

All seats supplied with the chassis shall be gray in color. All seats shall include red seat belts.

### **SEAT BACK LOGO**

The seat back shall include the “manufacture” logo. The logo shall be centered on the standard headrest of the seat back and on the left side of a split headrest.

### **SEAT DRIVER**

The driver's seat shall be an H.O. Bostrom 400 Series Firefighter model seat. The seat shall feature two-way manual fore and aft adjustment with 5.00 inches of travel. The seat shall also feature integral springs to isolate shock.

The seat shall feature an all belts to seat (ABTS) safety restraint system. The ABTS feature shall include a three-point shoulder harness with the lap belt, automatic retractor and buckle as an integral part of the seat assembly. The buckle portion of the seat belt shall be mounted on a semi-rigid stalk extending from the seat base within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests set forth by FMVSS 207, 209, and 210 in effect at the time of manufacture. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity.

The materials used in construction of the seat shall also have successfully completed testing with regard to the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which dictates the allowable burning rate of materials in the occupant compartments of motor vehicles.

### **SEAT BACK DRIVER**

The driver's seat shall include a standard seat back incorporating the all belts to seat feature (ABTS). The seat back shall feature a contoured head rest.

<b>Fannin County Fire-Rescue</b>	<b>Bidder Complies</b>	
	Yes	No
<p><b><u>SEAT MOUNTING DRIVER</u></b></p> <p>The driver’s seat shall be installed in an ergonomic position in relation to the cab dash.</p> <p><b><u>SEAT OFFICER</u></b></p> <p>The officer's seat shall be an H.O. Bostrom 300 Series Firefighter model seat. The seat shall feature two-way manual adjustment and shall include a tapered and padded seat cushion. The seat shall also feature integral springs to isolate shock.</p> <p>The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt, automatic retractor and buckle as an integral part of the seat assembly.</p> <p>The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches.</p> <p>This model of seat shall have successfully completed the static load tests by FMVSS 207, 209, 210 and 302 in effect at the time of manufacture. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.</p> <p><b><u>SEAT BACK OFFICER</u></b></p> <p>The officer’s seat shall feature a SecureAll™ SCBA locking system which shall be one bracket model and store most U.S. and International SCBA brands and sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.</p> <p>The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.</p> <p>The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto- locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.</p> <p>The SecureAll™ shall include a release handle which shall be integrated into the seat cushion for quick and easy release. This shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.</p> <p>The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**SEAT MOUNTING OFFICER**

The officer’s seat shall be installed in an ergonomic position in relation to the cab dash.

**SEAT BELT ORIENTATION CREW**

The crew position seat belts shall follow the standard orientation which extends from the outboard shoulder extending to the inboard hip.

**SEAT REAR FACING OUTER LOCATION**

The crew area shall include two (2) rear facing crew seats, which include one (1) located directly behind the left side front seat and one (1) located directly behind the right side front seat.

**SEAT CREW REAR FACING OUTER**

The crew area shall include a seat in the rear facing outboard position which shall be a H.O. Bostrom 300 Series Firefighter model seat. The seat shall feature a tapered and padded seat, and cushion.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

**SEAT BACK REAR FACING OUTER**

The rear facing outboard seat shall feature a Bostrom SecureAll™ self contained breathing apparatus (SCBA) locking system which shall store most U.S. and International SCBA brands and bottle sizes while in transit or for storage within the seat back. The bracket shall be easily

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the center of the bottom seat cushion for easy access and to eliminate hooking the release handle with clothing or other equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

### **SEAT MOUNTING REAR FACING OUTER**

The rear facing outer seats shall offer special mounting positions which shall be 2.00 inches towards the rear wall offering additional space between the front seats and the outer rear facing seats.

### **WINDSHIELD WIPER SYSTEM**

The cab shall include a triple arm linkage wiper system which shall clear the windshield of water, ice and debris. There shall be two (2) windshield wipers; each shall be affixed to a radial arm. The wiper motor shall be activated by an intermittent wiper control located within easy reach of the driver's position.

### **ELECTRONIC WINDSHIELD FLUID LEVEL INDICATOR**

The windshield washer fluid level shall be monitored electronically. When the washer fluid level becomes low the yellow "Check Message Center" indicator light on the instrument panel shall illuminate and the message center in the dual air pressure gauge shall display a "Check Washer Fluid Level" message.

### **CAB DOOR HARDWARE**

The cab entry doors shall be equipped with exterior pull handles, suitable for use while wearing firefighter gloves. The handles shall be made of a fiber reinforced plastic composite with a black matt finish.

The interior exit door handles shall be flush paddle type with a black finish, which are incorporated into the upper door panel.



<b>Fannin County Fire-Rescue</b>	<b>Bidder Complies</b>	
	<b>Yes</b>	<b>No</b>
<p>All cab entry doors shall include locks which are keyed alike. The door locks shall be designed to prevent accidental lockout.</p> <p><b><u>DOOR LOCKS</u></b></p> <p>Each cab entry door shall include a manually operated door lock. Each door lock may be actuated from the inside of the cab by means of a red knob located on the paddle handle of the respective door or by using a TriMark key from the exterior. The door locks are designed to prevent accidental lock out.</p> <p><b><u>GRAB HANDLES</u></b></p> <p>The cab shall include one (1) 18.00 inch knurled, anti-slip, one-piece exterior assist handle behind each cab door. The grab handle shall be made of SAE 304 stainless steel and be 1.25 inch diameter to enable non-slip assistance with a gloved hand.</p> <p><b><u>REARVIEW MIRRORS</u></b></p> <p>Retrac Aerodynamic West Coast style dual vision mirror heads model 613305 shall be provided and installed on each of the front cab doors.</p> <p>The mirrors shall be mounted via 1.00 inch diameter tubular stainless steel arms to provide a rigid mounting to reduce mirror vibration.</p> <p>The mirrors shall measure 8.00 inches wide X 19.00 inches high and shall include an integral convex mirrors installed in the mirror head below the flat glass to provide a wider field of vision. The flat and convex mirrors shall be motorized with remote horizontal and vertical adjustment. The control switches shall be mounted within easy reach of the driver. The flat and convex mirrors shall be heated for defrosting in severe cold weather conditions.</p> <p>The mirrors shall be constructed of a vacuum formed chrome plated ABS plastic housing that is corrosion resistant and shall include the finest quality non-glare glass.</p> <p><b><u>REARVIEW MIRROR HEAT SWITCH</u></b></p> <p>The heat for the rearview mirrors shall be controlled through a rocker switch on the dash in the switch panel.</p> <p><b><u>CAB FENDER</u></b></p> <p>Full width wheel well liners shall be installed on the extruded cab to limit road splash and enable easier cleaning. Fender shall consist of an inner liner 16.00 inches wide made of ABS composite and an outer fenderette 3.50 inches wide made of polished aluminum.</p> <p><b><u>CAB EXTERIOR FRONT &amp; SIDE EMBLEMS</u></b></p> <p>The cab shall include one (1) manufacture emblem installed on the front grille.</p>		

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

### **IGNITION**

A master battery system with a keyless start ignition system shall be provided. Each system shall be controlled by a one-quarter turn Cole Hersee switch, both of which shall be mounted to the left of the steering wheel on the dash. A chrome push type starter button shall be provided adjacent to the master battery and ignition switches.

Each switch shall illuminate a green LED indicator light on the dash when the respective switch is placed in the "ON" position.

The starter button shall only operate when both the master battery and ignition switches are in the "ON" position.

### **BATTERY**

The single start electrical system shall include three (3) Harris BCI 31 925 CCA batteries with a 210 minute reserve capacity and 4/0 welding type dual path starter cables per SAE J541.

### **BATTERY TRAY**

The batteries shall be installed on a steel battery tray located on the left side of the chassis, securely bolted to the frame rails. The battery tray shall be coated with the same material as the frame.

The battery tray shall include drain holes in the bottom for sufficient drainage of water. A durable, non-conducting, interlocking mat made by Dri-Dek shall be installed in the bottom of the tray to allow for air flow and help prevent moisture build up. The batteries shall be held in place by non-conducting phenolic resin hold down boards.

### **BATTERY BOX COVER**

The battery box shall include a steel cover which protects the top of the batteries on the left hand side of the vehicle. The cover shall include flush latches which shall keep the cover secure as well as a black powder coated handle for convenience when opening.

### **BATTERY CABLE**

The starting system shall include cables which shall be protected by 275 degree F. minimum high temperature flame retardant loom, sealed at the ends with heat shrink and sealant.

The battery terminals shall not be utilized for auxiliary connections. The only acceptable auxiliary connections shall be for the cross over link from the left bank to the right bank, power for jumper studs and starter cables. All other auxiliary connections will use remote studs mounted in the battery box area. There shall be four (4) remote studs labeled as Common Power, Common Ground, Clean Power, and Clean Ground.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**BATTERY JUMPER STUD**

The starting system shall include battery jumper studs. These studs shall be located in the forward most portion of the driver's side lower step, 8.00 inches apart. The studs shall allow the vehicle to be jump started, charged, or the cab to be raised in an emergency in the event of battery failure.

**ALTERNATOR**

The charging system shall include a 320 amp Leece-Neville 12 volt alternator. The alternator shall include a self-exciting integral regulator.

**STARTER MOTOR**

The single start electrical system shall include a Delco brand starter motor.

**BATTERY CONDITIONER**

A Kussmaul Auto Charge Chief 4012 battery conditioner shall be supplied. The battery conditioner shall provide a 40 amp output for the chassis batteries and a 20 amp output circuit for accessory loads. The battery conditioner shall be mounted in the cab in the LH rear facing outer seating position and shall include a battery temperature sensor.

**BATTERY CONDITIONER DISPLAY**

A Kussmaul battery conditioner display with a digital status center display shall be integrated into the electrical inlet.

**AUXILIARY AIR COMPRESSOR**

A Kussmaul Pump 12V air compressor shall be supplied. The air compressor shall be installed under the dashboard on the right-hand side, forward of the officer's seating position. The air compressor shall be plumbed to the air brake system to maintain air pressure. The air compressor shall include an auto drain as an extra precaution to prevent moisture from entering the air system. The automatic moisture drain shall be plumbed into the system between the auxiliary air compressor pump and the air tanks.

**ELECTRICAL INLET LOCATION**

An electrical inlet shall be installed on the left hand side of cab over the wheel well.

**ELECTRICAL INLET**

A Kussmaul 20 amp super auto-eject electrical receptacle shall be supplied. It shall automatically eject the plug when the starter button is depressed.

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

A single item or an addition of multiple items must not exceed the rating of the electric inlet that it's connected to.

### **Amp Draw Reference List:**

*Kussmaul 40 LPC Charger - 5 Amps*

*Kussmaul 40/20 Charger - 8.5 Amps*

*Kussmaul 80 LPC Charger - 13 Amps*

*Kussmaul EV-40 - 6.2 Amps*

*Blue Sea P12 7532 - 7.5 Amps*

*Iota DLS-45/IQ4 - 11 Amps*

*1000W Engine Heater - 8.33 Amps*

*1500W Engine Heater - 12.5 Amps*

*120V Air Compressor - 4.2 Amps*

*120V Dometic HVAC - 15 Amps*

### **ELECTRICAL INLET CONNECTION**

The electrical inlet shall be connected to the battery conditioner.

### **ELECTRICAL INLET COLOR**

The electrical inlet connection shall include a yellow cover.

### **HEADLIGHTS**

The cab front shall include four (4) rectangular LED headlamps with separate high and low beams mounted in bright chrome bezels. Each lamp shall include a heating system that de-ices the headlight.

### **FRONT TURN SIGNALS**

The front fascia shall include two (2) Whelen model 600 4.00 inches X 6.00 inches programmable amber LED turn signals which shall be installed in an outboard position within the front fascia chrome bezel.

### **HEADLIGHT LOCATION**

The headlights shall be located on the front fascia of the cab directly below the front warning lights.

### **SIDE TURN/MARKER LIGHTS**

The sides of the cab shall include two (2) Tecniq S170 LED side marker lights which shall be provided just behind the front cab radius corners. The lights shall be amber with chrome bezels.

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>MARKER AND ICC LIGHTS</u></b></p> <p>In accordance with FMVSS, there shall be five (5) marker lamps on the front of the vehicle designating identification and clearance. There shall be five (5) face mounted lights integrated into the scene light.</p> <p><b><u>HEADLIGHT AND MARKER LIGHT ACTIVATION</u></b></p> <p>The headlights and marker lights shall be controlled through a rocker switch within easy reach of the driver. There shall be a dimmer switch within easy reach of the driver to adjust the brightness of the dash lights. The headlamps shall be equipped with the "Daytime Running" light feature, which shall illuminate the headlights when the ignition switch is in the "On" position and the parking brake is released.</p> <p><b><u>LIGHTBAR SWITCH</u></b></p> <p>The light bar shall be controlled by a rocker switch located on the switch panel. This switch shall be clearly labeled for identification.</p> <p><b><u>INTERIOR OVERHEAD LIGHTS</u></b></p> <p>The cab shall include a LED dome lamp located over each door. The lights shall include push switches on each lamp to activate both the clear and red portions of the light individually.</p> <p><b><u>INTERIOR OVERHEAD LIGHTS ACTIVATION</u></b></p> <p>The clear portion of each lamp shall be activated by opening the respective door.</p> <p><b><u>LIGHTBAR PROVISION</u></b></p> <p>There shall be one (1) light bar installed on the cab roof. The light bar shall be provided and installed by the chassis manufacturer. The light bar installation shall include a lowered mounting that shall place the light bar just above the junction box and wiring to a control switch on the cab dash.</p> <p><b><u>CAB FRONT LIGHTBAR</u></b></p> <p>The lightbar provisions shall be for one (1) Whelen brand Freedom IV LED lightbar mounted centered on the front of the cab roof. The lightbar shall be 72.00 inches in length. The lightbar shall feature six (6) red LED light modules and two (2) clear LED light modules. The entire lightbar shall feature a clear lens. The clear lights shall be disabled with park brake engaged. The cable shall exit the lightbar on the right side of the cab.</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**FRONT SCENE LIGHTS**

The front of the cab shall include one (1) HiViz model FireTech FT-B-72-ML-W LED scene light installed on the brow of the cab. The light shall feature (5) five integrated marker lights.

The housing shall be powder coated white.

**FRONT SCENE LIGHT LOCATION**

There shall be one (1) scene light mounted center on the front brow of the cab.

**FRONT SCENE LIGHTS ACTIVATION**

The front scene lighting shall be activated by individual rocker switches for each of the three (3) separate scene lighting circuits. Each circuit shall be activated independently and shall include rocker switches labeled “Front Scene”, “Front Flood”, and “Front Spotlight”.

**SIDE SCENE LIGHTS**

The side of the cab shall include two (2) Whelen 900 series 9SC0ENZR model scene lights, one (1) each side which shall be surface mounted with a chrome bezel. The Whelen lights shall offer LED lighting at a gradient 32-degree angle.

**SIDE SCENE LIGHT LOCATION**

The scene lighting located on the left and right sides of the cab shall be mounted rearward of the cab “B” pillar in the 10.00 inch raised roof portion of the cab between the front and rear crew doors.

**SIDE SCENE ACTIVATION**

The scene lights shall be activated by two (2) rocker switches located in the switch panel, one (1) for each light, and by opening the respective side cab doors.

**GROUND LIGHTS**

Each door shall include a Tecniq T44 LED ground light mounted to the underside of the cab step below each door. The lights shall include a polycarbonate lens, a housing which is vibration welded and LEDs which shall be shock mounted for extended life.

**GROUND LIGHTS**

The ground lighting shall be activated when the parking brake is set.

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

### **LOWER CAB STEP LIGHTS**

The middle step located at each door shall include a Tecniq T44 LED light which shall activate with the opening of the respective door. The lights shall include a polycarbonate lens, a housing which is vibration welded and LEDs which shall be shock mounted for extended life.

### **INTERMEDIATE STEP LIGHTS**

The intermediate step well area at the front doors shall include a TecNiq D06 LED light within a chrome housing. The front egress step lights shall provide visibility to the step well area for the first step exiting the vehicle. The Egress step lights shall activate with entry step lighting.

### **ENGINE COMPARTMENT LIGHT**

There shall be a LED NFPA compliant light mounted under the engine tunnel for area work lighting on the engine. The light shall activate automatically when the cab is tilted.

### **DO NOT MOVE APPARATUS LIGHT**

The front headliner of the cab shall include a flashing red TecNiq K50 LED light clearly labeled "Do Not Move Apparatus". In addition to the flashing red light, an audible alarm shall be included which shall sound while the light is activated.

The flashing red light shall be located centered left to right for greatest visibility.

The light and alarm shall be interlocked for activation when either a cab door is not firmly closed, or an apparatus compartment door is not closed, and the parking brake is released.

### **MASTER WARNING SWITCH**

A master switch shall be included in the main rocker switch panel. The switch shall be a rocker type, red in color and labeled "Master" for identification. The switch shall feature control over all devices wired through it. Any warning device switch left in the "ON" position shall automatically power up when the master switch is activated.

### **HEADLIGHT FLASHER**

An alternating high beam headlight flashing system shall be installed into the high beam headlight circuit which shall allow the high beams to flash alternately from left to right.

Deliberate operator selection of high beams will override the flashing function until low beams are again selected. Per NFPA, these clear flashing lights will also be disabled "On Scene" when the park brake is applied.

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>HEADLIGHT FLASHER SWITCH</u></b></p> <p>The flashing headlights shall be activated through a rocker switch on the switch panel. The rocker switch shall be clearly labeled for identification.</p> <p><b><u>INBOARD FRONT WARNING LIGHTS</u></b></p> <p>The cab front fascia shall include two (2) Whelen M6 Super LED front warning lights in the left and right inboard positions. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the front fascia of the cab within a chrome bezel</p> <p><b><u>INBOARD FRONT WARNING LIGHTS COLOR</u></b></p> <p>The warning lights mounted on the cab front fascia in the inboard positions shall be red with a clear lens.</p> <p><b><u>FRONT WARNING SWITCH</u></b></p> <p>The front warning lights shall be controlled via rocker switch on the panel. This switch shall be clearly labeled for identification.</p> <p><b><u>INTERSECTION WARNING LIGHTS</u></b></p> <p>The chassis shall include two (2) Whelen M6 series Super LED intersection warning lights, one (1) each side. The lights shall feature multiple flash patterns including steady burn.</p> <p><b><u>INTERSECTION WARNING LIGHTS COLOR</u></b></p> <p>The intersection lights shall be red with a clear lens.</p> <p><b><u>INTERSECTION WARNING LIGHTS LOCATION</u></b></p> <p>The intersection lights shall be mounted on the side of the bumper in the rearward position.</p> <p><b><u>SIDE AND INTERSECTOR WARNING SWITCH</u></b></p> <p>The side and intersector warning lights shall be controlled by a rocker switch on the switch panel. This switch shall be clearly labeled for identification.</p> <p><b><u>SIREN CONTROL HEAD</u></b></p> <p>A Whelen 295HFS2 electronic siren control head with remote amplifier shall be provided and flush mounted in the switch panel with a location specific to the customer’s needs. The siren shall feature 200-watt output, hands free mode and shall be in “standby” mode awaiting instruction. The siren shall offer radio broadcast, public address, wail, yelp, or piercer tones</p>		



**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

and hands free operation which shall allow the operator to turn the siren on and off from the horn ring if a horn/siren selector switch option is also selected.

**STEERING WHEEL HORN BUTTON SELECTOR SWITCH**

A rocker switch shall be installed in the switch panel between the driver and officer to allow control of either the electric horn or the air horn from the steering wheel horn button.

**AUDIBLE WARNING LH FOOT SWITCH**

Two (2) foot actuated switches shall be supplied for installation in the front section of the cab for driver actuation. One (1) switch shall be wired to actuate the air horn(s) and one (1) switch the mechanical siren(s).

**AIR HORN FOOT SWITCH LH**

The air horn foot switch shall be a Linemaster model 491-S.

**AIR HORN FOOT SWITCH LH LOCATION**

The air horn foot switch shall be located on the left hand side accessible to the driver between the steering column and the door.

**AIR HORN FOOT SWITCH LH POSITION**

The air horn foot switch shall be positioned inboard of any other foot switch, if applicable.

**MECHANICAL SIREN FOOT SWITCH LH**

The mechanical siren foot switch shall be a Linemaster model 491-S.

**MECHANICAL SIREN FOOT SWITCH LH LOCATION**

The mechanical siren foot switch shall be located on the left hand side accessible to the driver between the steering column and the door.

**MECHANICAL SIREN FOOT SWITCH LH POSITION**

The mechanical siren foot switch shall be positioned outboard of any other foot switch, if applicable.

**AUDIBLE WARNING LH FOOT SWITCH BRACKET**

A 30.00 degree angled foot switch bracket, wide enough to accommodate (2) foot switches, shall be installed outboard of the steering column for specified driver accessible foot switch activations.

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>AUDIBLE WARNING RH FOOT SWITCH</u></b></p> <p>Two (2) foot actuated switches shall be supplied for installation in the front section of the cab for officer actuation. One (1) switch shall be wired to actuate the air horn(s) and one (1) switch the mechanical siren(s).</p> <p><b><u>AIR HORN FOOT SWITCH RH</u></b></p> <p>The air horn foot switch shall be a Linemaster model 491-S.</p> <p><b><u>AIR HORN FOOT SWITCH RH LOCATION</u></b></p> <p>The air horn foot switch shall be temporarily tied up with a coiled wire drop at the firewall inboard for installation by the customer on the right hand side accessible to the officer.</p> <p><b><u>MECHANICAL SIREN FOOT SWITCH RH</u></b></p> <p>The mechanical siren foot switch shall be a Linemaster model 491-S.</p> <p><b><u>MECHANICAL SIREN FOOT SWITCH RH LOCATION</u></b></p> <p>The mechanical siren foot switch shall be temporarily tied up with a coiled wire drop at the firewall inboard for installation by the customer on the right hand side accessible to the officer.</p> <p><b><u>AIR HORN CIRCUIT INTERLOCK</u></b></p> <p>The air horn shall be interlocked with the park brake to prevent accidental activation on scene.</p> <p><b><u>MECHANICAL SIREN BRAKE/AUXILIARY ACTIVATION</u></b></p> <p>The mechanical siren shall be actuated by a black push button in the switch panel on the dash. A red push button siren brake control shall be provided in the switch panel on the dash.</p> <p><b><u>MECHANICAL SIREN INTERLOCK</u></b></p> <p>The siren shall only be active when master warning switch is on to prevent accidental engagement.</p> <p><b><u>BACK-UP ALARM</u></b></p> <p>An ECCO model 575 backup alarm shall be installed at the rear of the chassis with an output level of 107 dB. The alarm shall automatically activate when the transmission is placed in reverse.</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**INSTRUMENTATION**

An ergonomically designed instrument panel shall be provided. Each gauge shall be backlit with LED lamps. Stepper motor movements shall drive all gauges. The instrumentation system shall be multiplexed and shall receive ABS, engine, and transmission information over the J1939 data bus to reduce redundant sensors and wiring.

A twenty-eight (28) icon lightbar message center with integral LCD odometer/trip odometer shall be included. The odometer shall display up to 999,999.9 miles. The trip odometer shall display 9,999.9 miles. The LCD message center screen shall be capable of custom configuration by the users for displaying certain vehicle status and diagnostic functions.

The instrument panel shall contain the following gauges:

One (1) three-movement gauge displaying vehicle speed, fuel level, and Diesel Exhaust Fluid (DEF) level. The primary scale on the speedometer shall read from 0 to 100 MPH, and the secondary scale on the speedometer shall read from 0 to 160 KM/H. The scale on the fuel and DEF level gauges shall read from empty to full as a fraction of full tank capacity. Red indicator lights in the gauge and an audible alarm shall indicate low fuel or low DEF at 1/8<sup>th</sup> tank level.

One (1) three-movement gauge displaying engine RPM, and primary and secondary air system pressures shall be included. The scale on the tachometer shall read from 0 to 3000 RPM. The scale on the air pressure gauges shall read from 0 to 150 pounds per square inch (PSI) with a red line zone indicating critical levels of air pressure. Red indicator lights in the gauge and an audible alarm shall indicate low air pressure.

One (1) four-movement gauge displaying engine oil pressure, coolant temperature, voltmeter, and transmission temperature shall be included. The scale on the engine oil pressure gauge shall read from 0 to 100 pounds PSI with a red line zone indicating critical levels of oil pressure. A red indicator light in the gauge and audible alarm shall indicate low engine oil pressure. The scale on the coolant temperature gauge shall read from 100 to 250 degrees Fahrenheit (°F) with a red line zone indicating critical coolant temperatures. A red indicator light in the gauge and audible alarm shall indicate high coolant temperature. The scale on the voltmeter shall read from 9 to 18 volts with a red line zone indicating critical levels of battery voltage. A red indicator light in the gauge and an audible alarm shall indicate high or low system voltage. The low voltage alarm shall indicate when the system voltage has dropped below 11.8 volts for more than 120 seconds in accordance with the requirements of NFPA 1901. The scale on the transmission temperature gauge shall read from 100 to 300 degrees °F with a red line zone indicating critical temperatures. A red indicator light in the gauge and an audible alarm shall indicate a high transmission temperature.

The light bar portion of the message center shall include twenty-eight (28) LED backlit indicators. The lightbar shall be split with fourteen (14) indicators on each side of the LCD message screen. The lightbar shall contain the following indicators and produce the following audible alarms when supplied in conjunction with applicable configurations:

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>RED INDICATORS</u></b>            Stop Engine - indicates critical engine fault            Air Filter Restricted - indicates excessive engine air intake restriction            Park Brake - indicates parking brake is set            Seat Belt - indicates a seat is occupied and corresponding seat belt remains unfastened            Low Coolant - indicates critically low engine coolant            Cab Tilt Lock - indicates the cab tilt system locks are not engaged.</p> <p><b><u>AMBER INDICATORS</u></b>            Malfunction Indicator Lamp (MIL) - indicates an engine emission control system fault            Check Engine - indicates engine fault            Check Transmission - indicates transmission fault            Anti-Lock Brake System (ABS) - indicates anti-lock brake system fault            High exhaust system temperature – indicates elevated exhaust temperatures            Water in Fuel - indicates presence of water in fuel filter            Wait to Start - indicates active engine air preheat cycle            Windshield Washer Fluid – indicates washer fluid is low            DPF restriction - indicates a restriction of the diesel particulate filter            Regen Inhibit-indicates regeneration of the DPF has been inhibited by the operator            Range Inhibit - indicates a transmission operation is prevented and requested shift request may not occur.            SRS - indicates a problem in the supplemental restraint system            Check Message - indicates a vehicle status or diagnostic message on the LCD display requiring attention.</p> <p><b><u>GREEN INDICATORS</u></b>            Left and Right turn signal indicators            ATC - indicates low wheel traction for automatic traction control equipped vehicles, also indicates mud/snow mode is active for ATC system            High Idle - indicates engine high idle is active.            Cruise Control - indicates cruise control is enabled            OK to Pump - indicates the pump is engaged and conditions have been met for pump operations            Pump Engaged - indicates the pump transmission is currently in pump gear            Auxiliary Brake - indicates secondary braking device is active</p> <p><b><u>BLUE INDICATORS</u></b>            High Beam indicator</p> <p><b><u>AUDIBLE ALARMS</u></b>            Air Filter Restriction            Cab Tilt Lock            Check Engine            Check Transmission            Open Door/Compartment            High Coolant Temperature            High or Low System Voltage</p>		

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p>High Transmission Temperature  Low Air Pressure  Low Coolant Level  Low DEF Level  Low Engine Oil Pressure  Low Fuel  Seatbelt Indicator  Stop Engine  Water in Fuel  Extended Left/Right Turn Signal On  ABS System Fault</p> <p><b><u>BACKLIGHTING COLOR</u></b></p> <p>The instrumentation gauges and the switch panel legends shall be backlit using red LED backlighting.</p> <p><b><u>CAMERA REAR</u></b></p> <p>One (1) Audiovox Voyager heavy duty box shaped HD camera shall be shipped loose for OEM installation in the body to afford the driver a clear view to the rear of the vehicle.</p> <p>The camera system shall include a one-way communication device that shall be an integral part of the rear camera for the use of voice commands directly to the driver. The rear camera display shall activate when the vehicle’s transmission is placed in reverse.</p> <p><b><u>CAMERA DISPLAY</u></b></p> <p>The camera system shall be wired to a 7.00 inch flip down HD monitor which shall include a color display and day and night brightness modes installed above the driver position.</p> <p><b><u>CAB EXTERIOR PROTECTION</u></b></p> <p>The cab face shall have a removable plastic film installed over the painted surfaces to protect the paint finish during transport to the body manufacturer.</p> <p><b><u>FIRE EXTINGUISHER</u></b></p> <p>A 2.50 pound D.O.T approved fire extinguisher with BC rating shall be shipped loose with the cab.</p> <p><b><u>DOOR KEYS</u></b></p> <p>The cab and chassis shall include a total of four (4) door keys for the manual door locks.</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**WARRANTY**

Purchaser shall receive a Custom Chassis One (1) Year or 18,000 Miles limited warranty in accordance with, and subject to, warranty certificate RFW0101. The warranty certificate is incorporated by reference into this proposal, and included with this proposal or available upon request.

**CHASSIS OPERATION MANUAL**

There shall be two (2) digital copies of the chassis operation manual provided with the chassis. The digital data shall include a parts list specific to the chassis model.

**ENGINE AND TRANSMISSION OPERATION MANUALS**

The following manuals specific to the engine and transmission models ordered will be included with the chassis in the ship loose items:

- (1) Hard copy of the Engine Operation and Maintenance manual with digital copy
- (1) Digital copy of the Transmission Operator’s manual
- (1) Digital copy of the Engine Owner’s manual

**CAB/CHASSIS AS BUILT WIRING DIAGRAMS**

The cab and chassis shall include two (2) digital copies of wiring schematics and option wiring diagrams.

**DRIVELINE LAYOUT CONFIRMATION**

During the design phase of the chassis the manufacture Chassis driveline engineer shall submit the driveline layout to an OEM engineer to review the chassis design for any potential problems integrating the OEM body to the chassis. The OEM engineer shall provide approval to the driveline engineer prior to driveline bills of materials being released.

**EXHAUST HEAT SHIELD**

There shall be an exhaust heat shield added to the chassis provided exhaust. The shield shall terminate past the front compartment and shall incorporate a heavy duty spray on insulation under R1. With this shield, the temperature of the front compartment shall not exceed the ambient temperature.

The heat shield shall be attached to the underside of the body utilizing a flexible bracket.

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>EMS STORAGE COMPARTMENT</u></b></p> <p>There shall be one (1) EMS compartment, fabricated out of .125 inch (3.18 mm) smooth aluminum installed along the center of the rear wall in the chassis cab.</p> <p>The compartment shall be approximately 36.00 inches (914.4 mm) wide by 15.00 inches (381 mm) deep. The interior of the compartment shall feature a natural aluminum finish.</p> <p>Vertically mounted Unistrut shall be installed inside the EMS storage compartment to accommodate the installation of shelving.</p> <p>The height of the EMS compartment shall be approximately 54.00 inches (1371.6 mm) tall, dependent on cab configuration.</p> <p>There shall be a 1.00 inch high lip included around the top perimeter of the EMS compartment specified to retain equipment stored on top of the compartment by the Fire Department.</p> <p><b><u>EMS COMPARTMENT NETTING</u></b></p> <p>A cargo net, black in color, shall be provided and installed on the opening of the EMS compartment. The cargo net enclosure shall be secured along the lower edge. The net shall drop out of the way for easy cabinet access.</p> <p>The cargo net covering the compartment shall include seat belt style fasteners along the top of the cabinet for ease of entry.</p> <p><b><u>EMS COMPARTMENT LIGHTING</u></b></p> <p>Two (2) LED Tube lights model #RX-15T16-5050 shall be installed in accordance with the compartment height to offer the best lighting in the EMS cabinet.</p> <p><b><u>EMS COMPARTMENT LIGHTING ACTIVATION</u></b></p> <p>The light(s) in each compartment shall be activated by a rocker switch inside the EMS compartment.</p> <p><b><u>EMS COMPARTMENT SHELVING</u></b></p> <p>There shall be two (2) shelves in the cab EMS compartment. Each shelf shall be fabricated of .188 inch (4.76 mm) thick aluminum sheet material with the outside and inside edges flanged up to prevent equipment from sliding off. Each shelf shall be as wide as possible to allow proper attachment to unistrut channels and shall be adjustable up and down.</p> <p>Each shelf shall feature a natural finish.</p>		

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>EMS COMPARTMENT(S) EXTERIOR FINISH</u></b></p> <p>The exterior of the EMS compartment(s) specified shall feature a painted finish/color equivalent to the chassis interior unless specified otherwise.</p> <p><b><u>CHASSIS REQUIRED LABELING</u></b></p> <p>Signs that state "Occupants must be seated and belted when apparatus is in motion" shall be provided.</p> <p>They shall be visible from each seating position.</p> <p>There shall be a lubrication plate mounted inside the cab listing the type and grade of lubrication used in the following areas on the apparatus and chassis:</p> <ul style="list-style-type: none"> <li>- Engine oil</li> <li>- Engine Coolant</li> <li>- Transmission Fluid</li> <li>- Pump Transmission Lubrication Fluid</li> <li>- Drive Axle Lubrication Fluid</li> <li>- Generator Lubrication Fluid (where applicable)</li> <li>- Tire Pressures</li> </ul> <p><b><u>APPARATUS INFORMATION LABEL</u></b></p> <p>There shall be a high-visibility label installed in a location clearly detectable to the driver while in the seated position.</p> <p>The label shall indicate the following specified information.</p> <p>Overall Height (feet and inches)  Overall Length (feet and inches)  Overall GVWR (tons or metric tons)</p> <p><b><u>CAB TILT CONTROL</u></b></p> <p>There shall be a cab tilt pendant control provided and installed on the right side of the apparatus. The pendant shall be located directly behind the upper auxiliary pump access panel, accessible through a small, hinged door secured with a push button style latch.</p> <p>A label shall be provided that states "CAB TILT".</p> <p>There shall also be a cab tilt instruction plate located as close as possible to the control pendant for ease of operation.</p>		



**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**HEAT EXCHANGER**

The supplementary heat exchanger cooling system shall be provided and installed to the discharge side of the fire pump through to the engine compartment without intermixing, for absorption of excess heat.

The heat exchanger shall be adequate in size to maintain safe operating temperature of the coolant in the pump drive engine and not in excess of the engine manufacturer's temperature rating, under all pumping conditions. Appropriate drains shall be provided to allow draining the heat exchanger to prevent damage from freezing.

**TIRE CHAINS**

There shall be a set of air operated, automatic tire chains provided and installed on the rear axle. The control for the tire chains shall be located in the apparatus cab and shall be easily accessible to the driver. The chains shall be Onspot brand.

There shall be six (6) chain lengths approximately 13 inches long that shall be welded to a single steel ring at 60-degree intervals. Each length of chain shall contain up to 10 twisted style links that are square-cut to provide for maximum traction in forward and reverse modes.

There shall be one (1) driver's side and one (1) passenger side mounting bracket. The brackets shall attach utilizing certified grade 8 fasteners manufactured in accordance with SAE specifications.

A continuous duty solenoid shall be provided that, when activated, shall open and allow compressed air to flow to each chain unit. All hardware shall be grade 8 type and within SAE specifications.

**HELMET RESTRAINTS**

All NFPA required helmet restraints will be supplied and installed by the Fire Department prior to the truck being placed into service.

**MUD FLAPS**

Heavy-duty black rubber mud flaps with manufactures logo shall be provided behind the rear wheels. The mud flaps shall be bolted in place.

**WHEEL COVERS**

There shall be chrome plated lug nut covers and hub caps installed on the front and rear wheels. "Baby Moon" hub covers provided for the rear wheels.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**PUMP COMPARTMENT**

The complete apparatus pump compartment shall be constructed of a combination of structural tubing and formed sheet metal. The same materials used in the body shall be utilized in the construction of the pump compartment. The structure shall be welded utilizing the same A.W.S. Certified welding procedure as used on the structural body module. These processes shall ensure the quality of structural stability of the pump compartment module.

The pump compartment module shall be separated from the apparatus body with a gap. This gap is necessary to accommodate the flexing of the chassis frame rails that are encountered while the vehicle is in transit so that harmful torsional forces are not transmitted into the structural framework.

**VIBRA-TORQ™ PUMP MODULE MOUNTING SYSTEM**

The entire pump module assembly shall be mounted so that it “floats” above the chassis frame rails exclusively with Vibra-Torq™ torsion isolator assemblies to reduce the vibration and stress providing an extremely durable pump module mounting system.

The pump module substructure shall be mounted above the frame to allow independent flexing to occur between the body and the chassis. Each assembly shall be mounted to the chassis frame rails with steel, gusseted mounting brackets. Each bracket shall be powder coated for corrosion resistance. Each pump compartment mount bracket shall be mounted to the side chassis frame flange with two 5/8”-UNC Grade 5 HHCS.

Each assembly shall have a two-part rubber vibration isolator. The isolator shall be of a specific durometer to carry the necessary loads of the pump module, apparatus body, equipment, tank, water, and hose. The quantity of mounts utilized shall correspond directly to the anticipated weight being supported. Certain assemblies shall also incorporate a torsion spring. Helical coil springs shall be incorporated into specific mounts in tandem with the rubber isolators to minimize the stress absorbed by the body caused from chassis frame rail flexing.

There shall be no welding to the chassis frame rail sides, web or flanges, or drilling of holes in the top or bottom frame flanges between axles. All pump module to chassis connections shall be bolted so that in the event of an accident, the body shall be easily removable from the truck chassis for repair or replacement.

Because of the constant vibration and twisting action that occurs in chassis frame rails and suspension, the torsion mounting system is required to minimize the possibility of premature pump module structural failures. The Vibra-Torq™ mounting system shall have a lifetime warranty. **NO EXCEPTIONS**

**PUMP COMPARTMENT WORK LIGHT**

One (1) Weldon LED work light model #2631-0000-30 shall be installed in the pump compartment module to illuminate the piping and plumbing components.

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

The light shall be activated by a weather resistant toggle switch installed inside the pump compartment.

### **LEFT SIDE OPERATORS PANEL & PUMP PANEL**

The pump operator's panel shall be located on the left side of the apparatus pump compartment. The panel shall be split into an upper and lower section.

The material of the operator's panel shall match that of the overlays and right side panels specified.

The upper panel shall house gauges and controls and be hinged to allow easy access to components. The door shall have a stainless steel hinge, dual point chrome push button latches and a rubber seal provided to prevent excessive moisture from entering or leaving the pump house.

The lower panel on the left side shall be a removable panel attached with mechanical fasteners.

Valve controls shall be immediately adjacent to its respective gauge. The valve controls shall be properly labeled, and color coded for ease of use. All markings shall be permanent in nature.

### **OPEN DOOR WARNING**

If the hinged panel is not properly closed and the parking brake is released, it shall activate the hazard light in the cab to alert the crew.

### **VALVE CONTROL - T-HANDLE PULL ASSEMBLY**

Unless specified otherwise, the discharge valves shall be controlled from an Innovative Controls side mount valve control assembly. The ergonomically designed handle shall be chrome-plated with recessed areas for name plate and color code. A .75 inch (19.5 mm) diameter hardcoat anodized aluminum control rod and housing shall, together with a stainless spring steel locking mechanism, eliminate valve drift. Teflon impregnated bronze bushings in both ends of the rod housing shall minimize rod deflection, never need lubrication, and ensure consistent long-term operation. The control assembly shall include a decorative chrome-plated panel-mounting bezel. The valve operating mechanism will indicate the position of the valve at all times.

### **PUMP PANEL LIGHTS**

There shall be adequate illumination provided at the side pump panels with the installation of two (2) embossed aluminum diamond plate shielded light assemblies functioning as an intermediate step and installed on a stationary surface, one (1) on the left and one (1) on the right side pump compartment.

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

There shall be up to three (3) handhold cutouts provided in the top step surface measuring approximately 2.50 inches deep. There shall be one (1) full length aluminum non lit handrail integrated into each side assembly.

Each shield shall contain the maximum number of lights permitted in the space available for 9.00 inch (21cm) LED Tube lights model #RX-15T16-5050-21CM.

### **PUMP PANEL LIGHT ACTIVATION**

One (1) pump panel light at the operator's panel shall be illuminated at the time the pump is ready to pump and it is "OK TO PUMP". The Pump shift has been completed and the chassis automatic transmission is engaged.

The remaining lights shall be controlled by a switch located on the side operator's panel.

### **PUMP COMPARTMENT SERVICE ACCESS**

The front portion of the pump compartment structure (directly behind the chassis cab) shall not be overlaid. The outer edges of the pump compartment shall be overlaid with aluminum diamond plate for a pleasing appearance.

### **PUMP COMPARTMENT WIDTH**

The width of the pump compartment (front to back) shall be 48.00 inches (1.21 m).

### **RIGHT SIDE PUMP PANELS STYLE**

There shall be two (2) pump panels on the right side of the pump compartment, one (1) upper and one (1) lower. Each panel shall be accessible by a quick-release mechanical type latch, closing against a door seal. Both panels shall be easily removed for access to the pump for service.

### **RIGHT & LEFT SIDE BRUSHED STAINLESS STEEL PANELS & OVERLAYS**

The panels for the pump compartment on the left and right side shall be made from 14 gauge "Brushed Stainless Steel" capable of withstanding the conditions and effects of extreme weather and temperature changes.

The tubular structure shall be overlaid on each side of the pump compartment underneath the access panels and shall be made of "Brushed Stainless Steel".

### **RUNNING BOARDS**

The pump compartment running boards shall be made of a structural tubular framework. The tubular frame supports all loads by transmitting the loads through the pump compartment structure directly to the chassis frame rails.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

The running boards shall be independent of the apparatus body and shall be integrated to the pump compartment structure only, eliminating any pump compartment to body interference. This is essential in keeping a truly 'modular' configuration. Slip-resistant abrasive adhesive materials shall be applied to the top surface of the running board framework to provide a suitable stepping surface where applicable.

**EMBOSSSED ALUMINUM DIAMOND PLATE OVERLAYS**

The side running boards shall have a .188 inch (4.76 mm) embossed aluminum diamond plate overlays installed. The stepping areas shall be as large as possible, overlapping the perimeter of the running board structure.

**CLASS 1 TPG PLUS PRESSURE GOVERNOR**

There shall be a Class 1 TPG + total pressure governor and monitoring display kit provided and installed with the apparatus.

The pressure governor shall be connected to the engine control module mounted on the engine and operate as a pressure sensor regulating governor (PSG) utilizing the engine's J1939 data for optimal resolution and response when supported by the engine manufacturer. If J-1939 engine control is not supported, then analog remote throttle control shall be provided by the "TPG". The "TPG" shall function as a master pump discharge and intake gauge.

The TPG shall utilize control algorithms that minimize pressure spikes during low or erratic water supply situations. The "TPG" shall be backwards compatible to any engine that supplies J1939 RPM, temperature and oil pressure information providing the ability to maintain a consistent fleet fire-fighting capability and reduce operator cross training and confusion.

The "TPG" shall have the ability to use either a 300 PSI or a 600 PSI discharge pressure transducer and a 300 PSI intake pressure transducer. PSG system diagnostics shall be built in and accessible by technicians. Programmable presets for RPM and pressure settings shall be easily configurable. The straightforward menu structure shall allow the "TPG" configuration to match existing apparatus operation as closely as possible.

The following indications shall be provided:

- Engine RPM
- System Voltage
- Engine oil pressure, engine transmission temperature with audible alarm
- J1939 data bus for engine information, requiring no additional sensors
- Monitor and display pump and engine hours
- J1939 broadcast warnings for the alarm as a standard and allow the "user" to select warning values if SOP's dictate.

**INTAKE PRESSURE RELIEF VALVE**

A Task Force Tips model #A18XX pressure relief valve shall be provided. The valve shall

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

have an easy to read adjustment range from 90 to 300 PSI with easy to read 90, 125, 150, 200, 250, 300 psi settings and an "OFF" position. Pressure adjustment can be made utilizing a ¼" hex key, 9/16" socket or 14mm socket.

For corrosion resistance the cast aluminum valve shall be a hardcoat anodized with a powder coat interior and exterior finish. The valve shall meet (NFPA) 1901, Standard for Automotive Fire Apparatus, requirements for pump inlet relief valves. The unit shall be covered by a five year warranty. The valve shall be preset at 125 PSI (860 kPa) suction inlet pressure, unless otherwise shop noted. The valve shall be installed inside the pump compartment where it will be easily accessible for future adjustment. The excess water shall be plumbed to the atmosphere and shall dump on the opposite side of the pump operator.

For normal pumping operations, the relief valve shall not be capped and there shall be a placard stating "DO NOT CAP" installed.

### **TESTING PORTS**

Test port connections for pressure and vacuum shall be provided at the pump operator's panel. One (1) shall be connected to the intake side of the pump, and the other to the discharge manifold side of the pump.

Each port shall have 0.25 inch (6.35 mm) standard pipe thread connection and be manufactured of non-corrosive polished stainless steel or brass plugs.

### **TANK LEVEL GAUGE**

An Innovative Controls SL Plus Tank Monitor System model number 3030796-01, with a manufacture bezel, shall be installed. The system shall include an electronic display module, a pressure transducer-based sender unit, and the necessary wiring with water-tight plug terminations.

The display module shall show the volume of water in the tank using 16 super bright easy-to-see LEDs. Tank level indication shall be achieved by the use of 4 horizontal rows of LEDs. Full and near-full levels shall be indicated with the illumination of all 4 rows of LEDs, including the illumination of the top row of 4 green LEDs. Tank levels between ½ and ¾ full shall be indicated with the illumination of the bottom 3 rows of LEDs, including the illumination of the top row of 4 blue LEDs. Tank levels between ¼ and ½ full shall be indicated with the illumination of the bottom 2 rows of LED's including the illumination of the top row of 4 amber LEDs. Tank levels between ¼ full and near empty shall be indicated with the illumination of the bottom row of 4 red LEDs only. Tank levels between near empty and empty shall be indicated by flashing the bottom row of 4 red LEDs.

A wide-angle polycarbonate diffusion lens in front of the LEDs create a 180 degree viewing angle. The electronic display module shall be waterproof and shock resistant being encapsulated in a urethane-based potting compound. The potted display module shall be mounted to a chrome plated panel-mount bezel with a durable easy-to-read polycarbonate insert featuring blue graphics and a water icon.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

All programming functions shall be accessed and performed from the front of the display module. The programming includes manual or self-calibration and networking capabilities to connect remote slave displays. Low tank level warnings shall include flashing red LEDs starting below the ¼ level, down-chasing LEDs when the tank is almost empty.

The display module shall receive an input signal from a pressure transducer. This stainless steel sender unit shall be installed on the outside of the water tank near the bottom. All wiring, cables and connectors shall be waterproof without the need for sealing grease.

**AUXILIARY WATER LEVEL GAUGE**

**TANK LEVEL GAUGE**

There shall be one (1) Whelen model PSTANK2 water tank level light provided with a black bezel. The tank level gauge shall indicate fluid level in the water tank. The light colors shall be from top to bottom; Green, Blue, Amber, and Red. These lights shall automatically turn off to indicate the water level in the booster tank in 1/4 increments. The tank level gauge shall utilize a pressure transducer and driver to provide an accurate reading of the water tank level.

**TANK LEVEL GAUGE LOCATION**

One (1) tank level readout shall be located at the upper body area toward the front on the left side.

**ADDITIONAL WATER LEVEL GAUGE**

**TANK LEVEL GAUGE**

There shall be one (1) Whelen model PSTANK2 water tank level light provided with a black bezel. The tank level gauge shall indicate fluid level in the water tank. The light colors shall be from top to bottom; Green, Blue, Amber, and Red. These lights shall automatically turn off to indicate the water level in the booster tank in 1/4 increments. The tank level gauge shall utilize a pressure transducer and driver to provide an accurate reading of the water tank level.

**TANK LEVEL GAUGE LOCATION**

One (1) tank level readout shall be located upper body on the right side in the upper body area.

**EXTRA WATER LEVEL GAUGE**

**TANK LEVEL GAUGE**

There shall be one (1) Whelen model PSTANK2 water tank level light provided with a black bezel. The tank level gauge shall indicate fluid level in the water tank. The light colors shall be from top to bottom; Green, Blue, Amber, and Red. These lights shall automatically turn off to indicate the water level in the booster tank in 1/4 increments. The tank level gauge shall utilize a pressure transducer and driver to provide an accurate reading of the water tank level.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**TANK LEVEL GAUGE LOCATION**

One (1) tank level readout shall be located at the rear of the vehicle, to the left side.

**AIR HORN BUTTON**

There shall be an air horn activation red push button provided and installed on the pump operator's gauge panel. The air horn button shall be of weather resistance type and labeled "AIR HORN".

**PUMP COMPARTMENT TOP OVERLAY**

The top cap of the pump compartment shall be overlaid with materials of a non-slip .188 inch (4.76 mm) embossed aluminum diamond plate.

**DUNNAGE AREA**

A single wall .188 inch (4.76 mm) aluminum diamond plate dunnage area shall be provided above the pump house compartment for equipment mounting and storage space.

The dunnage area shall be as wide as possible from side to side, and as deep as allowed with the available space.

**LED PUMP HOUSE DUNNAGE LIGHTING**

One (1) LED tube light, model # RX-15T16-5050-21CM, with an aluminum mounting bezel shall be installed to illuminate the pump house dunnage area.

The light shall activate with the pump panel lights.

**PUMP HOUSE DUNNAGE LIGHTING LOCATION**

The pump house dunnage lighting specified above shall be located as high as possible on the rearward wall in the dunnage area.

**MIDSHIP PUMP**

The pump shall have the capacity of 1500 gallons per minute, measured in U.S. Gallons. The pump shall be a Hale Fire Pump, DSD single stage.

**PUMP ASSEMBLY**

The entire pump shall be assembled and tested at the pump manufacturer's factory. The pump shall be driven by a drive line from the truck transmission. The engine shall provide sufficient horsepower and RPM to enable pump to meet and exceed its rated performance.



## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

The entire pump shall be hydrostatically tested to a pressure of 600 PSI. The pump shall be fully tested at the pump manufacturer's factory to the performance spots as outlined by (NFPA) 1901, Standard for Automotive Fire Apparatus. Pump shall be free from objectionable pulsation and vibration.

The pump body and related parts shall be of fine grain alloy cast iron, with a minimum tensile strength of 30,000 PSI (2069 bar). All metal moving parts in contact with water shall be of high quality bronze or stainless steel. Pump utilizing castings made of lower tensile strength cast iron not acceptable.

Pump body shall be vertically split on a single plane for easy removal of entire impeller assembly including clearance rings.

Pump shaft to be rigidly supported by two bearings for minimum deflection. The bearings shall be heavy-duty, deep groove ball bearings in the gearbox, and they shall be splash lubricated. Shaft seal comes standard with face-type, self-adjusting corrosion- and wear-resistant mechanical seals.

The pump impeller shall be hard, fine grain bronze of the mixed flow design; accurately machines, hand-ground and individually balanced. The vanes of the impeller intake eye shall be hand ground and polished to a sharp edge and be of sufficient size and design to provide ample reserve capacity utilizing minimum horsepower.

Impeller clearance rings shall be bronze, easily renewable without replacing impeller or pump volute body.

The pump shaft shall be heat-treated, electric furnace, corrosion resistant stainless steel. Pump shaft must be sealed with double-lip oil seal to keep road dirt and water out of gearbox.

### **GEAR BOX**

Pump gearbox shall be of sufficient size to withstand up to 16,000 lbs. ft. of torque of the engine. The drive unit shall be designed of ample capacity for lubrication reserve and to maintain the proper operating temperature.

The gearbox drive shafts shall be of heat-treated chrome nickel steel and at least 2.75 inches in diameter, on both the input and output drive shafts. They shall withstand the full torque of the engine.

All gears, drive and pump, shall be of highest quality electric furnace chrome nickel steel. Bores shall be ground to size and teeth integrated and hardened, to give an extremely accurate gear for long life, smooth, quiet running, and higher load carrying capability. An accurately cut spur design shall be provided to eliminate all possible end thrust. **NO EXCEPTIONS**

The pump ratio shall be selected by the apparatus manufacturer to give maximum performance with the engine and transmission selected.

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

If the gearbox is equipped with a power shift, the shifting mechanism shall be a heat treated, hard anodized aluminum power cylinder, with stainless steel shaft. An in-cab control for rapid shift shall be provided that locks in road or pump.

For automatic transmissions, three green warning lights shall be provided to indicate to the operator(s) when the pump has completed the shift from Road to Pump position. Two green lights to be located in the truck driving compartment and one green light on pump operator's panel adjacent to the throttle control. For manual transmissions, one green warning light will be provided for the driving compartment. All lights to have appropriate identification/instruction plates.

### **PUMP WARRANTY**

Hale Products Inc. shall provide a limited manufacturer's pump warranty to be free from defects in material and workmanship, under normal use and service, for a period of two (2) years parts and labor and parts only for years three (3) through five (5), from the date placed into service.

### **MECHANICAL PUMP SEAL**

A mechanical seal shall be supplied on the inboard side of the pump. The mechanical seal must be two (2) inches in diameter and shall be spring-loaded, maintenance-free and self-adjusting. Mechanical seal construction shall be a carbon sealing ring, stainless steel coil spring, Viton rubber cup, and a tungsten carbide seat.

### **PUMP SHIFT**

The drive unit shall be provided with an air pump shift system. The control valve shall be a spring loaded guard lever that locks in "Road" or "Pump" mode.

To the left of the pump shift control, there shall be two indicator lights to show the position of the pump when the control is moved to "Pump" position. A green light shall be energized when the pump shift has been completed and shall be labeled "PUMP ENGAGED"; a second green light shall be labeled "OK TO PUMP" energized when both the pump shift has been completed and the chassis automatic transmission is engaged.

A third green indicator light shall be installed adjacent to the throttle on the pump operator's panel. This light shall be labeled "Throttle Ready".

In addition to this indicator light, an additional indication shall be provided to the pump operator at the panel when the pump is ready to pump. This additional indication shall be that one (1) of the operator's panel illumination lights will only activate when the "OK TO PUMP" indicator is lit.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**AIR PUMP SHIFT LOCATION**

The pump shift shall be mounted in the shifter module in the chassis. **No Exception**

**AIR PRIMER SYSTEM**

The priming system shall be a Trident Emergency Products compressed air powered high efficiency, multi-stage, venturi based Air Prime System.

All wetted metallic parts of the priming system are to be of brass and stainless steel construction. A single panel mounted control will activate the priming pump and open the priming valve to the pump.

The priming components shall be mounted above the highest priming point on the suction side of the pump to permit air removal and allow for drainage. The primer shall also automatically drain when the panel control actuator is not in operation. The inlet side of the primer shall include a brass 'wye' type strainer with removable stainless steel fine mesh strainer to prevent entry of debris into the primer body.

The system shall employ an 80 PSI (5.5 bar) pressure protection valve, located on the chassis auxiliary air tank.

The primer shall be covered by a five (5) year parts warranty.

**PRIMER CONTROL**

There shall be one (1) push button control to actuate the primer control valve at the operator's panel.

**DISCHARGE AND INLET MANIFOLDS**

A pump manifold inlet shall be provided on the pump as required for the layout.

The inlet(s) shall protrude up to 2.00 inches (50 mm) away from the side panels and maintain a low connection height.

A discharge manifold shall also be added to the pressure side of the pump to feed the specified discharge waterways.

**MAIN PUMP INLET-LEFT SIDE**

A 6.00 inch (150 mm) pump manifold inlet shall be provided on the left side of the pump. The inlet shall protrude up to 2.00 inches (50 mm) away from the side panel and maintain a low connection height.

The main pump inlet shall have National Standard Threads and includes a removable screen designed to provide cathodic protection for reducing deterioration in the pump.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**6" CHROME PLATED BRONZE CAP**

There shall be one (1) 6.00 inch (150 mm) long handled chrome plated cap installed on the Steamer Inlet.

The cap shall be National Standard Thread.

**MAIN PUMP INLET-RIGHT SIDE**

A 6.00 inch (150 mm) pump manifold inlet shall be provided on the right side of the pump. The inlet shall protrude up to 2.00 inches (50 mm) away from the side panel and maintain a low connection height.

The main pump inlet shall have National Standard Threads and includes a removable screen designed to provide cathodic protection for reducing deterioration in the pump.

**6" CHROME PLATED BRONZE CAP**

There shall be one (1) 6.00 inch (150 mm) long handled chrome plated cap installed on the Steamer Inlet.

The cap shall be National Standard Thread.

**MASTER DRAIN VALVE**

A Trident manifold type drain valve shall be installed in the pump compartment. All pump drains shall be connected to the master drain valve. The drain valve shall be controlled from the left side lower pump house sill. The control shall be a hand wheel knob marked "open" and "closed".

The drain shall be located such that it shall not interfere with pumping operations or function such as soft suction hoses, etc. nor shall it protrude past the outer edge of the apparatus, to prevent damage to the valve.

In some cases, it is necessary to locate the master drain in a secondary location to ensure proper draining. If no lower or vertical sill exists, the drain shall be located below the bottom outside edge of the hose body near the forward most corner on the driver's side hose body. The drain shall not protrude past the outer edge of the body, thus preventing damage to the valve.

**PUMP COOLING LINE**

There shall be a .38 inch (9.5 mm) line running from the pump to the water tank to assist in keeping the pump water from overheating. A valve shall be installed on the operator's panel.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**PUMP ANODES**

Two (2) pump anodes shall be installed in the pumping system, one (1) on the discharge side and one (1) on the suction side, to prevent damage from galvanic corrosion within the pump system. **No Exception**

**STAINLESS STEEL PLUMBING**

All auxiliary suction and discharge plumbing related fittings, and manifolds shall be fabricated with a minimum of 3.00 inch (77 mm), or greater as required by design, schedule 10 stainless steel pipe; brass or high pressure flexible piping with stainless steel couplings. **NO EXCEPTIONS** Galvanized components and/or iron pipe shall NOT be accepted to ensure long life of the plumbing system without corrosion or deterioration of the waterway system. Where waterway transitions are critical (elbows, tees, etc.), no threaded fittings shall be allowed to promote the smooth transition of water flow to minimize friction loss and turbulence. All piping components and valves shall be non-painted, unless otherwise specified. All piping welds shall be wire brushed and cleaned for inspection and appearance.

The high pressure flexible piping shall be black SBR synthetic rubber hose with 700 PSI working pressure and 1200 PSI burst pressure for flexible piping sizes 1.50 inches (38 mm) through 4.00 inches (100 mm). Sizes .75 inch (19 mm), 1.00 inch (25 mm) and 5.00 inches (125 mm) are rated at 250 PSI working pressure and 1000 PSI burst pressure. All sizes are rated at 30 in HG vacuum. Reinforcement consists of two plies of high tensile strength tire cord for all sizes and helix wire installed in sizes 1.00 inch (25 mm) through 5.00 inches (125 mm) for maximum performance in tight bend applications. The material has a temperature rating of -40 degrees Fahrenheit to +210 degrees Fahrenheit.

The stainless steel full flow couplings are precision machined from high tensile strength stainless steel. All female couplings are brass. Mechanical grooved and male .75 inch (19 mm) and 1.00 inch (25 mm) couplings are brass. A high tensile strength stainless steel ferrule with serrations on the I.D. is utilized to assure maximum holding power when fastening couplings to hose.

**PUMP HOUSE LINE PROTECTION**

All drain lines for the discharges, suctions, ABS discharge gauge lines and any other appropriate connections in the pump house area shall have a protective cover provided on the lines in the required areas of the lines to prevent the lines from rubbing on any other components in the pump house area.

All drain lines, ABS lines, high pressure discharge lines and electrical wiring in the pump house area shall be properly and neatly routed, wire tied, and rubber coated "P" clamped, to keep the items secured.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**DRAIN VALVES**

An Innovative Controls 3/4" quarter turn drain valve shall be included on each discharge, gated intake, and steamer valve (if applicable). A side stem, long stroke chrome plated lift handle shall be provided on the drain valve to facilitate use with a gloved hand. The drain valve shall have an ergonomically designed handle with a recessed verbiage tag area easily read by the operator before opening.

The drain valve shall be connected to the valve with a flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus.

**ELKHART FOAM EDUCTOR**

There shall be a brass by-pass Eductor installed on the apparatus with a check valve to prevent the back flow of foam. It shall operate with 200 psi inlet pressure and have a metering valve mounted on the pump panel with settings of 0, 1/2%, 1%, 3% and 6%. The Eductor shall be an Elkhart Brass model #240-125P, rated at 125 GPM.

**FOAM SYSTEM TESTING**

The apparatus foam system shall be tested, and the Water Flow meter shall be certified by the manufacturer prior to delivery.

**FOAM SYSTEM SUPPLY**

The Eductor shall draw foam from the foam tank.

**FOAM TANK**

A 30 gallon foam tank with square hinged lid, equipped with a hold down device shall be installed and plumbed with non-corrosive piping to the foam system. The fill tower shall be approximately 10.00 inch by 10.00 inch.

A label shall be affixed to the foam tank fill indicating: "WARNING" Class A (or B) foam tank fill, do not mix brands or types of foam.

Each foam tank shall be integral with the booster water tank provided.

**FOAM TANK DRAIN**

There shall be a 1.00 inch (25.4 mm) quarter turn drain valve installed to drain the foam tank. The valve shall be installed in the pump house with a drain line extended to the side running board.

The drain line shall be labeled "FOAM DRAIN".

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**SHUTOFF VALVE**

There shall be a 1/4 turn valve installed at the foam tank to shut off the flow from the supply line.

**FOAM LEVEL GAUGE**

An Innovative Controls SL Plus Tank Monitor System model number 3030796-02, with a manufacture bezel, shall be installed. The system shall include an electronic display module, a pressure transducer-based sender unit, and the necessary wiring with water-tight plug terminations.

The display module shall show the volume of foam in the tank using 16 super bright easy-to-see LEDs. Tank level indication shall be achieved by the use of 4 horizontal rows of LEDs. Full and near-full levels shall be indicated with the illumination of all 4 rows of LEDs, including the illumination of the top row of 4 green LEDs. Tank levels between 1/2 and 3/4 full shall be indicated with the illumination of the bottom 3 rows of LEDs, including the illumination of the top row of 4 blue LEDs. Tank levels between 1/4 and 1/2 full shall be indicated with the illumination of the bottom 2 rows of LED's including the illumination of the top row of 4 amber LEDs. Tank levels between 1/4 full and near empty shall be indicated with the illumination of the bottom row of 4 red LEDs only. Tank levels between near empty and empty shall be indicated by flashing the bottom row of 4 red LEDs.

A wide-angle polycarbonate diffusion lens in front of the LEDs create a 180 degree viewing angle. The electronic display module shall be waterproof and shock resistant being encapsulated in a urethane-based potting compound. The potted display module shall be mounted to a chrome plated panel-mount bezel with a durable easy-to-read polycarbonate insert featuring blue graphics and a water icon.

All programming functions shall be accessed and performed from the front of the display module. The programming includes manual or self-calibration and networking capabilities to connect remote slave displays. Low tank level warnings shall include flashing red LEDs starting below the 1/4 level, down-chasing LEDs when the tank is almost empty.

The display module shall receive an input signal from a pressure transducer. This stainless steel sender unit shall be installed on the outside of the foam tank near the bottom. All wiring, cables and connectors shall be waterproof without the need for sealing grease.

**HALE EZ-FILL**

The apparatus shall be equipped with a Hale Products, Inc. EZ-Fill™ fixed-mount foam tank refill pump system. The unit shall include a 12-volt electric motor that drives a 5-gpm foam concentrate pump used to refill the foam apparatus reservoir(s), a panel mounted smart-switch operator control and a wand suction hose connection.

The EZ-Fill system shall incorporate push-button smart-switch technology and be designed so that with a momentary press of the EZ-Fill control panel "Fill" or "Flush" buttons, the unit

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

will automatically cycle respectively filling the foam concentrate reservoir or running itself through a flush cycle.

The system shall be configured to handle refilling a single foam concentrate tank apparatus reservoir system.

The EZ Fill shall be equipped with a clear wand suction hose having a cam-lock fitting designed for 5-gallon pail drafting operations. The suction hose shall be equipped with integral strainer to prevent intake of unwanted debris. The cam-lock foam suction inlet connection shall be equipped with a cap for stowage. The wand shall attach to a cam-lock fitting receptacle on the pump operators panel during the refill process. Once the clear suction wand is connected via the cam-lock fitting, and the wand end is placed in a 5-gallon bucket of foam concentrate, with one push of the "Fill" button the unit shall self-prime and fill the apparatus foam concentrate reservoir. The EZ-Fill system shall then automatically shut itself off either after a 60-second run duration or when the foam concentrate reservoir is full. The EZ-Fill system shall contain a foam pump "Flush" feature via a three-way integral valve mounted inside the pump-house.

The EZ-Fill pump panel smart-switch control shall be designed to override automatic re-fill operation by allowing the pump operator to hold down the "Fill" or "Flush" buttons, which allows for continuous foam pump refill or flush action. The foam concentrate reservoir(s) shall be equipped with a "high level tank switch" to prevent foam reservoir overflow during automatic operation. The EZ-Fill shall include a factory supplied wiring harness configured for power and ground leads and an installation and operation manual.

A label shall be affixed to the foam tank fill indicating: "WARNING" Class A (or B) foam tank fill, do not mix brands or types of foam.

**LEFT SIDE INLET**

There shall be one (1) gated suction inlet with .75 inch (19mm) bleeder installed on the left side of the apparatus with the following specified components.

**INTAKE VALVE**

A 2.50 inch (65 mm) Akron Brass 8000 series swing-out valve with stainless steel ball.

**INTAKE VALVE CONTROL**

The intake control valve shall be a 'swing out type' direct operation manual lever actuator at the valve.

**INTAKE PLUMBING**

The plumbing shall consist of 2.50 inch (65 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.



Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>SUCTION/INTAKE TERMINATION</u></b></p> <p>The termination shall include the following components:</p> <p>One (1) 2.50 inch (65 mm) NST swivel female straight adapter with screen</p> <p>One (1) 2.50 inch (65 mm) self-venting plug, secured by a chain</p> <p><b><u>INLET LOCATION</u></b></p> <p>The inlet shall be located on the pump panel in the forward position.</p> <p><b><u>AUXILIARY LEFT SIDE INLET</u></b></p> <p>There shall be one (1) auxiliary gated suction inlet with .75 inch (19mm) bleeder installed on the left side of the apparatus with the following specified components.</p> <p><b><u>INTAKE VALVE</u></b></p> <p>A 2.50 inch (65 mm) Akron Brass 8000 series swing-out valve with stainless steel ball.</p> <p><b><u>INTAKE VALVE CONTROL</u></b></p> <p>The intake control valve shall be a 'swing out type' direct operation manual lever actuator at the valve.</p> <p><b><u>INTAKE PLUMBING</u></b></p> <p>The plumbing shall consist of 2.50 inch (65 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.</p> <p><b><u>SUCTION/INTAKE TERMINATION</u></b></p> <p>The termination shall include the following components:</p> <p>One (1) 2.50 inch (65 mm) NST swivel female straight adapter with screen</p> <p>One (1) 2.50 inch (65 mm) self-venting plug, secured by a chain</p> <p><b><u>INLET LOCATION</u></b></p> <p>The inlet shall be located on the pump panel in the rearward position.</p> <p><b><u>RIGHT SIDE INLET</u></b></p> <p>There shall be one (1) gated suction inlet with .75 inch (19mm) bleeder installed on the right side of the apparatus with the following specified components.</p>		

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>INTAKE VALVE</u></b></p> <p>A 2.50 inch (65 mm) Akron Brass 8000 series swing-out valve with stainless steel ball.</p> <p><b><u>INTAKE VALVE CONTROL</u></b></p> <p>The intake control valve shall be a 'swing out type' direct operation manual lever actuator at the valve.</p> <p><b><u>INTAKE PLUMBING</u></b></p> <p>The plumbing shall consist of 2.50 inch (65 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.</p> <p><b><u>SUCTION/INTAKE TERMINATION</u></b></p> <p>The termination shall include the following components:</p> <p>One (1) 2.50 inch (65 mm) NST swivel female straight adapter with screen</p> <p>One (1) 2.50 inch (65 mm) self-venting plug, secured by a chain</p> <p><b><u>INLET LOCATION</u></b></p> <p>The inlet shall be located on the pump panel in the forward position.</p> <p><b><u>LEFT SIDE DISCHARGE</u></b></p> <p>There shall be two (2) gated discharges installed on the left side of the apparatus with the following specified components.</p> <p><b><u>DISCHARGE VALVE</u></b></p> <p>A 2.50 inch (65 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.</p> <p><b><u>DISCHARGE VALVE CONTROL</u></b></p> <p>The control valve shall be a 'swing out type' direct operation manual lever actuator at the valve.</p> <p><b><u>DISCHARGE PLUMBING</u></b></p> <p>The plumbing shall consist of 2.50 inch (65 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**DISCHARGE TERMINATION**

The discharge termination shall include the following components:

- One (1) 2.50 inch (65 mm) Male NST adapter
- One (1) 2.50 inch (65 mm) NST female swivel by male with 45 degree polished elbow
- One (1) 2.50 inch (65 mm) female self-venting cap, secured by a chain

**RIGHT SIDE DISCHARGE**

There shall be one (1) gated discharge installed on the right side of the apparatus with the following specified components.

**DISCHARGE VALVE**

A 2.50 inch (65 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.

**DISCHARGE VALVE CONTROL**

The discharge shall be controlled from the pump operator's panel location.

**DISCHARGE PLUMBING**

The plumbing shall consist of 2.50 inch (65 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.

**DISCHARGE TERMINATION**

The discharge termination shall include the following components:

- One (1) 2.50 inch (65 mm) Male NST adapter
- One (1) 2.50 inch (65 mm) NST female swivel by male with 45 degree polished elbow
- One (1) 2.50 inch (65 mm) female self-venting cap, secured by a chain

**RIGHT SIDE MASTER DISCHARGE**

There shall be one (1) master discharge installed on the right side of the apparatus provided with the following specified components.

**DISCHARGE VALVE**

A 3.00 inch (77 mm) Akron Brass 8000 series slo-cloz swing-out valve with a stainless steel ball.

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>DISCHARGE VALVE CONTROL</u></b></p> <p>The discharge shall be controlled from the pump operator's panel location.</p> <p><b><u>DISCHARGE PLUMBING</u></b></p> <p>The plumbing shall consist of 3.00 inch (77 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.</p> <p><b><u>DISCHARGE TERMINATION</u></b></p> <p>The discharge termination shall include the following components:</p> <p>One (1) 3.00 inch (77 mm) NST adapter</p> <p>One (1) 3.00 inch (77 mm) NST female swivel by 5.00 inch (125 mm) Storz with 30 degree elbow</p> <p>One (1) 5.00 inch (125 mm) Storz cap, secured by a chain</p> <p><b><u>LEFT REAR DISCHARGE</u></b></p> <p>There shall be one (1) gated discharge installed on the left rear of the apparatus with the following specified components.</p> <p><b><u>DISCHARGE VALVE</u></b></p> <p>A 2.50 inch (65 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.</p> <p><b><u>DISCHARGE VALVE CONTROL</u></b></p> <p>The discharge shall be controlled from the pump operator's panel location.</p> <p><b><u>DISCHARGE PLUMBING</u></b></p> <p>The plumbing shall consist of 2.50 inch (65 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.</p> <p><b><u>DISCHARGE TERMINATION</u></b></p> <p>The discharge termination shall include the following components:</p> <p>One (1) 2.50 inch (65 mm) Male NST adapter</p> <p>One (1) 2.50 inch (65 mm) NST female swivel by male with 45 degree polished elbow</p> <p>One (1) 2.50 inch (65 mm) female self-venting cap, secured by a chain</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**CROSSLAY AREA**

The crosslay hose beds shall be located in the upper portion of the pump compartment.

The crosslay area shall span the entire width of the apparatus pump module. Removable flooring shall be provided in the hose bed area for drainage.

**SINGLE STACK CROSSLAYS**

The crosslay area shall be constructed with a minimum of 25.00-inch (635mm) approximate depth for laying a single stack of each hose size as specified below.

Chiksan swivels shall be installed just below the floor of each crosslay bed just high enough for hose couplings to be accessed and tightened on to chiksans. Chiksan swivels shall swing from left to right to allow attached hose to be deployed from either side.

**FIXED CROSSLAY DIVIDERS WITH NO HAND HOLD CUTOUTS**

Each crosslay divider acting as a hose bed separator shall be fabricated of .188-inch smooth aluminum and shall have a dual-action sanded finish. Each divider shall NOT have hand hold cutouts provided.

**1 3/4" CROSSLAY**

A crosslay with the following specified components shall be provided for up to 200 feet (60 m) of 1.75 inch (44.4 mm) hose.

There shall be a total of two (2) provided.

**DISCHARGE VALVE**

A 2.00 inch (50 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.

**DISCHARGE VALVE CONTROL**

The discharge shall be controlled from the pump operator's panel location.

**DISCHARGE PLUMBING**

The plumbing shall consist of 2.00 inch (50 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.

**DISCHARGE TERMINATION**

The discharge termination shall include the following components:

One (1) 2.00 inch (50 mm) NPT x 1.50 inch (38 mm) NST brass chiksan swivel

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**DISCHARGE CAPABILITY**

One (1) discharge(s) shall be foam capable. Crosslay #2 will be foam capable.

**CROSSLAY TRIM**

Brushed stainless steel trim shall be installed at the openings on the bottom and on each side of the crosslay hose bed area. The trim shall reduce the chaffing of the hose jacket on the edges of the bay area.

**CROSSLAY COVER**

The crosslay hose bed area shall have a hinged .188 inch (4.76 mm) embossed aluminum diamond plate cover installed. The cover shall be installed to provide a solid surface over all bays. The cover shall have a hand hold slot on each end. The cover shall be attached with a full length piano style hinge.

**CROSSLAY END COVERS**

The crosslay hose bed area shall have a vinyl cover installed at each end of the crosslay area. The covers shall be held in place by an extrusion at the top of crosslay opening and shall include shock cord passing thru brass grommets. Hooks shall be installed at the lower corners to secure the cover to the apparatus.

**CROSSLAY SIDE COVERS COLOR**

The crosslay hose bed side covers shall be red in color.

**CROSSLAY HOSE BED LIGHT**

There shall be one (1) 18.00 inch OnScene "Access" LED strip light in a bezel provided and installed on the front face of the body to illuminate the crosslay hose bed.

**CROSSLAY LIGHT ACTIVATION**

The crosslay light shall be activated when the park brake is set.

**2 1/2" PRE-CONNECT**

One (1) hose bed pre-connect with the following specified components shall be provided for 2.50 inch (63.5 mm) hose on the right side of the hose bed.

**DISCHARGE VALVE**

A 2.50 inch (65 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**DISCHARGE VALVE CONTROL**

The discharge shall be controlled from the pump operator's panel location.

**DISCHARGE PLUMBING**

The plumbing shall consist of 2.50 inch (65 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access.

**DISCHARGE TERMINATION**

The discharge termination shall include the following components:

One (1) 2.50 inch (65 mm) NPT x 2.50 inch (65 mm) MNST chrome plated brass fitting

**PRE-CONNECT LOCATION**

The discharge shall terminate to the right side lower corner of the hose bed header approximately 8.00 inches, on center, above the hose bed floor.

**DECK GUN MONITOR WATERWAY**

There shall be one (1) deck gun monitor waterway installed on the apparatus with the following components.

**DISCHARGE VALVE**

A 3.00 inch (77 mm) Akron Brass 8000 series slo-cloz swing-out valve with a stainless steel ball.

**DISCHARGE VALVE CONTROL**

The discharge shall be controlled from the pump operator's panel location.

**DELUGE PLUMBING**

The deluge waterway shall consist of 3.00 inch (77 mm) piping and shall be drained with an auto-drain located at the lowest point of the waterway plumbing if required.

**DELUGE PIPE LOCATION**

The deluge pipe shall be located up through the pump compartment, at the center location.

**TELESCOPING MONITOR PIPE**

One (1) Task Force Tips model #XG18VL-XL manually telescoping waterway shall be provided with the apparatus.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

The waterway shall be capable of being lowered to deck level (or into a monitor well) for storage and transportation and shall be capable of being raised to an extended height of 18.00 inch (457.2 mm) by lifting a quick release latch located at the base of the extension tube. This latching device shall be capable of locking the waterway in either the raised or lowered position while maintaining the ability to horizontally rotate the monitor device 360 degrees.

If the extend-a-gun is not properly stowed and the parking brake is released, it shall activate the hazard light in the cab to alert the crew.

The aluminum riser shall have a 3.00 inch (77 mm) waterway; hardcoat anodized finish and be provided with a 3.00 inch (77 mm) Victaulic inlet and a Task Force Tips Crossfire coupling outlet.

**FRONT BUMPER DISCHARGE OUTLET**

One (1) front bumper discharge outlet shall be provided and installed in the location specified.

**DISCHARGE VALVE**

A 2.50 inch (65 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.

**DISCHARGE VALVE CONTROL**

The discharge shall be controlled from the pump operator's panel location.

**DISCHARGE PLUMBING**

The plumbing shall consist of 2.50 inch (65 mm) piping and shall incorporate a manual drain control installed below the pump area for ease of access. Auto-drain(s) shall be installed in the discharge piping at lowest point of the plumbed system.

NO Painted Front Bumper Discharge Plumbing

**DISCHARGE TERMINATION**

The discharge termination shall include the following components:

One (1) 2.50 inch (65 mm) NPT x 2.50 inch (65 mm) NST SST chiksan swivel

**FRONT BUMPER DISCHARGE LOCATION**

The front bumper discharge shall be mounted on top of the gravel shield of the front bumper extension. The discharge shall be placed outboard of the frame rail extensions on the right side.



**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**BOOSTER REEL**

There shall be an electric rewind booster reel with automatic brake installed on the apparatus. The booster reel shall have a capacity to handle 1.00-inch diameter (25.4 mm) booster hose.

There shall be a manual rewind device provided. A manual crank shall be mounted adjacent to booster reel.

**BOOSTER HOSE**

The reel shall come equipped with 200 feet (60 m) of 800 psi (55 BAR) booster hose.

The hose shall be provided in two (2) 100 foot (30 m) lengths with hardcoat aluminum couplings.

**REEL FINISH**

The hose reel specified shall be steel and painted the standard silver utilized by Hannay.

**HOSE REEL VALVE**

The reel shall be plumbed to the pump with a 1.00 inch (25.40 mm) quarter turn Akron brass 8000 series ball valve and 1.00 inch (25.40 mm) high pressure hose and couplings.

The valve shall be controlled from the operator's panel.

**REWIND ACTIVATION**

An electric rewind switch shall be located adjacent to the booster reel. The switch shall have a weather resistant rubber cover and a label indicating its function.

The switch shall be labeled "HOSE REEL".

**HOSE REEL LOCATION**

The hose reel shall be mounted in a dunnage area specified above the pump on the left side.

**HOSE REEL ROLLERS**

There will be one (1) bell roller assembly installed on the left side upper pump house to allow hose payout to the left side of the apparatus.

**HOSE REEL BLOW OUT**

There shall be an air "blowout" system provided and installed on the apparatus. The air blow out system shall be connected to the chassis air brake system. A check valve shall be installed between the chassis system and the reel blow out system. A ¼ turn manual control valve shall

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

be installed on the pump operator's panel for the air blow out system.

The valve shall be labeled "REEL BLOW OUT".

**BOOSTER REEL GAUGE**

There shall be no pressure gauge supplied for the Booster Reel.

**DISCHARGE GAUGES**

An (Innovative Controls) TC Series nominal 2.50 inch gauge shall be supplied for reading the pressure of each discharge greater than 1.50 inches (38 mm) in diameter, unless otherwise specified.

A KEM-X socket saver diaphragm, located in the stem, eliminates freeze-up by preventing water from entering and/or clogging the gauge internals while containing a low temperature instrument oil that fills and protects the socket and the bourdon tube.

The molded glass-filled Nylon 66 case will not corrode and includes a scratch-resistant molded polycarbonate lens with O-ring seal. The gauge shall withstand pressures up to 100psi over gauge range with operation from -40° F to +160°F.

**GAUGE SCALE**

Each gauge shall be marked for reading a pressure range of 0-400 PSI.

**GAUGE FACE COLOR**

Each gauge shall have black markings on a white face.

**BEZELS FOR 2.5" DISCHARGE GAUGES**

Highly-polished stainless steel Innovative Control bezels shall be provided around each of the 2.50 inch (65 mm) discharge pressure gauges to prevent corrosion and protect lenses and gauge cases. The gauges shall be installed into decorative chrome-plated mounting bezels that incorporate valve identifying verbiage and/or color labels.

**APPARATUS PLUMBING LABELING**

Innovative Controls verbiage tag bezels shall be installed. The bezel assemblies will be used to identify apparatus components. These tags shall be designed and manufactured to withstand the specified apparatus service environment and shall be backed by a warranty equal to that of the exterior paint and finish. The verbiage tag bezel assemblies shall include a chrome-plated panel-mount bezel with durable easy-to-read UV resistant polycarbonate inserts featuring the specified verbiage and color coding. These UV resistant polycarbonate verbiage and color inserts shall be subsurface screen printed to eliminate the possibility of wear and protect the inks from fading. Both the insert labels and bezel shall be backed with 3M permanent adhesive, which meets UL969 and NFPA standards.

# Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

## **TANK TO PUMP LINES**

The connections between the tank and the pump shall be capable of the flow recommendations as set forth in (NFPA) 1901, Standard for Automotive Fire Apparatus, latest revision and shall be tested to those standards when the pump is being certified.

Two (2) non-collapsible flexible hoses and valves shall be incorporated into the tank to pump plumbing to allow movement in the line as the chassis flexes to avoid damage during normal road operation. Four (4) inch stainless steel schedule 10 piping shall be used to complete the connections from the tank to pump valves to separate ports in the water tank. **No Exception**

## **PRIMARY TANK TO PUMP**

### **TANK TO PUMP CHECK VALVE**

There shall be a tank to pump check valve, conforming to NFPA standard requirements to prevent water from back flowing at an excessive rate if the pump is being supplied from a pressurized source. The check valve shall be mounted as an integral part of the pump suction extension. A hole up to .25 inch (6.00 mm) is allowable in the check valve to release steam or other pressure buildup so that the void between the valve and check valve may drain of water that could be subject to freezing. **No Exception**

### **TANK TO PUMP VALVE**

A 3.00 inch (77 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.

### **VALVE CONTROL**

The valve shall be controlled from the pump operator's panel location.

## **AUXILIARY TANK TO PUMP**

### **TANK TO PUMP CHECK VALVE**

There shall be a tank to pump check valve, conforming to NFPA standard requirements to prevent water from back flowing at an excessive rate if the pump is being supplied from a pressurized source. The check valve shall be mounted as an integral part of the pump suction extension. A hole up to .25 inch (6.00 mm) is allowable in the check valve to release steam or other pressure buildup so that the void between the valve and check valve may drain of water that could be subject to freezing. **No Exception**

### **TANK TO PUMP VALVE**

A 3.00 inch (77 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball shall be 'air actuated' by a toggle switch on the operators panel.

**Due to the terrain of Fannin County there shall be Two (2) tank to pump lines. No Exception**

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>TANK FILL LINE</u></b></p> <p>One (1) 2.00 inch (50.80 mm) tank fill/recirculating line shall be installed from the pump directly to the booster tank.</p> <p><b><u>TANK FILL VALVE</u></b></p> <p>A 2.00 inch (50 mm) Akron Brass 8000 series swing-out valve with a stainless steel ball.</p> <p><b><u>VALVE CONTROL</u></b></p> <p>The valve shall be controlled from the pump operator's panel location.</p> <p><b><u>DIRECT TANK FILL</u></b></p> <p>There shall be an external direct tank fill port installed on the rear of the apparatus.</p> <p>A total quantity of one (1) shall be provided with the following specified components:</p> <p><b><u>TANK FILL VALVE</u></b></p> <p>A Fireman's Friend 2.50 inch (65 mm) valve(s) manufactured utilizing heavy gauge stainless steel casting (316), EPDM rubber seals, high-grade stainless steel springs and shafts, as well as stainless steel prevailing torque fasteners shall be installed.</p> <p>A bleeder valve shall be included for the tank fill valve.</p> <p><b><u>DIRECT TANK FILL PLUMBING</u></b></p> <p>The plumbing shall consist of 2.50-inch (65 mm) piping.</p> <p><b><u>SUCTION INLET/INTAKE PLUMBING NO FINISH</u></b></p> <p>Any piping in the rear or side compartment shall remain exposed and be left raw finish and exposed within the side compartment.</p> <p><b><u>DIRECT TANK FILL TERMINATION</u></b></p> <p>The direct tank fill termination shall include the following components:</p> <p>One (1) 2.50 inch (65 mm) FNPT x 2.50 inch (65 mm) FNST swivel straight adapter with screen</p> <p>One (1) 2.50 inch (65 mm) MNST x 2.50 inch (65 mm) FNST swivel elbow</p> <p>One (1) 2.50 inch male self-venting plug, secured by a chain.</p>		

# Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes    No**

## **DIRECT TANK FILL LOCATION**

One (1) direct tank fill shall be located on the right rear of the apparatus.

## **TRI-MAX™ Space Frame Body - ALUMINUM**

The apparatus body shall be a Tri-Max™ **Space Frame** design, which serves as an incredibly durable, structural body framework. This framework acts as a series of beams and columns that support and protect the body and its contents. The space frame design provides maximum torsional resistance and load capabilities. The entire space frame structure shall be welded together utilizing an A.W.S. Certified welding procedure. **NO EXCEPTIONS**

The space frame design shall also be required because it provides energy absorbing impact zones in the structure, thus providing increased safety to the rest of the apparatus and personnel on board. Documented proof of this extra safety shall be required upon request.

The Tri-Max™ body structure shall consist entirely of closed section members, except where the body is mounted to the chassis. Closed section members (such as square, rectangular, triangular, or round tubes) are required because they provide maximum strength and torsion rigidity. This solid tubular structural style of design ultimately adds longevity to the body structure by eliminating flex and twists in material, creating less stress and fatigue. Body designs that use independent sub-frames will not be acceptable. **NO EXCEPTIONS**

## **BODY STRUCTURE MEMBERS**

The space frame body shall have triangular shaped structural members in certain areas of the body. This shape is required to prevent loss of useable compartment space. Other body structure members shall be square or rectangular. Each structural member will have a nominal outside dimension of 2.50 inches (63.50 mm) in at least one direction. The body shall be designed for maximum strength to weight ratio, therefore the gauge of sheet metal and structural members varies from .125 inches (3.18 mm) to .250 inches (6.35 mm) throughout, dependent on the design requirement. **No Exception**

## **BODY MATERIAL TYPE**

All body structural members shall be Aluminum 6061-T6 alloy material. All .125 inch (3.18 mm) sheet material shall be Aluminum Alloy 5052-H32, and .250 inch (6.35 mm) sheet materials shall be Aluminum Alloy 3003. These alloys are required because it provides optimum all-around performance for strength, manufacturing properties, and corrosion resistance. **No Exception**

## **ECK® ANTI-CORROSION PROCESS**

Absolutely no dissimilar metals shall be used in the body and its supporting substructure without being separated by Eck®, which prevents corrosion by providing a barrier between dissimilar metals, sealing out moisture and absorbing energy created by a dissimilar metal reaction.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**FRONT BODY COMPARTMENT WALLS**

The front compartment walls of both forward most compartments shall be sheet finished. No overlay material shall be visible from the interior of the compartments.

**REAR BODY COMPARTMENT WALLS**

The rear compartment walls of both rearward most compartments shall be sheet finished. No overlay material shall be visible from the interior of the compartments. Access panels from the rear walls shall be strategically placed to ensure access to the rear taillight clusters for any servicing that may be completed.

**COMPARTMENT TOP**

The top of the compartments shall be an integral portion of the body. No overlay material shall be visible from the interior of the compartments.

**COMPARTMENT FLOORS**

The body compartments shall be enclosed with aluminum sheet metal as specified above. The compartment floors shall have a 1.00 inch (25.40 mm) lip downward at the door opening side of the compartment. This lip shall integrate with a structural member on the bottom edge and form a “sweep-out” compartment. This design shall also allow for a structural flush fitting door frame and a complete door/weather seal.

**COMPARTMENT LOAD CAPACITY**

Each compartment shall have a minimum of one additional structural compartment floor support centered on the underside of the compartment floor. This additional member shall be integral with the rest of the body structure. Each compartment must be designed, and 3<sup>rd</sup> party analyzed to carry a working load of:

- Full depth side compartment: 1,000 lbs (453.59 kg) per compartment
- Half depth side compartment: 750 lbs (340.19 kg) per compartment
- Rear center compartment: 1,500 lbs (680.39 kg)

**NO EXCEPTIONS**

**NOTE: These values are for design purposes only for individual compartment construction and are not meant to be used as an actual overall weight rating for equipment load per compartment for the specified apparatus. The apparatus shall be engineered such that the completed unit, when loaded to its estimated in-service weight, shall comply with the gross axle weight ratings {GAWR}, the overall gross vehicle weight rating {GVWR}, and the chassis manufacturer's load balance guidelines per NFPA.**

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

### EXTERIOR HOSE BED WALLS

The exterior hose bed walls shall be an integral portion of the body. The wall shall give a smooth exterior look and finish with no vertical supports tubing visible from the exterior of the truck.

### FASTENERS

All bolts and nuts used in the finish construction of the apparatus shall be coated stainless steel which helps prevent dissimilar metal electrolytic reaction and corrosion. Any bolt extending into a compartment or into the hose bed area shall have an acorn nut attached or be protected in such manner where sharp edges are avoided.

### FINITE ELEMENT ANALYSIS

The proposed body design must have completed a review and analysis by a legitimate 3<sup>rd</sup> party engineering firm. At a minimum, the 3<sup>rd</sup> party must have conducted a computer model finite element analysis of the proposed design. The analysis is to include real world working load scenarios. Analysis to cover both static and dynamic situations must be completed. The purpose of the finite element analysis is to ensure proper design of the apparatus body, and that it is capable of carrying the typical fire apparatus loads and those specified by NFPA for equipment. The analysis process must conclude that the body structure is properly designed and manufactured to provide longevity under normal conditions. The 3<sup>rd</sup> party must also validate the manufacturing processes are consistent with the design and analysis performed. Proof of having completed this testing must be submitted with the bid. **NO EXCEPTIONS**

### PAINT SPECIFICATIONS

All bright metal fittings, if unavailable in stainless steel, shall be heavily chrome plated.

Critical body and sub-frame area which cannot be primed after assembly shall be pre-painted.

All welded metal surfaces shall be ground to a smooth surface prior to a degreasing and high pressure, high temperature phosphatizing process. The entire surface shall be sprayed with a non-chromate sealing compound to prevent formulation of stains or flash rust on previously phosphatized parts.

The paint applied to the apparatus shall be Akzo Nobel, Sikkens brand, LVBT650 basecoat, applied throughout a multi-step process including at least two coats of each color and clear coat finish.

The coating shall be an infra-red, baked air dried. The coatings shall provide full gloss finished suitable for application by high-pressure airless or conventional low pressure air atomizing spray.

The coatings shall not contain lead, cadmium or arsenic. The polyisocyanate component shall

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

consist of only aliphatic isocyanates, with no portion being aromatic isocyanates in character. The solvents used in all components and products shall not contain ethylene glycol monoethyl ethers or their acetates (commercially recognized as cello solves), nor shall they contain any chlorinated hydrocarbons. The products shall have no adverse effects on the health or nor present any unusual hazard to personnel when used according to manufacturer's recommendations for handling and proper protective safety equipment, and for its intended use.

The coating system, as supplied and recommended for application, shall meet all applicable federal, state and local laws and regulations now in force or at any time during the courses of the bid.

The manufacturer shall supply (upon request) for each product and component of the system, a properly complete OSHA "Safety Data Sheet".

The following documents of the issue in effect on the date of the invitation to quote form a part of this document to the extent specified herein:

Federal Standards: Number 141A and 141B paint, varnish, lacquer and related material: methods of inspection, sampling, and testing.

Military Standard: MIL-C 83486B Coating, Urethane, Aliphatic Isocyanates, for Aerospace applications.

Industry Methods and Standards: ASTM Method of Analysis (American Society for testing and Materials). BMS 10-72A (Boeing Material Specifications).

The entire exterior body structure (excluding roll-up doors) shall receive the primer coats and the finish coats. The apparatus body will be painted in a down draft type paint booth to reduce dust, dirt or impurities in the finish paint. The painted surfaces shall have a finish with no runs, sags, craters, pinholes or other defects. The coating will meet the following test performance properties as a minimum standard.

### **BODY PAINT COLOR**

The apparatus body shall be painted to match FLNA 3001 Red

### **SUPERLINER COMPARTMENT FINISH**

The compartment interiors shall be coated with Superliner.

### **COMPARTMENT FINISH COLOR**

The Superliner Color shall be Medium Gray.



Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>UNDERCOATING</u></b></p> <p>The underside of the apparatus body shall be cleaned and prepared for the application of a sprayed on automotive type undercoating for added corrosion resistance.</p> <p>The undercoating is to be of a quick dry rubberized, solvent based coating that is (black) in color. Resists rust and abrasion as it seals out dust and moisture.</p> <p>The application does <u>not</u> include any additional underbody, chassis or body cavity components.</p> <p><b><u>STRUCTURAL BODY WARRANTY</u></b></p> <p>A structural Aluminum body warranty shall be provided by the apparatus manufacturer for products of its manufacture to be free from defects in material and workmanship under normal use and service for a period of ten (10) years. <b>No Exceptions</b></p> <p><b><u>PAINT WARRANTY</u></b></p> <p>A Prorated Paint Warranty shall be provided by the apparatus manufacturer for products of its manufacture to be free from defects in material and workmanship, under normal use and service, for a period of ten (10) years. <b>No Exceptions</b></p> <p><b><u>DIAMOND PLATE FRONT OVERLAYS</u></b></p> <p>The entire front face of the apparatus body shall have aluminum diamond plate overlays installed.</p> <p><b><u>RAW ALUMINUM REAR OVERLAYS</u></b></p> <p>The entire rear face of the apparatus body shall have raw aluminum overlays installed for the installation of chevron striping.</p> <p>All overlay materials shall be coated with 3M adhesive sealant on the back portion to provide an insulating barrier between dissimilar metals.</p> <p><b><u>FRONT CORNER TRIM 1/8" ALUMINUM DIAMOND PLATE</u></b></p> <p>The front of the apparatus body, vertical wall overlay shall be integrated with a 1/8" aluminum diamond plate 1.00 inch x 1.00 inch corner trim pieces for edge protection. The vertical edge trim piece shall extend from the top to bottom and shall be fastened at a minimum of three locations, top, middle, and bottom.</p> <p><b><u>REAR CORNER TRIM 1/8" ALUMINUM DIAMOND PLATE</u></b></p> <p>The rear face of the apparatus body, vertical wall overlays shall be installed with a .125 inch aluminum diamond plate 1.00 inch by 1.00 inch corner trim piece, for edge protection. The</p>		

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

vertical edge trim piece shall extend from the top to bottom and shall be fastened at a minimum of three locations, top, middle, and bottom.

The vertical edge trim piece that is protecting the chevron striping surface or that is utilized for the purpose of striping, shall be secured utilizing fasteners only.

### **CATWALKS**

The catwalks shall be constructed with materials of a non-slip .125 inch embossed aluminum diamond plate.

### **VIBRA-TORQ™ BODY MOUNTING SYSTEM**

The entire body module assembly shall be mounted so that it “floats” above the chassis frame rails exclusively with Vibra-Torq™ torsion isolator assemblies to reduce the vibration and stress providing an extremely durable body mounting system.

The body substructure shall be mounted above the frame to allow independent flexing to occur between the body and the chassis. Each assembly shall be mounted to the chassis frame rails with steel, gusseted mounting brackets. Each bracket shall be powder coated for corrosion resistance. Each body mount bracket shall be mounted to the side chassis frame flange with two 5/8”-UNC Grade 5 HHCS.

Each assembly shall have a two-part rubber vibration isolator. The isolator shall be of a specific durometer to carry the necessary loads of the apparatus body, equipment, tank, water, and hose. The quantity of mounts utilized shall correspond directly to the anticipated weight being supported. Certain assemblies shall also incorporate a torsion spring. Helical coil springs shall be incorporated into specific mounts in tandem with the rubber isolators to minimize the stress absorbed by the body caused from chassis frame rail flexing.

There shall be no welding to the chassis frame rail sides, web or flanges, or drilling of holes in the top or bottom frame flanges between axles. All body to chassis connections shall be bolted so that in the event of an accident, the body shall be easily removable from the truck chassis for repair or replacement.

Because of the constant vibration and twisting action that occurs in chassis frame rails and suspension, the torsion mounting system is required to minimize the possibility of premature body structural failures. The Vibra-Torq™ body mounting system shall have a lifetime warranty. **NO EXCEPTIONS**

### **BODY STRUCTURE WIDTH**

The width of the apparatus body from the outside of the left compartments to the outside of the right compartments shall be 99.00 inch (2.51 m) excluding any attached peripherals such as rub rails, fenderettes, grab handles, etc.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**COMPARTMENT VENTILATION**

To allow for proper air circulation & flow, each compartment shall have a venting route. The venting locations shall be determined by best-fit for each body configuration. Chrome louvered plate vents shall be installed appropriately on the compartment interior walls.

**COMPARTMENTATION**

The following compartments shall be supplied on the apparatus:

**Compartment "L1"**

There shall be one (1) full height compartment ahead of the rear wheels on the left side of the apparatus.

The approximate interior dimensions of this compartment shall be 49.00 inches (1244.60 mm) wide by 69.00 inches (1752.60 mm) high with a depth of 25.50 inches (647.70 mm).

The framed opening shall measure approximately 46.50 inches (1181.10 mm) wide by 65.00 inches (1651.00 mm) high.

The compartment will have approximately 49.89 cubic feet (1.40 cu m) of space.

**Compartment "L2"**

There shall be one (1) compartment located directly over the rear wheels on the left side of the apparatus.

The approximate interior dimensions of this compartment shall be 62.00 inches (1574.80 mm) wide by 35.00 inches (889.00 mm) high with a depth of 25.50 inches (647.70 mm).

The framed opening shall measure approximately 62.00 inches (1574.80 mm) wide by 31.00 inches (787.40 mm) high.

The compartment will have approximately 32.02 cubic feet (0.90 cu m) of space.

**Compartment "L3"**

There shall be one (1) full height compartment located behind the rear wheels on the left side of the apparatus.

The approximate interior dimensions of this compartment shall be 49.00 inches (1244.60 mm) wide by 69.00 inches (1752.60 mm) high with an upper depth of 25.50 inches (647.70 mm) and the lower portion being transverse into the rear compartment, unless partitions are installed.

## Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes No**

The framed opening shall measure approximately 46.50 inches (1181.10 mm) wide by 65.00 inches (1651.00 mm) high.

The compartment will have approximately 49.89 cubic feet (1.40 cu m) of space.

### Compartment "R1"

There shall be one (1) full height compartment ahead of the rear wheels on the right side of the apparatus.

The approximate interior dimensions of this compartment shall be 49.00 inches (1244.60 mm) wide by 69.00 inches (1752.60 mm) high with a lower depth of 25.50 inches (647.70 mm) and an upper depth of 12.50 inches (317.50 mm).

The framed opening shall measure approximately 46.50 inches (1181.10 mm) wide by 65.00 inches (1651.00 mm) high.

The compartment will have approximately 36.62 cubic feet (1.04 cu m) of space.

### Compartment "R2"

There shall be one (1) compartment located directly over the rear wheels on the right side of the apparatus.

The approximate interior dimensions of this compartment shall be 62.00 inches (1574.80 mm) wide by 35.00 inches (889.00 mm) high with a depth of 12.50 inches (317.50 mm).

The framed opening shall measure approximately 62.00 inches (1574.80 mm) wide by 31.00 inches (787.40 mm) high.

The compartment will have approximately 15.70 cubic feet (0.44 cu m) of space.

### Compartment "R3"

There shall be one (1) full height compartment located behind the rear wheels on the right side of the apparatus.

The approximate interior dimensions of this compartment shall be 49.00 inches (1244.60 mm) wide by 69.00 inches (1752.60 mm) high with an upper depth of 12.50 inches (317.50 mm) and the lower portion being transverse into the rear compartment, unless partitions are installed.

The framed opening shall measure approximately 46.50 inches (1181.10 mm) wide by 65.00 inches (1651.00 mm) high.

The compartment will have approximately 36.62 cubic feet (1.04 cu m) of space.

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

### **ROLL-UP DOOR CONSTRUCTION**

All horizontal and vertical side compartment doors shall be roll-up style doors.

### **R•O•M ROLL-UP DOOR**

A R•O•M Corporation Series IV roll-up shutter door shall be installed. Each shutter slat, track, bottom rail, and drip rail shall be constructed from anodized 6063 T6 aluminum.

Shutter slats shall feature a double wall extrusion 0.315 inches thick with a concave interior surface to minimize loose equipment jamming the shutter door closed. Shutter slats shall feature an interlocking end shoe to prevent side to side binding of the shutter door during operation. Slat must have interlocking joints with an inverted locking flange. Slat inner seal shall be a one piece PVC extrusion; seal design shall be such to prevent metal to metal contact while minimizing dirt and water from entering the compartment.

Shutter door track shall be one piece design with integral overlapping flange to provide a clean finished look without the need of caulk. Door track shall feature an extruded Santoprene rubber double lip low profile side seal with a silicone co-extruded back to reduce friction during shutter operation.

Shutter bottom rail shall be a one piece double wall extrusion with integrated finger pull. Finger pull shall be curved upward with a linear striated surface to improve operator grip while operating the shutter door. Bottom rail shall have a smooth contoured interior surface to prevent loose equipment from jamming the shutter door. Bottom rail seal shall be made from Santoprene; it will be a double "V" seal to prevent water and debris from entering compartment. Bottom rail lift bar shall be a one piece "D" shaped aluminum extrusion with linear striations to improve operator grip during operation. Lift bar shall have a wall thickness of 0.125 inches. Lift bar shall be supported by no less than two pivot blocks; pivot blocks shall be constructed from Type 66 Glass filled reinforced nylon for superior strength. Bottom rail end blocks shall have incorporated drain holes which will allow any moisture that collects inside the extrusion to drain out.

Shutter door shall have an enclosed counterbalance system. Counterbalance system shall be 4.00 inches in diameter and held in place by 2 heavy duty 18 gauge zinc plated plates. Counterbalance system shall have 2 over-molded rubber guide wheels to provide a smooth transition from vertical track to counterbalance system.

### **SIDE COMPARTMENT DOOR ALUMINUM SATIN FINISH**

The side compartment roll up doors shall be satin aluminum finish.

### **DOOR OPEN INDICATOR**

Each roll up door shall have an integral door open indicator magnet in the lift bar.

If the door is not properly closed and the parking brake is released, it shall activate the "hazard light" in the cab to alert the crew.

# Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes      No**

## **REAR CENTER COMPARTMENT**

There shall be one (1) compartment, "B1", located at the rear of the apparatus, below the hose bed access area.

The approximate interior dimensions of this compartment shall be 43.00 inches (1092.20 mm) wide and 47.00 inches (1193.80 mm) high or as high as possible determined by the hose bed height and rear configuration. The depth shall be determined by the length of the rear side compartments specified and maximized for the suspension specified for the chassis.

The framed opening shall be approximately 38.00 inches (965.20 mm) wide and 41.00 inches (1041.10 mm) high.

## **REAR COMPARTMENT DOOR**

A non-locking R•O•M Corporation Series IV roll-up shutter door shall be installed. Each shutter slat, track, bottom rail, and drip rail shall be constructed from anodized 6063 T6 aluminum.

Shutter slats shall feature a double wall extrusion 0.315 inches thick with a concave interior surface to minimize loose equipment jamming the shutter door closed. Shutter slats shall feature an interlocking end shoe to prevent side to side binding of the shutter door during operation. Slat must have interlocking joints with an inverted locking flange. Slat inner seal shall be a one piece PVC extrusion; seal design shall be such to prevent metal to metal contact while minimizing dirt and water from entering the compartment.

Shutter door track shall be one piece design with integral overlapping flange to provide a clean finished look without the need of caulk. Door track shall feature an extruded Santoprene rubber double lip low profile side seal with a silicone co-extruded back to reduce friction during shutter operation.

Shutter bottom rail shall be a one piece double wall extrusion with integrated finger pull. Finger pull shall be curved upward with a linear striated surface to improve operator grip while operating the shutter door. Bottom rail shall have a smooth contoured interior surface to prevent loose equipment from jamming the shutter door. Bottom rail seal shall be made from Santoprene; it will be a double "V" seal to prevent water and debris from entering compartment. Bottom rail lift bar shall be a one piece "D" shaped aluminum extrusion with linear striations to improve operator grip during operation. Lift bar shall have a wall thickness of 0.125 inches. Lift bar shall be supported by no less than two pivot blocks; pivot blocks shall be constructed from Type 66 Glass filled reinforced nylon for superior strength. Bottom rail end blocks shall have incorporated drain holes which will allow any moisture that collects inside the extrusion to drain out.

Shutter door shall have an enclosed counterbalance system. Counterbalance system shall be 4.00 inches in diameter and held in place by 2 heavy duty 18 gauge zinc plated plates. Counterbalance system shall have 2 over-molded rubber guide wheels to provide a smooth transition from vertical track to counterbalance system.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**REAR COMPARTMENT DOOR FINISH**

The rear center compartment door shall be satin aluminum finish.

**DOOR OPEN INDICATOR**

Each roll up door shall have an integral door open indicator magnet in the lift bar.

If the door is not properly closed and the parking brake is released, it shall activate the “hazard light” in the cab to alert the crew.

**RECESSED INTERMEDIATE REAR STEP**

There will be a 10.00 inch recessed intermediate step above the rear center compartment designed into the rear body wall. This step will shorten the length of the hose bed by 10.00 inches and lower the door opening of the rear center compartment. The stepping surface shall be overlaid with embossed diamond plate, while the side shall be overlaid with standard diamond plate. **No Exceptions**

**STEP LIGHTING**

One (1) light shall be installed to illuminate the stepping areas as provided. The light shall be a LED Tube light model #RX-15T16-5050-21CM with an aluminum mounting bezel.

The light shall be directed towards and positioned above the stepping surfaces.

**STEP LIGHT ACTIVATION**

The step light shall be activated when the park brake is set.

**SILL PLATES**

Brushed stainless steel sill plates shall be installed at the bottom of each body compartment door opening. **No Exceptions**

**COMPARTMENT LIGHTING**

Two (2) LED Tube lights model #RX-15T16-5050 shall be installed in each body compartment. The tube lights shall be centered vertically along each side of the door framing and at maximum length available to fit the opening.

The lights in each compartment shall be on a separate circuit, turning on only those lights that have open compartment doors.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**COMPARTMENT LIGHTING ACTIVATION**

Each compartment light shall be activated with the ignition, park brake and the respective compartment door open switch

**REAR TAILBOARD**

The rear of the apparatus body shall be vertical in design - otherwise known as a 'flat-back'.

The rear tailboard shall be fabricated of the same tubular materials as used in the apparatus body.

The tailboard shall be an independent assembly welded to the rear body structural framing to provide body protection and a solid rear stepping platform.

The rear step shall be designed to incorporate "crush zone" technology. This idea incorporates lighter materials in the tailboard than the body structure so the step will "crush" in a collision before the body structure.

On the rear body surface, a sign shall be attached that states: "DO NOT RIDE ON REAR STEP, DEATH OR SERIOUS INJURY MAY RESULT."

The rear tailboard and body shall be constructed such that the angle of departure shall be no less than 8 degrees at the rear of the apparatus when fully loaded (NFPA) 1901, Standard for Automotive Fire Apparatus.

**TAILBOARD LENGTH**

The rear tailboard shall be approximately 13.50 inches (342.90 mm) deep and shall incorporate a .188 inch (4.78 mm) embossed aluminum diamond plate overlay.

The stepping area shall span the width of the apparatus, overlapping the perimeter of the structural tailboard framework.

**WHEEL WELLS**

Wheel wells shall have semicircular black polymer composite inner liners that are bolted to the wheel well panel and supported inboard by brackets that are connected to the body framework. Each wheel well shall be a continuous piece with no breaks or ledges where road grime or debris may accumulate. This liner shall be removable for access to suspension assembly for repairs. There shall be no exception to the bolted wheel well inner liner requirement.

**WHEEL WELL MODULES**

The body wheel well area shall be fabricated of same material type as the body and finish painted. There shall be "smart storage" compartmentation features incorporated on each side of the apparatus body wheel well modules to utilize and maximize storage space availability.



<b>Fannin County Fire-Rescue</b>	<b>Bidder Complies</b>	
	Yes	No
<p><b><u>LEFT FRONT WHEEL WELL</u></b></p> <p>There shall be provisions in the wheel well on the left side in front of the axle.</p> <p><b><u>SCBA COMPARTMENT</u></b></p> <p>The compartment shall hold three (3) 6.75 inch (171.45 mm) Diameter x 24.00 inch (609.60 mm) long SCBA bottles with 1.00 inch (25.40 mm) nylon safety loops installed.</p> <p><b><u>LEFT REAR WHEEL WELL</u></b></p> <p>There shall be provisions in the wheel well on the left side behind the axle.</p> <p><b><u>FUEL FILL &amp; CYLINDER COMPARTMENT</u></b></p> <p>The compartment shall accommodate the fuel fill and hold one (1) 2.5 gallon H2O bottle with 1.00 inch (25.40 mm) nylon safety loop installed.</p> <p><b><u>SMART STORAGE FUEL FILL ASSEMBLY</u></b></p> <p>There shall be a fuel fill assembly located on the apparatus body accessing the chassis supplied fuel tank. The assembly shall be located in the rear Smart Storage module specified behind the rear axle.</p> <p>There shall be a drain in the fuel fill assembly to allow overflow to drain on the back side of the apparatus body. The fuel fill cap shall be manufactured of plastic materials, green in color and equipped with a tether.</p> <p>The fuel fill cap shall be labeled "DIESEL FUEL". The fuel fill neck shall have a .375 inch inside diameter vent line installed from the top of the fuel tank to the fill tube.</p> <p><b><u>RIGHT FRONT WHEEL WELL</u></b></p> <p>There shall be provisions in the wheel well on the front side in front of the axle.</p> <p><b><u>SCBA COMPARTMENT</u></b></p> <p>The compartment shall hold three (3) 6.75 inch (171.45 mm) Diameter x 24.00 inch (609.60 mm) long SCBA bottles with 1.00 inch (25.40 mm) nylon safety loops installed.</p> <p><b><u>RIGHT REAR WHEEL WELL</u></b></p> <p>There shall be provisions in the wheel well on the right side behind the axle.</p> <p><b><u>FIRE EXTINGUISHER STORAGE COMPARTMENT</u></b></p> <p>The compartment shall hold one (1) 2.5 gallon water extinguisher and one (1) 20 lb. ABC fire extinguisher.</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**SMART STORAGE DOORS**

The smart storage compartment doors shall be smooth and painted stainless steel to match body job color. Where a module storage compartment is specified, a hinged door shall be provided. Each compartment door shall be secured with a round chrome latch.

**DOOR OPEN INDICATOR**

There shall be a switch installed for each smart storage compartment door.

If the door is not properly closed and the parking brake is released, it shall activate the “hazard light” in the cab to alert the crew.

**FENDERETTES**

Two (2) polished stainless steel fenderettes shall be provided and installed on body rear wheel well openings, one (1) each side. Rubber welting shall be provided between the body and the crown to seal the seam and restrict moisture from entering. A dielectric barrier shall be provided between the fender crown fasteners (screws) and the fender sheet metal to resist deterioration.

**LEFT SIDE UPPER STORAGE COMPARTMENTS**

Two (2) storage compartments shall be provided and installed on the upper left side of the apparatus body. The approximate length of each compartment shall be 80.00 inches long. The depth of the compartments shall be determined by the hose bed wall height. The compartment shall extend beyond the apparatus body roof and walking surface and provide a vertical edge to prevent water intrusion. An adhesive backed bulb seal shall be applied to the underside perimeter of the lid, excluding the hinge side, to ensure a positive seal.

The formed doors, incorporating broken edges of 45 degrees or less, shall extend over the compartments edge approximately 1.00 inch to minimize water penetration. Each door shall be secured by push button weather resistant (C5) South Co Brand style latches. The doors shall be fabricated of embossed aluminum diamond plate and be secured by a stainless steel hinge. If deemed necessary due to width, the doors shall be reinforced to act as a suitable walking or standing surface. Each door shall be held open by a gas charged strut on each side and permit full access to the compartment along its length. The struts shall be concealed inside the compartment when the door is in the closed position. The compartments shall be constructed as part of the body and be accessible from the hose bed area.

The upper compartments shall not be vented. There shall be plastic tubing installed for adequate drainage that is routed from corners of the upper compartment floors down to below the lower compartment floor level.

**RIGHT SIDE UPPER STORAGE COMPARTMENTS**

Two (2) storage compartments shall be provided and installed on the upper right side of the

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

apparatus body. The approximate length of each compartment shall be 80.00 inches long. The depth of the compartments shall be determined by the hose bed wall height. The compartment shall extend beyond the apparatus body roof and walking surface and provide a vertical edge to prevent water intrusion. An adhesive backed bulb seal shall be applied to the underside perimeter of the lid, excluding the hinge side, to ensure a positive seal.

The formed doors, incorporating broken edges of 45 degrees or less, shall extend over the compartments edge approximately 1.00 inch to minimize water penetration. Each door shall be secured by push button weather resistant (C5) South Co Brand style latches. The doors shall be fabricated of embossed aluminum diamond plate and be secured by a stainless steel hinge. If deemed necessary due to width, the doors shall be reinforced to act as a suitable walking or standing surface. Each door shall be held open by a gas charged strut on each side and permit full access to the compartment along its length. The struts shall be concealed inside the compartment when the door is in the closed position. The compartments shall be constructed as part of the body and be accessible from the hose bed area.

The upper compartments shall not be vented. There shall be plastic tubing installed for adequate drainage that is routed from corners of the upper compartment floors down to below the lower compartment floor level.

### **UPPER STORAGE COMPARTMENT LIGHTING**

One (1) LED Tube light model #RX-15T16-5050 shall be installed in each upper body storage compartment along the hinge. The tube light shall be of maximum length available to fit in the compartment.

The lights shall be on a separate circuit, activating only those lights that have an open compartment door.

### **STANDING PLATFORM**

There shall be an open rear section above the access ladder recessed into the upper back of the body to act as a standing platform/landing area to allow access to the upper storage area of the body. The opening of the platform shall be approximately 11.00 inches (0.28 m) wide with the interior landing area being of maximum width for the design and approximately 12.00 inches (0.30m) long to the rear off the upper storage compartment. **No Exceptions**

The vertical and horizontal surfaces shall be finished with embossed aluminum diamond plate.

### **SUPERLINER COMPARTMENT FINISH**

The upper storage compartment interiors shall be coated with Superliner.

### **COMPARTMENT FINISH COLOR**

The Superliner Color shall be Medium Gray.

Fannin County Fire-Rescue

Bidder  
Complies

Yes No

**HOSE STORAGE**

A hose bed shall be provided and installed with the minimum capacity as required by (NFPA) 1901, Standard for Automotive Fire Apparatus.

The hose bed shall have a slotted .25 inch (6.35 mm) aluminum flooring installed to allow drainage through the tank cavity to the ground below.

The aluminum flooring shall be manufactured in discrete sections to allow for ease of removal and stability. The area shall be free of sharp edges to protect the hose when loading and unloading.

**HOSE BED AREA**

The hose bed area of the apparatus shall be overlaid with brushed stainless steel material.

**HOSE BED AREA TRIMMED W/ BRUSHED SST**

The vertical corners at the back hose bed shall be trimmed with brushed stainless steel. The trim shall extend from the hose floor level up to the top edge of the body side.

**HOSE BED WALL CAP**

The top rail on the hose bed side walls shall have a trim cap fabricated of 16 gauge brushed 304L stainless steel. The cap shall run the entire length of the hose bed side wall and shall provide a smooth surface with a highly finished appearance. It shall extend down at least 1.00 inch on each side of the hose bed side wall.

**HOSE BED WALL HEIGHT**

The walls of the hose bed shall be 100.00 inches (2.54 m) tall, measured from the bottom edge of the compartments to the top flange.

**'A' FRAME HOSE BED COVER**

There shall be a double door cover provided and installed which overlays a tubular structure for the hose bed. **No Exceptions**

Each cover shall be capable of supporting 600 pounds (272 kg) while standing on the cover. Each cover shall be capable of being opened independently and rest on a tubular structure which runs down the middle of the hose bed with a truss support at the rear of the apparatus. The covers in the closed position shall be higher in the center of the hose bed than they are at the hinged end to create an 'A' frame appearance and to aid in water runoff. **No Exceptions**

The front and rear of hose bed covers shall have vertical end caps that extend down to create a level line of diamond plate the width of the covers. **No Exceptions**

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

The doors shall be fabricated of .125 inch (3.18 mm) embossed aluminum diamond plate with full length two-piece stainless steel piano hinges.

The hose bed covers shall be wired to the hazard light in chassis cab. Inductive proximity switches shall be installed at the hose bed cover door hinges. If the door is not properly closed with the parking brake released, it shall activate the "hazard light" in the cab to alert the crew.

### **MANUAL RAISED COVERS**

Each cover shall be raised independently and manually. There shall be a gas shock hold open device provided to hold each cover in the open position. Each gas shock shall be accompanied by a vinyl covered safety chain.

### **HANDRAILS**

Two (2) 1.25-inch diameter handrails constructed of bright-anodized knurled extruded aluminum with 18.00 inches of grip surface shall be installed on top of the hose bed covers, one (1) each cover, accessible from the rear of the apparatus.

### **SYNTEX VINYL REAR HOSE BED RESTRAINT**

There shall be a vinyl flap that extends down over the rear of the hose bed provided and installed with the apparatus. The cover shall be fastened by an elastic shock cord sewn into the tarp with brass grommets where the shock cord passes through the hose bed cover. Hooks shall be provided on the lower corners to provide a means of attaching the cover to the apparatus. The hooks shall be made of cast aluminum.

### **REAR FLAP COLOR**

The rear flap shall be red.

### **HOSE BED DUNNAGE AREA**

A vertical bulkhead shall be provided and installed at the front of the hose bed area, behind the water tank fill tower, forming a storage area that is separated from the hose bed.

The rear face of the bulkhead shall serve as a mounting surface for the hose bed dividers, resulting in the ability to move any hose bed divider across the entire width of the hose bed.

### **HOSE BED DIVIDER(S)**

There shall be a full height adjustable divider provided and installed in the hose bed area of the apparatus body.

The divider shall be fabricated of .25 inch (6.35 mm) thick aluminum plate with a double sided reinforcement and attached to the adjustable slide rails. The rear of the divider shall have a radius to provide a smooth corner. Hose payout shall be unobstructed by the divider.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

There shall be a total of two (2) provided and installed in the hose bed.

**HOSE LOAD**

The hose bed shall accommodate the following hose loads:

**BAY 1:**

-250 feet of 2.50 inch hose

**BAY 2:**

-1000 feet of 5.00 inch hose

**TANK CAPACITY**

The tank shall be 1000 gallons (3785 liters) in capacity.

**PRO POLY POLYPRENE TANK**

The water tank shall be designed to utilize cavities that have commonly been wasted space. The water tank shall extend up and over the rear center compartment to just behind the rear body wall. The water tank shall fill the void between the main hose bed floor and the top of the rear center compartment. This tank design shall provide for a lower overall tank height, resulting in a lower overall main hose bed height. In addition, this design shall create a lower center of gravity of the vehicle, for improved vehicle handling. NO EXCEPTIONS

**TANK CONSTRUCTION**

The booster tank shall be constructed of .50 inch (12.70 mm) thick Polyprene sheet stock which is a non-corrosive stress relieved thermoplastic. It shall be designed to be completely independent of the body and compartments. All joints and seams are extrusion welded and/or contain the "Bent Edge" and tested for maximum strength and integrity. The top of the booster tank is fitted with lifting eyes designed with a 3 to 1 safety factor to facilitate tank removal.

**COVER**

The tank cover shall be constructed of .50 inch (12.70 mm) thick Polyprene and shall be recessed. A minimum of two lifting dowels shall be drilled and tapped .50 inch (12.70 mm) x 2.00 inch (50.00 mm) to accommodate the lifting eyes.

**BAFFLES**

The swash partitions shall be manufactured from .50 inch (12.70 mm) Polyprene. All partitions shall be equipped with vent and air holes to permit movement of air and water

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

between compartments to provide maximum water flow. All swash partitions interlock and are welded to one another as well as to the walls of the tank.

### **MOUNTING**

The tank shall have a reinforced .75 inch (19.10 mm) floor for added strength and durability. The tank shall be isolated from the body substructure cross members with .50 inch (12.70 mm) x 2.50 inch (65.00 mm) rubber strips that are 60 durometer in hardness. The tank shall sit nested inside the center body substructure and shall be completely removable without disturbing the body side panels. Tank stops on all four sides will keep the tank from shifting front to back or side to side.

### **TANK WARRANTY**

A lifetime tank warranty will be provided by the tank manufacturer, Pro Poly.

Please see the official warranty document in the appendix (attached) for specific details.

### **FILL TOWER**

The fill tower opening shall be approximately 13.00 inches (330.20 mm) x 12.00 inches (304.80 mm).

The tower will have a .25 inch (6.40 mm) thick removable Polyprene screen and a Polyprene hinged type cover that will open if the tank is filled at an excess rate. There shall be a removable .25 inch (6.40 mm) thick Polyprene screen to prevent debris from falling into the tank.

The fill tower shall have a 4.00 inch (100.00 mm) overflow that will discharge underneath the tank, behind the rear axle(s), avoiding the chassis fuel tank and suspension components where applicable. The overflow shall terminate above the tank water level when filled to the rated capacity.

### **FILL TOWER LOCATION**

The fill tower shall be located to the left side at the front of the hose bed.

### **SUMP**

The Two (2) sumps will be constructed in an 8.00 inch (203.20 mm) x 16.00 inch (406.40 mm) x 3.00 inch (77.00 mm) deep area.

The construction material shall utilize .50 inch (12.70 mm) Polyprene and be located in line with the tank suction valves. There shall be Two (2) 4.00 inch (100.00 mm) schedule 40 Polyprene tubes installed that will run from the suction outlet to the sump locations. The tank will have an anti-swirl plate located approximately 2.00 inch (50.00 mm) above the sumps.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**SUMP PLUG**

The sump shall have a 3.00 inch (77.00 mm) plug for use in draining and cleaning out the tank.

**OUTLETS**

In addition to the tank suction valve outlet located in the sump, there shall be an outlet provided for the tank fill valve. If there are any additional options selected (such as an extra tank suction or direct tank inlets), there shall be additional outlets provided to accommodate these items.

**LADDER COMPARTMENT**

The ground ladders shall be stored within a compartment installed beside the booster tank.

All items shall be stored in their own independent section to allow one item to be removed without disturbing another. There shall be polypropylene slide angles installed in each section where applicable, and for the ladders to slide on. There shall be a stop in the front of each section to prevent the items from sliding forward.

**LADDER COMPARTMENT MATERIAL**

The ground ladder compartment shall be fabricated of .125-inch smooth aluminum.

**LADDER COMPARTMENT LOCATION**

The ground ladder compartment shall be mounted vertically on the right side of the water tank.

**LADDER COMPARTMENT END CAP**

The compartment shall be enclosed through to the pumphouse and incorporate a removable weather resistant end cap, providing access for serviceability, drainage, and cleaning.

**No Exceptions**

**LADDER COMPARTMENT DOOR HINGE LOCATION**

The door hinge shall be mounted vertically across the outboard edge of the compartment door opening.

**LADDER COMPARTMENT DOOR**

The door material shall match the rear overlay material. The door shall have two (2) push button type latches installed with a chrome handle centered between the push button latches. If the door is not properly closed and the parking brake is released, it shall activate the “hazard light” in the cab to alert the crew.



<b>Fannin County Fire-Rescue</b>	<b>Bidder Complies</b>	
	Yes	No
<p><b><u>LADDER COMPARTMENT DOOR REFLECTIVE CHEVRON</u></b></p> <p>The ladder compartment door shall be left unfinished and include retro-reflective chevron material matching the rear of the apparatus.</p> <p><b><u>LADDER COMPLEMENT</u></b></p> <p>The following ladders shall be supplied with the apparatus:</p> <p>One (1) Duo-Safety 24 foot (7.0 m) two (2) section aluminum extension ladder(s), model 900A.</p> <p>One (1) Duo-Safety 14 foot (4.0 m) aluminum roof ladder(s) with folding hooks, model 775A.</p> <p>One (1) Duo-Safety 10 foot (3.0 m) aluminum attic ladder(s), model 585A.</p> <p><b><u>PIKE POLE STORAGE</u></b></p> <p>There shall be two (2) tubes provided for storage of the pike poles installed with the ground ladder complement.</p> <p>The pike poles provided shall be standard hook with straight handle.</p> <p>The pike poles shall be supplied and installed by the Fire Department before the apparatus is placed into service.</p> <p><b><u>SUCTION HOSE STORAGE</u></b></p> <p>One (1) suction hose compartment shall be provided in the lower section on each side of the body, manufactured integral to the upper storage compartments. There shall be a permanent divider above the hose storage area, creating a floor for the upper storage compartments.</p> <p>All items shall be stored in their own sleeve to allow one item to be removed without disturbing the others. There shall be a stop located in the front section to prevent each item from sliding forward.</p> <p>The interior floor of the compartments shall be lined with black ABS plastic for ease of storing and removing the suction hose.</p> <p><b><u>ENCLOSED SUCTION HOSE COMPARTMENTS DOOR</u></b></p> <p>Each door for the suction hose compartments shall be fabricated of the same material as the rear overlay, hinged on the outboard edge and shall be equipped with one (1) push button style latch.</p> <p>If the door is not properly closed and the parking brake is released, it shall activate the “hazard light” in the cab to alert the crew.</p>		

<b>Fannin County Fire-Rescue</b>	<b>Bidder Complies</b>	
	Yes	No
<p><b><u>STORAGE COMPARTMENT DOOR HINGE LOCATION</u></b></p> <p>The door hinge shall be mounted vertically on the outboard edge of the compartment door opening.</p> <p><b><u>EQUIPMENT DOOR STRIPING</u></b></p> <p>Retro-Reflective striping in a chevron pattern matching the rear layout shall be provided on the equipment access door.</p> <p><b><u>ENCLOSED SUCTION HOSE COMPARTMENT LOCATION</u></b></p> <p>The compartment shall be located in the top upper body side of the apparatus.</p> <p>There shall be 2 - 10 foot length(s) of 6.00 inch clear PVC suction hose with lightweight couplings provided with the above specified storage.</p> <p><b><u>RESCUE STORAGE COMPARTMENT</u></b></p> <p>There shall be a rescue equipment storage compartment provided and installed with the apparatus. The compartment shall be constructed of .125 inch (3.18 mm) smooth aluminum.</p> <p>All items shall be stored in their own independent section to allow one item to be removed without disturbing another. As required, there shall be a stop in the front of each section to prevent items from sliding forward.</p> <p>The interior floor of the compartment shall be lined with black ABS plastic for ease of stowing and un-stowing equipment.</p> <p>The compartment shall include provisions for mounting the following:</p> <ul style="list-style-type: none"> <li>-One (1) Backboard with inside dimensions of 18.00 inches by 2.50 inches by 75.00 inches.</li> <li>-One (1) Stokes basket with inside dimensions of 26.00 inches by 9.00 inches by 86.00 inches.</li> </ul> <p><b><u>RESCUE COMPARTMENT LOCATION</u></b></p> <p>The storage compartment shall be located in the hose bed storage area vertical on the right side.</p> <p><b><u>DIAMOND PLATE HINGED DOOR</u></b></p> <p>The compartment shall have a hinged door to access equipment. The door shall be fabricated with .125 aluminum diamond plate and shall be secured with two (2) push button type latches and a 7.00 inch chrome handle centered between the latches.</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

If the door is not properly closed and the transmission is placed into drive or reverse mode with the parking brake released, it shall activate the hazard light in the cab to alert the crew.

**COMPARTMENT UNISTRUT**

Vertically mounted Unistrut shall be installed in all apparatus body compartments, in the upper and lower sections, to accommodate the installation of shelves, trays, and or other miscellaneous equipment.

**OVER-WHEEL COMPARTMENT PARTITIONS**

Compartment partitions fabricated of the same material as the body shall be permanently installed in the left over-wheel compartment, right over-wheel compartment, or both where applicable by design.

The partitions shall be permanently installed in place and flush to the forward and rearward frame openings.

The partitions shall aid in keeping loose equipment from falling into the fore and aft compartments.

**FIXED VERTICAL COMPARTMENT DIVIDER(S)**

A permanently mounted sheet metal compartment divider shall be installed in each compartment specified. There shall be vertical Unistrut tracks attached to each side of the divider to aid in equipment mounting.

The following shall be provided in each compartment:

**SHELVING**

The shelving shall be made out of .190 inch (4.83 mm) smooth aluminum sheet material with a formed 2.00 inch (50.80 mm) lip on the front and back.

The side mounting brackets shall be provided for vertical adjustment.

Standard manufacture shelf construction capacity ratings are as follows, any requested change to the manufacture's standard design may affect/reduce the ratings accordingly:

Shelving shall be rated at a capacity of 200 pounds (90.72 kg) and applicable to the design configuration.

The following shelving shall be provided:

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**UPPER HALF DEPTH SHELVING**

A half depth shelf mounted between the fixed compartment divider and the forward wall shall be provided and installed in the upper area of the compartment specified.

There shall be a total quantity of two (2) provided.

- Two (2) located in the L1 compartment.

**UPPER HALF DEPTH SHELVING**

A full width x half depth shelf shall be provided and installed in the upper area of the compartment specified.

There shall be a total quantity of two (2) provided.

- One (1) located in the R1 compartment.
- One (1) located in the R3 compartment.

**REAR COMPARTMENT SHELF**

An adjustable shelf installed in the rear center compartment, B-1, of the apparatus. Each shelf shall be as wide and deep as possible.

There shall be a total quantity of one (1) provided.

**ROLL OUT TRAY(S)**

Each tray shall be fabricated of .19 inch (4.83 mm) thick 3003 grade or higher aluminum sheet material with four (4) 3.00 inch (76.20 mm) side flanges, corner welded for maximum strength and shall be as wide and as deep as compartment allows.

The following shall be supplied:

**ROLL-OUT ASSEMBLY/AUSTIN**

The floor mounted tray shall be full width and shall be secured to an Austin Hardware 22.00 inch (558.80 mm) long ball bearing "heavy duty" slide assembly. The slide assemblies shall incorporate cadmium plated ball bearing roller slides and a lock-in, lock-out front drawer release system (FDR).

The tray shall have a 300# capacity and 100% extension.

There shall be a total quantity of five (5) provided.

- One (1) located in the L1 compartment.

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p>- One (1) located in the R1 compartment.</p> <p>- One (1) located in the rear center compartment.</p> <p><b><u>ROLL-OUT ASSEMBLY/SLIDE MASTER</u></b></p> <p>The floor mounted tray shall be full width and shall be secured to a (Slide Master) roll-out system constructed of “heavy duty steel” with structural tube and channels. The slide assemblies shall incorporate cadmium plated ball bearing roller slides and a latching device to hold the tray in the stored position.</p> <p>The tray shall have a 600# capacity and 100% extension.</p> <p>There shall be a total quantity of one (1) provided.</p> <p>This tray will have an adjustable tool board in it.</p> <p>Each slide shall be held in the locked position by a lever actuated twist lock.</p> <p>Each Slide Master slide shall be <u>wet painted</u> {silver} in color.</p> <p>- One (1) located in the L3 compartment.</p> <p><b><u>ROLL-OUT ASSEMBLY/AUSTIN</u></b></p> <p>The adjustable tray shall be full width and shall be secured to an Austin Hardware 22.00 inch (558.80 mm) long ball bearing "heavy duty" slide assembly. The slide assemblies shall incorporate cadmium plated ball bearing roller slides and a lock-in, lock-out front drawer release system (FDR).</p> <p>The tray shall have a 300# capacity and 100% extension and adjustable height utilizing unistrut materials.</p> <p>There shall be a total quantity of one (1) provided.</p> <p>- One (1) located in the L3 compartment.</p> <p><b><u>PULL-OUT TOOL BOARD/PAC TRAC</u></b></p> <p>A Pac-Trac pull-out tool board with DA finish shall be installed in the compartment as specified. The tool board shall be attached to unistrut material mounted on the floor and ceiling of the compartment, extending perpendicular to the rear wall, allowing for horizontal adjustment from front to rear.</p> <p>The tool board shall be mounted utilizing a SlideMaster slide with locking device at the bottom to keep the board in the stored and extended positions.</p>		

# Fannin County Fire-Rescue

**Bidder  
Complies**

**Yes    No**

There shall be a total quantity of one (1).

The pull-out/swing-out style tool board shall have RED reflective striping installed making the perimeter of the tool board more readily visible.

- One (1) located in the L1 compartment rearward of the fixed vertical divider.

- One (1) located in the L3 compartment. This will be configured so that it will be adjustable left to right on a roll out tray.

## **ADJUSTABLE DEPTH SWING-OUT TOOL BOARD/ALUMINUM**

An aluminum swing-out tool board with DA finish shall be installed in the compartment as specified. The tool board shall be fabricated within a structural tubular frame, supported on a pivot rod, seated in bearings attached to the compartment floor and upper bracket.

The tool board shall be mounted to unistrut channels to enable adjustment of the tool panel at various depths within the compartment.

The tool board shall be capable of swinging open to a position perpendicular to the rear wall. A thumb latch and gas shock shall be installed to keep the board in the open and or closed positions.

There shall be a total quantity of one (1).

The pull-out/swing-out style tool board shall have RED reflective striping installed making the perimeter of the tool board more readily visible.

- One (1) located in the L2 compartment.

## **SIDE RUB RAILS (ALUMINUM CHANNEL)**

The lowest edge of the apparatus body side compartments shall be trimmed with brightly anodized aluminum channel rub rail material.

The rub rails shall be approximately 3.00 inches high with flanges turned outwards for increased rigidity, with each end chamfered to a 45 degree angle. The rub rails shall not be constructed as an integral part of the apparatus body structure, allowing each rub rail to be easily removed in the event of damage.

The rub rails shall be secured with stainless steel fasteners and spaced away from the apparatus body with .50 inch nylon spacers to help absorb moderate side impacts and prevent the collection of water and debris for easier cleaning.

## **FOLDING STEPS**

Cast Products, Inc. model #SP6610-1CH dual LED illuminated folding steps, made of high

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

strength die cast aluminum with a protective chromed coating, pyramid tread platform, conforming to current NFPA requirements, shall be provided and installed on the apparatus as specified.

The steps shall have a minimum of 46 sq. inches of surface area capable of sustaining a 1200 lb. static load. The steps shall be mounted no more than 18" inches between each step.

**STEP LOCATION**

Three (3) folding steps shall be installed on the right forward vertical wall of the front compartment.

**10" HANDRAILS**

One (1) 10.00 inch long by 1.25 inch diameter handrail constructed of extruded aluminum with a knurled grip, full length red reflective strip and full length illuminated LED light strip shall be installed in a location above the forward step(s) and in accordance with (NFPA) 1901, Standard for Automotive Fire Apparatus, standard requirements. There shall be a minimum of 2.00 inches of clearance between the bracket and the body.

Each handrail LED light strip specified shall be white/clear in color.

**ILLUMINATED HANDRAIL LIGHTING ACTIVATION**

The illuminated handrail light shall be activated when the park brake is set.

**STEP LIGHT ACTIVATION**

The step light shall be activated when the park brake is set.

**STEP LOCATION**

Three (3) folding steps shall be installed on the left forward vertical wall of the front compartment.

**10" HANDRAILS**

One (1) 10.00 inch long by 1.25 inch diameter handrail constructed of extruded aluminum with a knurled grip, full length red reflective strip and full length illuminated LED light strip shall be installed in a location above the forward step(s) and in accordance with (NFPA) 1901, Standard for Automotive Fire Apparatus, standard requirements. There shall be a minimum of 2.00 inches of clearance between the bracket and the body.

Each handrail LED light strip specified shall be white/clear in color.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**ILLUMINATED HANDRAIL LIGHTING ACTIVATION**

The illuminated handrail light shall be activated when the park brake is set.

**STEP LIGHT ACTIVATION**

The step light shall be activated when the park brake is set.

**INTERMEDIATE REAR STEP**

The rear step shall be 8.75 inches (222.25 mm) in depth.

The step shall be constructed of an 8.13 inch (206.50 mm) wide piece of extruded stair tread "Diamondback" grip material and spaced away from the back of the body 0.75 inch (19.05 mm) to provide an 8.75 inch (222.25 mm) deep stepping surface.

The step shall be mounted on the flat back of the apparatus with gusset-type mounting to provide sufficient support for loading and deploying hose and for gaining access to the hose bed area.

**INTERMEDIATE REAR STEP LOCATION**

The rear step shall be located as high as possible beneath the hose bed floor and the horizontal handrail specified.

**STEP LIGHTING**

One (1) light shall be installed to illuminate the stepping areas as provided. The light shall be a LED Tube light model #RX-15T16-5050-21CM with an aluminum mounting bezel.

The light shall be directed towards and positioned above the stepping surfaces.

**STEP LIGHT ACTIVATION**

The step light shall be activated when the park brake is set.

**"SMART" ALUMINUM ACCESS LADDER No Exception**

A "Smart" aluminum fold down access ladder shall be provided at the rear of the apparatus. The ladder rungs shall be constructed of a slip resistant stepping material.

The upper section shall be permanently secured to the body with a mechanical style hinge and fasteners that allow the ladder to extend down and out to the ground from the apparatus body. When deployed, the fold-down steps shall create a safe and comfortable climbing angle.

Two (2) gas cylinders shall be installed to assist in the deployment of the lower fold-down section. A mechanical locking mechanism shall be provided to retain the ladder in a stowed



## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

and secured position when in transit or when not in use. Access ladder rung illumination shall be provided during low light conditions.

A notch will be provided on all tailboards 'exceeding' 13.50 inches deep when specifying the addition of a Smart Fold Down Ladder. The notch will provide the proper clearance to allow the ladder to 'swing down' freely when being deployed.

If the step is not properly stowed and the parking brake is released, it shall activate the hazard light in the cab to alert the crew.

### **ACCESS LADDER LOCATION**

The ladder shall be installed at the rear of the apparatus on the left side.

### **STEP LIGHTING**

One (1) light shall be installed to illuminate the stepping areas as provided. The light shall be a LED Tube light model #RX-15T16-5050-21CM with an aluminum mounting bezel.

The light shall be directed towards and positioned above the stepping surfaces.

### **STEP LIGHT ACTIVATION**

The step light shall be activated when the park brake is set.

### **HANDRAILS KNURLED ALUMINUM ILLUMINATED**

Handrails shall be 1.25 inches in diameter, constructed of extruded aluminum with a knurled grip, full length red reflective strip and full length illuminated LED light strip.

There shall be a 2.00 inch minimum clearance between the handrail and the body. The light shall illuminate an area adjacent to the handrail and in accordance with (NFPA) 1901, Standard for Automotive Fire Apparatus, standard requirements.

The following handrails shall be installed at the approximate lengths noted:

### **REAR HANDRAIL LOCATION**

Two (2) handrails shall be installed on the rear of the apparatus. Each handrail shall be of an adequate length, as available usable space allows, to provide a suitable gripping area for personnel.

The handrails shall be spaced away from the body using chrome plated straight stanchions. One (1) vertical handrail shall be installed just below the hose bed side opposite of the rear access ladder. This vertical handrail shall utilize an offset stanchion with the offset directed away from storage door openings for added clearance where applicable.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

The remaining handrail shall be installed horizontally, just below the hose bed area.

Each handrail LED light strip specified shall be white/clear in color.

**ILLUMINATED HANDRAIL LIGHTING ACTIVATION**

The illuminated handrail light shall be activated when the park brake is set.

**TOW EYES**

There shall be two (2) rear tow eyes installed to the frame rails, one each side, accessible below the rear of the apparatus.

They shall be manufactured of 1.00 inch plate steel and each plate shall be bolted to the chassis frame rail with a minimum quantity of six (6) grade 8 bolts. The two plates shall be anchored together with 1.00 inch steel tubing to prevent swaying of the frame rails during a towing operation. All steel components shall be painted black.

**SIDE RECEIVERS**

There shall be a rescue winch receiver tube located in line with the rear tow eyes below the body, behind the rear axle on the left and right side. The receiver shall have a maximum straight line pull capacity equaling 9000 pounds (4080 kg) to either side.

Each receiver shall have a 2.00 inch (50.80 mm) square opening for the attachment of a portable rescue winch.

A receptacle shall be supplied adjacent to each rescue winch receiver tube and wired for a portable electric winch.

A label shall be permanently affixed on or near each winch receiver indicating the maximum straight line pull rating of the anchor.

**REAR RECEIVER**

A rescue winch receiver shall be installed at the rear of the apparatus mounted directly to the chassis frame rails and below the apparatus in the center. The receiver shall have a maximum straight line pull capacity equaling 9000 pounds (4080 kg).

The receiver shall have a 2.00 inch (50.80 mm) square opening for the attachment of a portable rescue winch.

A power receptacle shall be installed adjacent to the rescue winch receiver and wired for a portable electric winch.

A label shall be permanently affixed on or near the winch receiver indicating the maximum straight line pull rating of the anchor.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**TRAILER HITCH CLASS IV**

The rear receiver can also be used to pull trailers.

The receiver shall be classified as a Class IV receiver hitch with a 2.00 inch (50.80 mm) hitch box opening.

The maximum towing capacity shall be 7500 pounds (3400 kg) with a tongue weight of 750 pounds (340 kg) or 12000 pounds (5443 kg) towing capacity with an approved distributed trailer load.

**2" BALL MOUNT AND 1 7/8" BALL**

A ball mount for a 2" receiver tube and a 1-7/8" chrome ball shall be provided with the apparatus. A pin and clip shall also be included to fixture the ball mount into the receiver.

**TRAILER 12 VOLT RECEPTACLE**

A 6-pin, 12V trailer receptacle shall be supplied adjacent to the receiver tube and wired for trailer lights.

**FRONT RECEIVER**

A rescue winch receiver shall be installed on the front of the apparatus mounted directly to the chassis frame rails and below the front bumper in the center. The receiver shall have a maximum straight line pull capacity equaling 9000 pounds (4080 kg).

The receiver shall have a 2.00 inch (50.80 mm) square opening for the attachment of a portable rescue winch.

A power receptacle shall be installed adjacent to the rescue winch receiver and wired for a portable electric winch.

A label shall be permanently affixed on or near the winch receiver indicating the maximum straight line pull rating of the anchor.

**LOW-VOLTAGE ELECTRICAL SYSTEM**

The apparatus shall be equipped with a Logic Controlled, Low-Voltage (12v) Electrical System, compliant with the latest revision of the (NFPA) 1901, Standard for Automotive Fire Apparatus.

The system shall be capable of performing total load management, load management sequencing, and load shedding via continuous monitoring of the low-voltage electrical system. In addition, the system shall be capable of switching loads (similar to operating as an emergency warning lamp flasher) eliminating the dependency on many archaic electrical components such as conventional flasher modules. The system shall also incorporate

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

provisions for future expansion or system modification.

The low-voltage electrical system shall be designed to distribute the placement of electrical system hardware throughout the apparatus thereby enabling a smaller, optimized wire harness. The programmable, logic controlled system shall eliminate redundant electrical hardware such as extra harnesses, circuit boards, relays, circuit breakers, and separate electrical or interlock subsystems and associated electronics for controlling various electrical loads and inputs.

As-built electrical system drawings and an apparatus-specific reference of I/O shall be furnished in the final delivery manuals. These drawings shall illustrate the electrical system broken down into separate functions, or small groups of related functions. Drawings shall depict circuit numbers, electrical components and connectors from beginning to end. **A single drawing for all electrical circuits installed by the apparatus manufacturer shall not be accepted.**

### **MULTI-PLEXED ELECTRICAL WARRANTY**

A four (4) year limited (V-MUX) multiplex system warranty, of Weldon Technologies, Inc.; shall be provided by the apparatus manufacture for parts and labor, while under normal use and service; against mechanical, electrical and physical defects from the date of installation.

The warranty shall exclude; sensors, shunt interface modules, serial or USB kits, transceivers, cameras, GPS, and electrical display screens, which shall be limited to a period of one (1) year repair parts and labor from the date of installation.

### **NODE**

An electrical distribution node or relay shall be installed in the below locations of the apparatus body.

The pump node shall be mounted as high as practical in the full depth portion of the right front compartment.

The rear body nodes shall be mounted as high and as far rearward as practical on the back wall of the rearmost compartment.

A protective cover shall be installed to prevent damage to the node or electrical system during equipment installation and or removal. Node covers shall be approximately 16.00 to 22.00 inches in length with an inspection hole positioned for view of the node indicator LED lights. The finish of the cover shall match the compartments interior finish. Node covers will not include any type of shelve mounting structure and shall limit the height of unistrut or shelf height within the compartments.

### **PERIMETER LIGHTS LOCATION**

There shall be four (4) underbody perimeter lights installed on the apparatus positioned to provide illumination to the immediate ground area around the unit.

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

One (1) under each side of the pumphouse running boards and two (2) under the rear tailboard.

**PERIMETER LIGHTS**

The underbody perimeter lights provided will be TecNiq model T44 series, 4" round, 8 diode LED lights.

**PERIMETER LIGHTS ACTIVATION**

The perimeter lights under the body shall illuminate the area with the activation of the chassis ground lights.

**UPPER LIGHTING PACKAGE**

The following NFPA lighting package, manufactured by Whelen, shall be supplied and installed in the upper areas of the vehicle.

**UPPER ZONE B&D-FORWARD:**

There shall be two (2) Whelen model M9 series LED lights with chrome bezels provided and installed with the apparatus.

There shall be one (1) each side of the body in the upper forward corners.

**SIDE WARNING LIGHTS FLASH**

The upper side lights shall feature multiple flash patterns including steady burn.

NO Low Intensity Flash Pattern

**SIDE WARNING LIGHTS COLOR**

The upper warning lights mounted on the side positions shall be red with red lenses.

**UPPER ZONE B&D-REAR:**

There shall be two (2) Whelen model M9 series LED lights with chrome bezels provided and installed with the apparatus.

There shall be one (1) each side of the body in the upper rear corners.

**SIDE WARNING LIGHTS FLASH**

The upper side lights shall feature multiple flash patterns including steady burn.

NO Low Intensity Flash Pattern

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>SIDE WARNING LIGHTS COLOR</u></b></p> <p>The upper warning lights mounted on the side positions shall be red with red lenses.</p> <p><b><u>UPPER ZONE C:</u></b></p> <p>There shall be two (2) Whelen model M9 series LED lights with chrome bezels, one (1) each side, provided and installed with the apparatus.</p> <p><b><u>REAR WARNING LIGHTS FLASH</u></b></p> <p>The rear upper lights shall feature multiple flash patterns including steady burn.</p> <p>NO Low Intensity Flash Pattern</p> <p><b><u>REAR WARNING LIGHTS COLOR</u></b></p> <p>The upper warning lights mounted at the rear shall be red with red lenses.</p> <p><b><u>AUXILIARY UPPER ZONE C:</u></b></p> <p>There shall be two (2) Whelen model M9 series LED lights with chrome bezels, one (1) each side, provided and installed with the apparatus.</p> <p><b><u>REAR WARNING LIGHTS FLASH</u></b></p> <p>The rear upper lights shall feature multiple flash patterns including steady burn.</p> <p>NO Low Intensity Flash Pattern</p> <p><b><u>REAR WARNING LIGHTS COLOR</u></b></p> <p>The upper warning lights mounted at the rear shall be red with red lenses.</p> <p><b><u>UPPER REAR WARNING LIGHT SWITCH E-MASTER/SECONDARY ROCKER</u></b></p> <p>The upper rear warning lights shall be controlled through the master warning switch and a secondary rear warning rocker switch located on the control switch panel in the cab. The switches shall be clearly labeled for ease of identification.</p> <p><b><u>LOWER LED WARNING LIGHTING</u></b></p> <p>The following NFPA lighting package, manufactured by Whelen, shall be supplied and installed in the lower areas of the vehicle.</p>		
139		

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>LOWER ZONE B&amp;D:</u></b></p> <p>There shall be four (4) Whelen model M6 series LED lights with chrome bezels, two (2) each side, provided and installed with the apparatus.</p> <p><b><u>SIDE WARNING LIGHTS FLASH</u></b></p> <p>The lower side lights shall feature multiple flash patterns including steady burn.</p> <p>NO Low Intensity Flash Pattern</p> <p><b><u>SIDE WARNING LIGHTS COLOR</u></b></p> <p>The lower side warning lights mounted on the side positions shall be red with red lenses.</p> <p><b><u>SIDE WARNING LIGHTS LOCATION</u></b></p> <p>The warning lights on the side of the apparatus shall be mounted at the pump panel location and at the rear tailboard location.</p> <p><b><u>LOWER ZONES B&amp;D CAST ALUMINUM ANGLED LIGHT HOUSING</u></b></p> <p>A cast aluminum angled light housing shall be used for the rearmost warning light in zones B&amp;D to ensure the light is mounted as far rearward as possible on the tailboard.</p> <p><b><u>LOWER SIDE WARNING LIGHT SWITCH E-MASTER/VISTA</u></b></p> <p>The lower side warning lights shall be controlled through the master warning switch and a secondary side warning switch located on the Vista display control screen. The switches shall be clearly labeled for ease of identification.</p> <p><b><u>LOWER ZONE C:</u></b></p> <p>There shall be two (2) Whelen model M6 series Super-LED lights with chrome bezels, one (1) each side, on provided and installed on the rear of the body.</p> <p><b><u>REAR WARNING LIGHTS FLASH</u></b></p> <p>The lower rear lights shall feature multiple flash patterns including steady burn.</p> <p>NO Low Intensity Flash Pattern</p> <p><b><u>REAR WARNING LIGHTS COLOR</u></b></p> <p>The lower rear warning lights mounted at the rear shall be red with red lenses.</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes    No**

**LOWER REAR WARNING LIGHT SWITCH E-MASTER/VISTA**

The lower rear warning lights shall be controlled through the master warning switch and a secondary rear warning switch located on the Vista display control screen. The switches shall be clearly labeled for ease of identification.

**LED REAR TAILLIGHT ASSEMBLY**

There shall be Whelen M6-Series Super LED rear taillight assemblies provided and installed with the apparatus, one (1) each side at the rear.

The following shall be installed in the order as specified from top to bottom:

- One (1) M62BTT LED red brake light
- One (1) M62T LED series amber turn signal light
- One (1) M62BU LED clear back-up light

**MOUNTING ASSEMBLY**

There shall be Whelen 4-position vertical chrome plated housing provided for each taillight assembly.

The upper most open cavity shall be filled with the specified warning light for the rear of the apparatus.

**REAR TAILLIGHTS COLOR**

The taillights mounted at the rear shall have clear lenses.

**BACKUP LIGHTS**

The backup lights shall illuminate when the apparatus is placed in reverse.

**LED DOT LIGHTING**

There shall be seven (7) lights located on the rear of the apparatus. Three (3) of the lights shall be mounted on the rear of the apparatus center location, for use as identification lamps. Two (2) additional lights shall be located on the rear outboard locations, one (1) each side as high as possible. Two (2) lights shall be mounted on the sides facing the side at the rear corners, for use as clearance lamps.

The lights shall be TecNiq S17 series LED red markers with red lens.



Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>DOT ADDITIONAL MARKER LIGHTS</u></b></p> <p>There shall be two (2) amber LED intermediate marker lights/intermediate turn signals installed in the rub rail, forward of the rear wheel well, one (1) each side.</p> <p>The lights shall be TecNiq S17 series LED amber markers/turn with amber lens.</p> <p><b><u>INTERMEDIATE TURN SIGNALS</u></b></p> <p>The intermediate turn signals will flash with the turn indicators.</p> <p><b><u>REAR VIEW CAMERA LOCATION</u></b></p> <p>A camera shipped loose with the chassis shall be surface mounted at the center location on the rear of the apparatus body for maximum viewing capability. A protective shroud shall be installed over the system to protect against damage.</p> <p><b><u>6 POSITION 12-VOLT POWER FUSE BLOCK</u></b></p> <p>A Blue Sea Systems #5025 Six (6) Circuit ST Blade Fuse Block shall be provided. The fuse panel shall be protected by a 40amp battery direct load.</p> <p>A 6 position Blue Sea Systems fuse block shall be provided in each of the following locations:</p> <p><b><u>ACCESSORY POWER LOCATION</u></b></p> <p>In the chassis cab, within reach of the driver, there shall be accessory power.</p> <p>There shall be a total of one (1) provided.</p> <p><b><u>ACCESSORY POWER LOCATION</u></b></p> <p>In the EMS cabinet, on the right side wall, there shall be accessory power.</p> <p>There shall be a total of one (1) provided.</p> <p><b><u>SIDE SCENE LIGHT LOCATION</u></b></p> <p>There shall be four (4) scene lights installed on the sides of the apparatus, two (2) on each side.</p> <p>One (1) located at the front and one (1) located at the rear corner.</p> <p>The scene lights on the side shall be positioned inboard of the warning lights specified.</p>		

## Fannin County Fire-Rescue

Bidder  
Complies

Yes No

### **SCENE LIGHT MODEL**

Whelen model #M9LZC LED gradient scene lighting with chrome flange shall be surface mounted on the apparatus.

Each light shall offer LED directional lighting from 2 to 40-degrees with internal and external optics. The lamp shall draw 6 amps and generate 6,500 lumens.

### **BODY SIDE SCENE LIGHT ACTIVATION**

The scene lighting shall be activated by two (2) rocker switches installed on the switch panel in the cab and two (2) weather resistant push button switches at the pump operator's panel, one (1) for each side of the apparatus.

The switch shall be labeled as follows:

Left Scene

Right Scene

### **REAR SCENE LIGHT LOCATION**

There shall be two (2) scene lights installed on the rear facing vertical surface of the apparatus, one (1) on each side.

The scene lights on the rear vertical panel shall be positioned far outboard on each side between each set of warning lights specified.

### **SCENE LIGHT MODEL**

Whelen model #M9LZC LED gradient scene lighting with chrome flange shall be surface mounted on the apparatus.

Each light shall offer LED directional lighting from 2 to 40-degrees with internal and external optics. The lamp shall draw 6 amps and generate 6,500 lumens.

### **REAR SCENE LIGHT ACTIVATION**

The rear scene lighting shall be activated when the apparatus transmission is shifted into reverse and by a rocker switch located on the switch panel in the cab and a weather resistant push button switch at the pump operator's panel. The scene shall also be interlocked with the park brake.

The switch shall be labeled as follows:

Rear Scene

Fannin County Fire-Rescue	Bidder Complies	
	Yes	No
<p><b><u>DEALER SUPPLIED/INSTALLED INVERTER</u></b></p> <p>The inverter shall be supplied and installed by the Dealership prior to the truck being placed into service. The apparatus manufacturer shall provide wiring provisions from the chassis batteries to the location specified below. The apparatus manufacture shall also provide any mounting and/or provisions as specified below.</p> <p><b><u>INVERTER L1</u></b></p> <p>The inverter shall be surface mounted in the L1 compartment.</p> <p><b><u>LINE VOLTAGE OUTLETS</u></b></p> <p><b><u>NEMA 5-15 DUPLEX RECEPTACLE(S)</u></b></p> <p>There shall be one (1) type NEMA 5-15 120V/15A duplex receptacle with a cover installed in the below specified location(s).</p> <p><b><u>RECEPTACLE LOCATION</u></b></p> <p>The L3 body compartment shall be equipped with two (2) receptacle(s).</p> <p>The outlet shall be located in the compartment, as outboard as practical on the middle portion of the forward wall.</p> <p>The outlet(s) shall be powered by the shoreline connection or the on-board AC inverter. An automatic transfer switch shall provide power from the shoreline connection when the apparatus is housed at the station or from the inverter when the inverter is engaged/excited.</p> <p><b><u>3M REFLECTIVE STRIPING</u></b></p> <p>There shall be a 4.00 inch (101.60 mm), 3M reflective stripe with two (2) 1.00 inch (25.40 mm) accent stripes applied to the chassis and apparatus body as specified:</p> <p>The above specified Striping shall consist of one color. The provided stripe shall be:</p> <p>reflective stripe white in color.</p> <p><b><u>STRIPE PATTERN</u></b></p> <p>The reflective striping shall be applied around the perimeter of the front of the apparatus in a straight line. In addition, when the stripe reaches the front area of the body, the stripe shall jog in an 'S' shape pattern, then continuing around the rear of the apparatus at a slightly higher level. In the 'S' curve area, the stripe shall be shadowed to give it a three-dimensional look.</p>		

**Fannin County Fire-Rescue**

**Bidder  
Complies**

**Yes No**

**REAR RETRO-REFLECTIVE CHEVRON STRIPING**

A minimum of 50 percent of the rear-facing vertical surface, visible from the rear of the apparatus, shall be equipped with 3M Diamond Grade, retro-reflective striping in a chevron pattern, sloping downward and away from the centerline of the vehicle at an angle of 45-degrees.

The stripe shall be 6.00 inches (152.40 mm) wide alternating in colors.

**CHEVRON COLOR**

The retro-reflective chevron striping shall be red and fluorescent yellow-green in color.

**FIRE DEPARTMENT SUPPLIED LETTERING**

The apparatus lettering shall be provided and installed by the Fire Department after final delivery of the completed apparatus.

**FIRE DEPARTMENT SUPPLIED DECALS**

The apparatus decals shall be provided and installed by the Fire Department after final delivery of the completed apparatus.

**LICENSE PLATE MOUNTING**

A Cast Products, model LP0004-1-B, cast aluminum fully enclosed license plate bracket shall be installed. The bracket shall incorporate a clear LED light (WL0501) to illuminate the license plate and meet DOT requirements.

**LICENSE PLATE BRACKET LOCATION**

The above specified license plate bracket shall be installed at the back of the apparatus on the right side. The bracket shall be mounted to meet all applicable DOT standards.

**MISCELLANEOUS EQUIPMENT**

The following equipment list shall be provided with the completed apparatus.

**WHEEL CHOCKS**

One (1) set of NFPA compliant Ziamatic folding wheel chocks model # SAC-44-E shall be supplied with the apparatus.

**ZICO WHEEL CHOCK MOUNTING BRACKETS**

One (1) set of Ziamatic folding wheel chock underbody horizontal mounts, model # SQCH-44-H, shall be installed on the apparatus under the body in front of the rear wheels on the left side.